

Delaware (DEL) NERR Nutrient Metadata

January 01, 2024 – December 31, 2024

Latest Update: June 06, 2025

Note: This is a provisional metadata document; it has not been authenticated as of its download date. Contents of this document are subject to change throughout the QAQC process and it should not be considered a final record of data documentation until that process is complete. Contact the CDMO (cdmosupport@baruch.sc.edu) or reserve with any additional questions.

I. Data Set and Research Descriptors

1) Principal investigator(s) and contact persons –

a) Reserve Contacts:

Mollie Yacano, Ph.D. (P.I)
Delaware Dept. of Natural Resources & Environmental Control
Division of Coastal, Climate, and Energy, Delaware Coastal Programs
Delaware National Estuarine Research Reserve Program
818 Kitts Hummock Road
Dover, Delaware 19901
Phone: 302-739-6377
e-mail: mollie.yacano@delaware.gov

Michael G. Mensinger
Delaware Dept. of Natural Resources & Environmental Control
Division of Coastal, Climate, and Energy, Delaware Coastal Programs
Delaware National Estuarine Research Reserve Program
818 Kitts Hummock Road
Dover, Delaware 19901
Phone: 302-739-6377
e-mail: mike.mensing@delaware.gov

b) Laboratory Contact:

Laura Lockard (Laboratory Manager)
Delaware Dept. of Natural Resources and Environmental Control
Division of Water Resources – Environmental Laboratory Section
89 Kings Highway Dover, DE 19901
Phone: 302-739-9942
e-mail: lauara.lockard@delaware.gov

Michael G. Mensinger is responsible for the collection, implementation, and data management related to the DNERR nutrient program. Laura Lockard was responsible for sample processing, analyses, and data output for the DNREC Lab.

2) Research objectives –

a) Monthly grab program:

The objective of this monitoring program is to provide baseline information on inorganic nutrient and Chl *a* water quality status in the Delaware NERR while also contributing to baseline information nationally. The six sites chosen for monitoring will assist in understanding the impacts of both urban and agricultural impacts on the watersheds.

b) Diel sampling program:

The objective of this monitoring program is to provide baseline information on inorganic nutrient and Chl *a* water quality status in the Delaware NERR. The diel sampling program attempts to capture a more comprehensive view by assessing fluctuating nutrient amounts throughout a lunar tidal cycle. The site chosen for monitoring will assist in understanding the impacts of both urban and agricultural impacts on the watersheds.

3) Research methods –

a) Monthly grab sampling program

Monthly grab samples are taken at 3 sites in the St. Jones River watershed and 3 sites in the Blackbird watershed: Scotton Landing, Lebanon Landing, Division Street, Blackbird Landing, Beaver Branch (Secondary-SWMP site), and Taylor's Bridge (Secondary-SWMP site). All 6 sites are also equipped with water quality datasondes; water quality data for the primary sites are reported as part of SWMP and are also available at www.nerrsdata.org, water quality data for the secondary SWMP stations are currently considered non-SWMP and only available by contacting the Reserve directly. Please note that Secondary SWMP data in the nutrient/pigment dataset are treated exactly the same as Primary SWMP data.

All grab samples are taken on the same day between +/- 3 hours slack-low tide. No distinction is made between neap and spring tide conditions. Efforts are made to allow for an antecedent dry period of 72 hours prior to sampling, however this was not always possible due to staffing limitations and extensive periods of inclement weather. Sampling events are staggered 30 days apart to the best of the research staff's ability. One grab sample is collected from each station monthly, with triplicate (N=3) samples collected every other month at a randomly chosen station. Samples are collected with a Wildco grab sampler at an approximate depth of 30 cm above the bottom. All samples are collected in wide-mouth, Nalgene sample bottles that were previously acid washed (10%), rinsed (3x) with distilled-deionized water, dried, and rinsed (2x) with ambient water prior to collection of the sample. Samples are immediately placed on ice, in a dark cooler and returned to the laboratory.

Once in the DNERR laboratory, samples are shaken and processed for nutrient and Chl *a* analysis. Sample processing includes the filtration of samples since all analysis took place at the DNREC Lab from January – December 2024. The filtering methods differ between samples for Chl *a* analysis and other nutrient parameter analysis. Chl-*a* processing included filtering 50ml samples through 47 mm Whatman GF/F filter using a vacuum-pump and filter flask apparatus. The Whatman type GF/F is immediately placed in a glass jar, and transported in an ice-filled cooler via car to the DNREC lab upon completion of sample processing. Sample processing for other parameters includes filtering 225ml of a sample through 0.45 µm Millipore filters using a vacuum-pump and a filtering flask apparatus. If samples are extremely dirty a 47mm GF/C filter may be used to filter the sample prior to filtering through the 0.45 µm Millipore filter. The liquid volume of the filtered sample is collected into a Nalgene bottle and transported to the DNREC lab the same day once sample processing is complete. All lab glassware is acid washed (10% HCl) and rinsed (6x) using distilled-deionized water between samples to avoid any contamination. Once at the laboratory, samples are held at 4°C until analyzed. Chl *a* and phaeophytin filters were held at -20°C until extraction.

b) Diel sampling program

Diel samples are collected once a month at Scotton Landing, a site located along the St. Jones River. An ISCO 6700 automated sampler takes samples at 2.5-hour intervals over a 25-hour cycle, thus resulting in 11 samples per event. Diel sampling starts between +/- 3 hours slack-low tide. No distinction is made between neap and spring tide conditions. Efforts are made to allow for an

antecedent dry period of 72 hours prior to starting the sampler, however this was not always possible due to staffing limitations and extensive periods of inclement weather. Sampling events are staggered 30 days apart to the best of the research staff's ability. Samples are collected at an approximate depth of 30 cm from the bottom coinciding with the vertical placement of the data sonde. All samples are collected in wide-mouth, Nalgene sampler bottles that were previously acid washed (10%), rinsed (3x) with distilled-deionized water, and dried. Samples are immediately placed on ice, inside the ice-filled sampler. Samples are processed in the same manner illustrated in the "Monthly Grab Sampling Program" portion of this section.

4) Site location and character –

The Delaware National Estuarine Research Reserve is comprised of two component sites, the St. Jones River and Blackbird Creek components. Both components are located along the Delaware Bay Coast. The St. Jones River Component is located in central Kent County Delaware, east of the state capital city, Dover. The Blackbird Creek component is located in the unincorporated area of Southern New Castle County. There are four sampling sites, three located in the St. Jones component and one in the Blackbird Creek component.

Site name	Scotton Landing
Latitude and longitude	Latitude : 39° 05' 05.9160" N Longitude : 75° 27' 38.1049" W
Tidal range (<i>meters</i>)	1.26
Salinity range (<i>psu</i>)	1-30
Type and amount of freshwater input	The site is influenced by freshwater runoff from the relatively urbanized area upstream
Water depth (<i>meters, MLW</i>)	1.9 - estimated
Sonde distance from bottom (<i>meters</i>)	0.5
Bottom habitat or type	Sediment is clayey silt with no bottom vegetation
Pollutants in area	PCB's, PAH's, and pesticides.
Description of watershed	The St. Jones watershed drainage area is 228.1 km ² (22810 ha) and Scotton Landing's drainage area is 196.2 km ² (19620 ha)

Site name	Blackbird Landing
Latitude and longitude	Latitude : 39° 23' 19.5196" N Longitude : 75° 38' 09.5882" W
Tidal range (<i>meters</i>)	1.12
Salinity range (<i>psu</i>)	0-9
Type and amount of freshwater input	The site is influenced by freshwater runoff from unimpacted forested areas intermixed with agricultural land uses and a small amount of low-density development.

Water depth (<i>meters, MLW</i>)	0.7 estimated
Sonde distance from bottom (<i>meters</i>)	0.5
Bottom habitat or type	The sediment is silty clay with no bottom vegetation.
Pollutants in area	There is very little pollutant presence in the area.
Description of watershed	The Blackbird watershed drainage area is 90.6 km ² (9060 ha) and Blackbird Landing's drainage area is 48.3 km ² (4830 ha).

Site name	Lebanon Landing
Latitude and longitude	Latitude: 39° 06' 51.8" N Longitude: 75° 29' 57.1" W
Tidal range (<i>meters</i>)	1.12
Salinity range (<i>psu</i>)	0-28
Type and amount of freshwater input	The site is influenced by freshwater runoff from the relatively urbanized area upstream.
Water depth (<i>meters, MLW</i>)	2.1 - estimated
Sonde distance from bottom (<i>meters</i>)	0.5
Bottom habitat or type	The sediment is clayey silt with no bottom vegetation.
Pollutants in area	PCB's, PAH's, and pesticides.
Description of watershed	The St. Jones watershed drainage area is 228.1 km ² (22810 ha) and Lebanon Landing's drainage area is 171.6 km ² (17160 ha).

Site name	Division Street
Latitude and longitude	Latitude : 39° 09' 49.4" N Longitude : 75° 31' 08.7" W
Tidal range (<i>meters</i>)	Not applicable, freshwater
Salinity range (<i>psu</i>)	0.1
Type and amount of freshwater input	The site is fresh water and is influenced by urban freshwater runoff.
Water depth (<i>meters, MLW</i>)	Non-tidal site
Sonde distance from bottom (<i>meters</i>)	0.5
Bottom habitat or type	The sediment is clayey silt with no bottom vegetation.
Pollutants in area	PCB's, PAH's, and pesticides

Description of watershed	The St. Jones watershed drainage area is 228.1 km ² (22810 ha) and Division Street's drainage area is 81.2 km ² (8120 ha).
--------------------------	--

All Delaware NERR historical nutrient/pigment monitoring stations:

Station Code	SWMP Status	Station Name	Location	Active Dates	Reason Decommissioned	Notes
delblnut	P	Blackbird Landing	39° 23' 19.54 N, 75° 38' 9.60 W	01/01/2002 - current	NA	NA
deldsnut	P	Division Street	39° 9' 49.32 N, 75° 31' 8.76 W	01/01/2002 - current	NA	NA
delllnut	P	Lebanon Landing	39° 6' 51.84 N, 75° 29' 57.12 W	01/01/2002 - current	NA	NA
delslnut	P	Scotton Landing	39° 5' 5.93 N, 75° 27' 38.09 W	01/01/2002 - current	NA	NA
delbbnut	S	Beaver Branch	39° 24' 8.64 N, 75° 37' 40.80 W	02/01/2002 - current	NA	NA
deltbnut	S	Taylor's Bridge	39° 24' 17.6 N, 75° 35' 58.4 W	01/01/2007 - current	NA	NA

5) Coded variable definitions –

Each individual sample is given a 3-part name code in addition to other codes. The 3 part name code, “delslnut” for example, gives the reserve name (del = Delaware), station name (sl = Scotton Landing, etc.), and SWMP program code (nut = nutrient monitoring program).

Sampling Site Codes:

delslnut = Delaware Reserve nutrient data for Scotton Landing
delblnut = Delaware Reserve nutrient data for Blackbird Landing
delllnut = Delaware Reserve nutrient data for Lebanon Landing
deldsnut = Delaware Reserve nutrient data for Division Street
delbbnut = Delaware Reserve nutrient data for Beaver Branch
deltbnut = Delaware Reserve nutrient data for Taylors Bridge

The monitoring codes are set as “1” to indicate grab samples and “2” to indicate diel samples. Replicates are also given specific codes. Grab samples in which triplicates sample are taken utilize a “1” for the first sample, a “2” for the second sample, and a “3” for the third sample. Diel samples are always labeled with a “1” since only one sample is taken at each 2.5-hour interval.

6) Data collection period –

SWMP nutrient monitoring via grab samples and diel samples began in 2002 at Scotton Landing, Lebanon Landing, Division Street, Blackbird Landing, and Beaver Branch. Taylors Bridge was added as a nutrient and water quality monitoring station in 2008.

Grab Sampling (All times in EST)

Site: **SL**

Sample date	Rep 1	Rep 2	Rep 3
01/23/2024	4:22		
02/12/2024	6:34		
03/04/2024	6:33		
04/08/2024	4:27	4:31	4:34
05/07/2024	4:09		
06/24/2024	6:07	6:10	6:14
07/22/2024	5:20		
08/20/2024	5:56		
09/03/2024	4:11		
10/22/2024	4:10		
11/04/2024	5:19		
12/03/2024	5:34		

Site: **LL**

Sample date	Rep 1	Rep 2	Rep 3
01/23/2024	4:36		
02/12/2024	6:47	6:49	6:51
03/04/2024	6:43		
04/08/2024	4:43		
05/07/2024	4:21		
06/24/2024	6:24		
07/22/2024	5:31		
08/20/2024	6:07		
09/03/2024	4:23		
10/22/2024	4:21		
11/04/2024	5:31		
12/03/2024	5:47		

Site: **DS**

Sample date	Rep 1	Rep 2	Rep 3
01/23/2024	4:50		
02/12/2024	7:05		
03/04/2024	6:57		
04/08/2024	4:57		
05/07/2024	4:34		
06/24/2024	6:37		
07/22/2024	5:46		
08/20/2024	6:19		
09/03/2024	4:35		
10/22/2024	4:35		
11/04/2024	5:44		
12/03/2024	6:01		

Site: **BL**

Sample date	Rep 1	Rep 2	Rep 3
-------------	-------	-------	-------

01/23/2024	6:18		
02/12/2024	8:40		
03/04/2024	8:13		
04/08/2024	6:37		
05/07/2024	5:43		
06/24/2024	7:57		
07/22/2024	7:13		
08/20/2024	6:49		
09/03/2024	6:09		
10/22/2024	5:07	5:09	5:11
11/04/2024	6:53		
12/03/2024	7:17		

Site: **BB**

Sample date	Rep 1	Rep 2	Rep 3
01/23/2024	6:26		
02/12/2024	8:48		
03/04/2024	8:19		
04/08/2024	6:47		
05/07/2024	5:50		
06/24/2024	8:05		
07/22/2024	7:20		
08/20/2024	6:57	6:59	7:02
09/03/2024	6:16		
10/22/2024	5:19		
11/04/2024	6:59		
12/03/2024	7:24		

Site: **TB**

Sample date	Rep 1	Rep 2	Rep 3
01/23/2024	6:35		
02/12/2024	8:56		
03/04/2024	8:26		
04/08/2024	6:54		
05/07/2024	5:57		
06/24/2024	8:13		
07/22/2024	7:27		
08/20/2024	7:09		
09/03/2024	6:24		
10/22/2024	5:26		
11/04/2024	7:07		
12/03/2024	7:34	7:36	7:38

Diel Sampling (All times in EST)

Site: **SL**

Start Date	Start Time	End Date	End Time
01/08/2024	5:30	01/09/2024	6:30
02/26/2024	7:00	02/27/2024	8:00
03/04/2024	6:30	03/05/2024	7:30
04/22/2024	5:00	04/23/2024	6:00
05/13/2024	7:00	05/14/2024	8:00

06/24/2024	6:00	06/25/2024	7:00
07/08/2024	5:30	07/09/2024	6:30
08/05/2024	5:00	08/06/2024	6:00
09/09/2024	5:30	09/10/2024	6:30
10/07/2024	6:30	10/08/2024	7:30
11/05/2024	5:00	11/06/2024	6:00
12/09/2024	9:00	12/10/2024	10:00

7) Associated researchers and projects–

The DEL NERR water quality monitoring program occurs at the corresponding nutrient sample sites. A Xylem/YSI EXO datasonde is deployed at each site measuring: dissolved oxygen, salinity, water temperature, water level, turbidity, and pH. Weather data is collected in both the St. Jones River and Blackbird Creek watershed near nutrient/water quality sites as another portion of the NERRS SWMP program. Water quality data from the St. Jones River sites (Scotton Landing, Lebanon Landing, and Division Street), Blackbird Creek (Blackbird Landing), and meteorological data from the St. Jones station are available at www.nerrsdata.org. One additional St. Jones River water quality station (Aspen Landing), two additional Blackbird Creek water quality stations (Beaver Branch & Taylors Bridge), and Blackbird Creek meteorological data are available from Reserve staff. Contact Michael G. Mensinger at mike.mensinger@delaware.gov with data inquiries pertaining to these additional sites.

8) Distribution –

NOAA retains the right to analyze, synthesize and publish summaries of the NERRS System-wide Monitoring Program data. The NERRS retains the right to be fully credited for having collected and process the data. Following academic courtesy standards, the NERR site where the data were collected should be contacted and fully acknowledged in any subsequent publications in which any part of the data are used. The data set enclosed within this package/transmission is only as good as the quality assurance and quality control procedures outlined by the enclosed metadata reporting statement. The user bears all responsibility for its subsequent use/misuse in any further analyses or comparisons. The Federal government does not assume liability to the Recipient or third persons, nor will the Federal government reimburse or indemnify the Recipient for its liability due to any losses resulting in any way from the use of this data.

Requested citation format:

NOAA National Estuarine Research Reserve System (NERRS). System-wide Monitoring Program. Data accessed from the NOAA NERRS Centralized Data Management Office website: www.nerrsdata.org; *accessed* 12 October 2024.

NERR nutrient data and metadata can be obtained from the Research Coordinator at the individual NERR site (please see Principal investigators and contact persons), from the Data Manager at the Centralized Data Management Office (please see personnel directory under the general information link on the CDMO home page) and online at the CDMO home page www.nerrsdata.org. Data are available in comma separated version format.

II. Physical Structure Descriptors

9) Entry verification –

Nutrient data are entered into a Microsoft Excel worksheet and processed using the NutrientQAQC Excel macro. The NutrientQAQC macro sets up the data worksheet, metadata worksheets, and MDL worksheet; adds chosen parameters and facilitates data entry; allows the user to set the number of significant figures to be reported for each parameter and rounds using banker's rounding rules; allows the user to input MDL values and then automatically flags/codes measured values below MDL and inserts the MDL; calculates parameters chosen by the user and automatically flags/codes for component values below MDL, negative calculated values, and missing data; allows the user to apply QAQC flags and codes to the data; produces summary statistics; graphs selected parameters for review; and exports the resulting data file to the CDMO for tertiary QAQC and assimilation into the CDMO's authoritative online database.

Michael G. Mensinger is also responsible for all data entry and QA/QC procedures related to the Delaware NERR dataset. The original Excel files received from ELS are archived on the State of Delaware server. Edited files containing additional calculated parameters are archived on the State of Delaware server and sent to the CDMO for additional archiving.

10) Parameter titles and variable names by category –

Required NOAA/NERRS System-wide Monitoring Program nutrient parameters are denoted by an asterisks “*”.

Data Category	Parameter	Variable Name	Units of Measure
Phosphorus and Nitrogen:			
	*Orthophosphate, Filtered	PO4F	mg/L as P
	*Ammonium, Filtered	NH4F	mg/L as N
	*Nitrite, Filtered	NO2F	mg/L as N
	*Nitrate, Filtered	NO3F	mg/L as N
	*Nitrite + Nitrate, Filtered	NO23F	mg/L as N
	Dissolved Inorganic Nitrogen	DIN	mg/L as N
Plant Pigments:			
	*Chlorophyll a	CHLA_N	µg/L
	Phaeophytin	PHEA	µg/L
Other Lab Parameters:			
	Silicate, Filtered	SiO4F	mg/L as SI

Notes:

1. Time is coded based on a 2400 clock and is referenced to Standard Time.
2. Reserves have the option of measuring either NO2 and NO3 or they may substitute NO23 for individual analyses if they can show that NO2 is a minor component relative to NO3.

11) Measured or calculated laboratory parameters –

a) Parameters measured directly

Nitrogen species:	NH4F, NO2F, NO23F
Phosphorus species:	PO4F
Other:	CHLA_N, PHEA, SiO4F

b) **Calculated parameters**

NO3F

NO23F-NO2F

DIN

NO23F+NH4F

12) Limits of detection –

Method detection limits (MDLs) are revisited annually in accordance with federal guidelines contained in 40 CFR Appendix B to Part 136—Definition and Procedure for the Determination of the Method Detection Limit—Revision 2 unless otherwise specified or defined by the analytical method or program. The MDL procedure now uses method blanks to calculate an MDL, in addition to the spiked samples that have always been used to calculate the MDL. As a result, the new definition of the MDL is: "The method detection limit (MDL) is defined as the minimum measured concentration of a substance that can be reported with 99% confidence that the measured concentration is distinguishable from method blank results." The value calculated from the spiked samples is called the MDLS. The MDLS calculation is the same as the MDL calculation in Revision 1.11. The method blank samples are used to calculate the MDLb, which is a very similar calculation that also calculates the 99% confidence level that the result is derived from the sample rather than from contamination/noise. The MDL is the higher of the two values (either the MDLS calculated using spiked samples or the MDLb calculated using method blanks). EPA considers this change important because as detector sensitivity improves, the background contamination of the laboratory, consumable supplies, and equipment can be more important in determining the detection limit than the sensitivity of the instrument. The MDL now requires that the samples used to calculate the MDL are representative of laboratory performance throughout the year, rather than on a single date.

Table 1. DNREC Method Detection Limits (MDL) for measured water quality parameters.

Variable	Method Detection Limit	Dates in Use	Revisited	Comment
NH4F	0.010 mg/L as N	01/01/2024 - 12/31/2024	01/05/2025	
NO2F	0.004 mg/L as N	01/01/2021 - 12/31/2024	01/05/2025	
PO4F	0.004 mg/L as P	01/01/2024 - 12/31/2024	01/05/2025	
NO23F	0.010 mg/L as N	01/01/2024 - 12/31/2024	01/05/2025	MDL updated based on annual verification per EOPA "Definition and Procedure for the Determination of the Method Detection Limit, Revision 2"
SiO4F	1.0 mg/L SiO4*	01/01/2024 - 12/31/2024		*Data are reported to the LOQ (lowest calibration standard) 1.0 mg/L. In general, reported results are > 1.0 mg/L. MDL determinations are not required when reporting to the lowest calibration standard.
CHLA_N	0.50 µg/L	01/01/2024 - 12/31/2024	8/26/2016	EPA 445 Method defined as estimated detection limit (EDL) established during initial demonstration of capability and verified each run by method blanks
PHEA	0.50 µg/L	01/01/2024 - 12/31/2024	8/26/2016	EPA 445 Method defined as estimated detection limit (EDL) established during initial demonstration of capability and verified each run by method blanks

13) Laboratory methods –

Delaware Department of Natural Resources & Environmental Control – Division of Water Resources –
Environmental Laboratory Section Laboratory

i) **Parameter: Orthophosphate**

Method References:

USEPA Method 365.1 Revision 2.0 Determination of Phosphorus by Semi-Automated Colorimetry. *Methods for Chemical Analysis of Water and Wastes*; U.S. Environmental Protection Agency, Office of Research and Development, Environmental Monitoring and Support Laboratory: Cincinnati, OH, 1993

OI Analytical Low-Level Orthophosphate by Segmented Flow Analysis (SFA)

Method Descriptor:

Instrumentation: OI Analytical Flow Solution IV with WinFLOW software

Ammonium molybdate and antimony potassium tartrate react in a sulfuric acid environment to form an antimony-phospho-molybdo complex, which is reduced to a blue colored complex by ascorbic acid. Reaction is heat catalyzed at 40°C and measured colorimetrically at 880nm. The range is 0.01-0.2mg/L.

Preservation Method:

250ml of a sample is filtered through 0.45 µm Millipore filters using a vacuum-pump and a filtering flask apparatus. The liquid volume of the filtered sample is collected into a HDPE bottle, cooled to <6°C, and delivered to the ELS within 24 hours.

ii) **Parameter: Nitrite**

Method References:

USEPA Method 353.2, Revision 2.0: Nitrogen, Nitrate-Nitrite (Colorimetric, Automated, Cadmium Reduction). *Methods for Chemical Analysis of Water and Wastes*; U.S. Environmental Protection Agency, Office of Research and Development, Environmental Monitoring and Support Laboratory: Cincinnati, OH, 1993.

OI Analytical Nitrite determination by Segmented Flow Analysis (SFA)

Method Descriptor:

Instrumentation: OI Analytical Flow Solution IV with WinFLOW software

The nitrite is determined by diazotizing with sulfanilamide and coupling with N-(1-naphthyl)-ethylenediamine dihydrochloride at pH 2.0 to 2.5 to form a reddish-purple azo dye. The absorbance of the colored azo dye is quantitatively measured at 540 nm. The range is 0.008 to 0.500 mg/L. Higher concentrations may be quantified by diluting the sample.

Preservation Method:

250ml of a sample is filtered through 0.45 µm Millipore filters using a vacuum-pump and a filtering flask apparatus. The liquid volume of the filtered sample is collected into an HDPE bottle, cooled to <6°C, and delivered to the ELS within 24 hours.

iii) **Parameter: Nitrate + Nitrite**

Method References:

USEPA Method 353.2, and Method 353.2 LL (Low Level) Revision 2.0: Nitrogen, Nitrate-Nitrite (Colorimetric, Automated, Cadmium Reduction). *Methods for Chemical Analysis of Water and Wastes*; U.S. Environmental Protection Agency, Office of Research and Development, Environmental Monitoring and Support Laboratory: Cincinnati, OH, 1993.

OI Analytical Nitrate/Nitrite determination by Segmented Flow Analysis (SFA)

Method Descriptor:

Instrumentation: OI Analytical Flow Solution IV with WinFLOW software

Nitrate is reduced quantitatively to nitrite by cadmium metal. The nitrite formed; in addition to any nitrite originally present in the sample is determined by diazotizing with sulfanilamide and coupling with N-(1-naphthyl)-ethylenediamine dihydrochloride at pH 2.0 to 2.5 to form a reddish-purple azo dye. The

absorbance of the colored azo dye is quantitatively measured at 540 nm. Separate, rather than combined nitrate-nitrite, values are readily obtained by carrying out the procedure first with, and then without, the Cu-Cd reduction step. The range is 0.108 to 0.500 mg/L. The Low Level range is 0.01 to 0.2 mg/L.

Preservation Method:

250ml of a sample is filtered through 0.45 µm Millipore filters using a vacuum-pump and a filtering flask apparatus. The liquid volume of the filtered sample is collected into a HDPE bottle, cooled to <6°C, and delivered to the ELS within 24 hours.

iv) **Parameter: Ammonia**

Method References:

USEPA method 350.1 Revision 2.0: determination of Ammonia Nitrogen by Semi-Automated Colorimetry. *Methods for Chemical Analysis of Water and Wastes*; U.S. Environmental Protection Agency, Office of Research and Development, Environmental Monitoring and Support Laboratory: Cincinnati, OH, 1993

Method Descriptor:

Instrumentation: SEAL AA3 flow autoanalyzer.

The sample is buffered at a pH of 9.5 with a borate buffer in order to decrease hydrolysis of cyanates and organic nitrogen compounds and is mixed into a solution of boric acid. Alkaline phenol and hypochlorite react with ammonia to form indophenol blue that is proportional to the ammonia concentration. The blue color formed is intensified with sodium nitroprusside and measured colorimetrically. The range is 0.02 to 1.0 mg/L.

Preservation Method:

250ml of a sample is filtered through 0.45 µm Millipore filters using a vacuum-pump and a filtering flask apparatus. The liquid volume of the filtered sample is collected into an HDPE bottle, cooled to <6°C, and delivered to the ELS within 24 hours. The pH is adjusted to <2 with sulfuric acid.

v) **Parameter: Chlorophyll and Pheophytin**

Method References:

Trilogy Laboratory Fluorometer Operating Manual. Version 1.2. September 15, 2010. Turner Designs, 845 West Maude Avenue, Sunnyvale, CA 94086.

USEPA Method 445.0. In Vitro Determination of Chlorophyll a and Pheophytin a in Marine and Freshwater Algae by Fluorescence. Turner Designs Application Notes, Chlorophyll and Pheophytin March 24 2008. Turner Designs, 845 West Maude Avenue, Sunnyvale, CA 94086.

Method Descriptor:

Instrumentation: Turner Designs Trilogy fluorometer.

Chlorophyll-containing phytoplankton in a measured volume of sample water is concentrated by filtering through a glass fiber filter. The pigments are extracted from the phytoplankton in a DMSO/Acetone solution because this solution has a greater extraction efficiency than Acetone alone. Conversion of chlorophyll to pheophytin is carried out by acidification of the sample. Typically, 50-100 ml of water is filtered. The concentration in the water sample is reported in units of µg/L. Range is 0.5 to 200 µg/L

Preservation Method:

A 100ml sample is filtered through a 47mm Whatman GF/F filters using a vacuum-pump and filter flask apparatus. The Whatman type GF/F filter is placed in a clean wide-mouth glass sample jar, protected from light exposure, cooled to <6°C and delivered to the ELS within 24 hours. Filters are stored at ELS at -20°C until extraction.

vi) **Parameter: Silicate**

Method References:

Standard Methods for the Examination of Water and Wastewater, Method 4500-SiO₂C-1997. Automated Method for Molybdate-Reactive Silica.

Method Descriptor:

Instrumentation: SEAL AQ2 Discrete autoanalyzer.

This analysis is used for the determination of reactive silica, often referred to as molybdate-reactive silica. It includes mainly monomeric and dimeric silica acids and silicate. Under acidic conditions molybdate-reactive silica combines with ammonium molybdate to form a yellow molybdo-silica acid complex. The absorbance of the final product is measured spectrophotometrically at 405 nm. The applicable range is 0.25 to 25 mg/L.

Preservation Method:

250ml of a sample is filtered through 0.45 µm Millipore filters using a vacuum-pump and a filtering flask apparatus. The liquid volume of the filtered sample is collected into an HDPE bottle, cooled to <6°C, and delivered to the ELS within 24 hours.

14) Field and laboratory QAQC programs –

a) Precision

- i) **Field variability** – True field replicates are taken at a single site every other month during grab sampling. The two replicates are successive grabs. Sample #1 (XXXXXX-G1) is taken and the sampler emptied. The grab sampler is deployed once again to acquire sample #2 (XXXXXX-G2), and then again for replicate #3 (XXXXXX-G3). During months when replicates are not taken, a single sample is collected from each site.
- ii) **Laboratory Variability** – see charts below
- iii) **Inter-organizational splits** – none

b) Accuracy

- i) **Sample spikes** – see charts below.
- ii) **Standard reference material analysis** – see charts below
- iii) **Cross calibration exercises** – none

Information for DNREC Lab:

Nitrate-Nitrite & Nitrite

Quality Control Checks	Criteria	Frequency
Quantitative limit	0.005 mg/L	On SOP approval
Initial Calibration	$r \geq 0.995$ minimum 3 standards $\%D \leq$	A valid initial calibration is required for sample analysis initially and verified every 6 months.
Continuing Calibration Verification/CCVI	$\%D \leq 10\%$	With each analytical batch; at the beginning and end of the run and after every 10 samples.
Method Detection Limit (MDL)	A MDL must be achieved prior to the practice of this procedure.	Once prior to the use of this procedure with semi-annual verification.
Initial Demonstration of Capability (IDOC)	Precision $\leq 10\%$ Recovery (X) between 80-120%	Each analyst prior to analyzing (preparing) samples by this procedure.
Continuous Demonstration of Capability (DOC)	Acceptable performance on a PE or blind sample.	Each analyst annually.
Laboratory Blank (Method Blank)	< 0.005 mg/L	Each analytical batch
Standard Reference Material / Quality Control Sample	Percent Recovery between 90-110% $\pm 10\%$	Each analytical batch
Duplicate	$\% RPD \leq 30\%$.	Each analytical batch of 10 or less samples

Orthophosphate

Quality Control Checks	Criteria	Frequency
Initial Calibration	$r \geq 0.995$	A valid initial calibration is required for sample analysis.
Continuing Calibration Verification	$\%D \leq 25\%$ at the reporting limit $\%D \leq 10\%$ for all other levels	Immediately following daily calibration, after every 10% of samples and at the end of the run.
Initial Demonstration of Capability (IDOC) Initial Precision and Recovery (IPR)	Precision $\leq 10\%$ Recovery (X) between 90-110%	Each analyst prior to analyzing (preparing) samples by this procedure.
Continuous Demonstration of Capability (DOC) Laboratory Blank (Method Blank)	Acceptable performance on a PE or blind sample.	Each analyst annually.
Method Detection Limit (MDL)	Follow procedure in the Quality Manual.	Once prior to the use of this procedure and verified annually.
Laboratory Blank (Method Blank)	$< MDL$	Each analytical batch of 20 or less samples.
Matrix Spike (MS) and Matrix Spike Duplicate (MSD)	Recovery 90-110%	Each analytical batch of 10 or less samples.
Duplicate (sample duplicate or matrix spike duplicate)	$\%RPD \leq 20\%$.	Each analytical batch of 10 or less samples.
Laboratory Control Sample (LCS)	Recovery 90-110%	Each analytical batch of 20 or less samples

Chlorophyll-a & Pheophytin

Quality Control Checks	Criteria	Frequency
Initial Demonstration of Capability (IDOC)	Four aliquots of an environmental sample are extracted and analyzed. Average recovery 90-110% (compared to an experienced analyst extracting and analyzing four aliquots of the same sample). $\%RSD \leq 20\%$.	Each analyst upon completion of training.
On-going Demonstration of Capability (DOC)	Acceptable performance on a PE or blind sample. Recovery 75-125%.	Each analyst annually.
Method Blank	$\leq 0.2 \mu\text{g l}^{-1}$	Analyze one extracted blank with each batch of 20 samples.
Duplicate	$\% RPD \leq 20\%$	As required by project/customer
Laboratory Control Sample (LCS) and LCSD	$\% \text{ recovery} = 80-120\%$ $\% RPD \leq 10\%$	Each analytical batch of 20 environmental samples.
Matrix Spike and Matrix Spike Duplicate	$\% \text{ Recovery} = 75-125\%$ $\%RPD \leq 20\%$	As required by the Customer, contract or QAPP.
Calibration Verification	$\% \text{ recovery} = 90-110\%$	Analysis of solid standards (high and low) at the start of each analytical run.
Instrument Calibration	Follow manufacturer recommendations. Calibrate with high ($\sim 200 \mu\text{g l}^{-1}$) secondary standard. Check calibration with low ($\sim 20 \mu\text{g l}^{-1}$) secondary standard (criteria $100 \pm 10\%$) $\% \text{ Recovery of Standards} \leq 10\%$ of true value.	Whenever lamp, filter or photomultiplier has been changed. When QC no longer meets acceptance criteria, or when instrument maintenance is required.

Silica

Quality Control Checks	Criteria
Initial Calibration	0.995 regression or better
Continuing Calibration Verification (CCVB)	±20% - 80%-120%
Method Detection Limit (MDL)	A MDL must be achieved prior to the practice of this procedure.
Initial Demonstration of Capability (IDOC)	Precision $\leq$ 10% Recovery (X) between 80-120%
Continuous Demonstration of Capability (DOC)	Acceptable performance on a PE or blind sample.
Matrix Spike and Matrix Spike Duplicate Recovery (MS & MSD)	%RPD(s) $\leq$ 20 % Recovery (X) between 80-120 %
Laboratory Blank (Method Blank)	< 0.10 mg/L (< MDL)
Laboratory Control Sample Laboratory Control Sample Duplicate	This check standard is a commercial standard with a certified value and acceptance limits. The standard will vary each time it is purchased. Please refer the current Certificate of Analysis.

15) QAQC flag definitions –

QAQC flags provide documentation of the data and are applied to individual data points by insertion into the parameter's associated flag column (header preceded by an F_). QAQC flags are applied to the nutrient data during secondary QAQC to indicate data that are out of sensor range low (-4), rejected due to QAQC checks (-3), missing (-2), optional and were not collected (-1), suspect (1), and that have been corrected (5). All remaining data are flagged as having passed initial QAQC checks (0) when the data are uploaded and assimilated into the CDMO ODIS as provisional plus data. The historical data flag (4) is used to indicate data that were submitted to the CDMO prior to the initiation of secondary QAQC flags and codes (and the use of the automated primary QAQC system for WQ and MET data). This flag is only present in historical data that are exported from the CDMO ODIS.

- 4 Outside Low Sensor Range
- 3 Data Rejected due to QAQC
- 2 Missing Data
- 1 Optional SWMP Supported Parameter
- 0 Data Passed Initial QAQC Checks
- 1 Suspect Data
- 4 Historical Data: Pre-Auto QAQC
- 5 Corrected Data

16) QAQC code definitions –

QAQC codes are used in conjunction with QAQC flags to provide further documentation of the data and are also applied by insertion into the associated flag column. There are three (3) different code categories, general, sensor, and comment. General errors document general problems with the sample or sample collection, sensor errors document common sensor or parameter specific problems, and comment codes are used to further document conditions or a problem with the data. Only one general or sensor error and one comment code can be applied to a particular data point. However, a record flag column (F_Record) in the nutrient data allows multiple comment codes to be applied to the entire data record.

General errors

- GCM Calculated value could not be determined due to missing data
- GCR Calculated value could not be determined due to rejected data
- GDM Data missing or sample never collected

GQD	Data rejected due to QA/QC checks
GQS	Data suspect due to QA/QC checks
GSM	See metadata

Sensor errors

SBL	Value below minimum limit of method detection
SCB	Calculated value could not be determined due to a below MDL component
SCC	Calculation with this component resulted in a negative value
SNV	Calculated value is negative
SRD	Replicate values differ substantially
SUL	Value above upper limit of method detection

Parameter Comments

CAB	Algal bloom
CDR	Sample diluted and rerun
CHB	Sample held beyond specified holding time
CIP	Ice present in sample vicinity
CIF	Flotsam present in sample vicinity
CLE	Sample collected later/earlier than scheduled
CRE	Significant rain event
CSM	See metadata
CUS	Lab analysis from unpreserved sample

Record comments

CAB	Algal bloom
CHB	Sample held beyond specified holding time
CIP	Ice present in sample vicinity
CIF	Flotsam present in sample vicinity
CLE	Sample collected later/earlier than scheduled
CRE	Significant rain event
CSM	See metadata
CUS	Lab analysis from unpreserved sample

Cloud cover

CCL	clear (0-10%)
CSP	scattered to partly cloudy (10-50%)
CPB	partly to broken (50-90%)
COC	overcast (>90%)
CFY	foggy
CHY	hazy
CCC	cloud (no percentage)

Precipitation

PNP	none
PDR	drizzle
PLR	light rain
PHR	heavy rain
PSQ	squally
PFQ	frozen precipitation (sleet/snow/freezing rain)
PSR	mixed rain and snow

Tide stage

TSE	ebb tide
TSF	flood tide
TSH	high tide
TSL	low tide

Wave height

WH0	0 to <0.1 meters
WH1	0.1 to 0.3 meters
WH2	0.3 to 0.6 meters
WH3	0.6 to > 1.0 meters
WH4	1.0 to 1.3 meters
WH5	1.3 or greater meters
<i>Wind direction</i>	
N	from the north
NNE	from the north northeast
NE	from the northeast
ENE	from the east northeast
E	from the east
ESE	from the east southeast
SE	from the southeast
SSE	from the south southeast
S	from the south
SSW	from the south southwest
SW	from the southwest
WSW	from the west southwest
W	from the west
WNW	from the west northwest
NW	from the northwest
NNW	from the north northwest
<i>Wind speed</i>	
WS0	0 to 1 knot
WS1	> 1 to 10 knots
WS2	> 10 to 20 knots
WS3	> 20 to 30 knots
WS4	> 30 to 40 knots
WS5	> 40 knots

17) Other remarks/notes –

Data may be missing due to problems with sample collection or processing. Laboratories in the NERR System submit data that are censored at a lower detection rate limit, called the Method Detection Limit or MDL. MDLs for specific parameters are listed in the Laboratory Methods and Detection Limits Section (Section II, Part 12) of this document. Concentrations that are less than this limit are censored with the use of a QAQC flag and code, and the reported value is the method detection limit itself rather than a measured value. For example, if the measured concentration of NO₂3F was 0.0005 mg/l as N (MDL=0.0008), the reported value would be 0.0008 and would be flagged as out of sensor range low (-4) and coded SBL. In addition, if any of the components used to calculate a variable are below the MDL, the calculated variable is removed and flagged/coded -4 SCB. If a calculated value is negative, it is rejected and all measured components are marked suspect. If additional information on MDL's or missing, suspect, or rejected data is needed, contact the Research Coordinator at the reserve submitting the data.

Note: The way below MDL values are handled in the NERRS SWMP dataset was changed in November of 2011. Previously, below MDL data from 2007-2010 were also flagged/coded, but either reported as the measured value or a blank cell. Any 2007-2011 nutrient/pigment data downloaded from the CDMO prior to November of 2011 will reflect this difference.

Notes for <CSM> “See Metadata Code” usage with nutrient data; LOQ refers to the lowest calibration standard:

1. The Beaver Branch PO4F value (0.017 mg/L) from the 01/23/2024 (06:26 EST) grab sample is likely underestimated due to the matrix effect.
2. The Taylors Bridge NH4F value (0.320) from the 01/23/2024 (06:35 EST) grab sample is suspect because it is outside of the typical annual range.
3. The Division Street NO2F value (0.009 mg/L) from the 01/23/2024 (04:50 EST) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
4. The Blackbird Landing NO2F value (0.007 mg/L) from the 01/23/2024 (06:18 EST) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
5. The Division Street NH4F value (0.013 mg/L) from the 03/04/2024 (06:57 EST) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
6. The Division Street NO2F value (0.009 mg/L) from the 03/04/2024 (06:57 EST) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
7. The Blackbird Landing NO2F value (0.009 mg/L) from the 03/04/2024 (08:13 EST) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
8. The Beaver Branch NO2F value (0.005 mg/L) from the 03/04/2024 (08:19 EST) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
9. The Scotton Landing PO4F value (0.009 mg/L) from the 03/05/2024 (07:30 EST) diel sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
10. The Scotton Landing NH4F value (0.045 mg/L) from the 03/05/2024 (07:30 EST) diel sample is likely overestimated due to the matrix effect.
11. The Division Street NO2F value (0.007 mg/L) from the 04/08/2024 (04:57 EST) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
12. The Blackbird Landing NO2F value (0.006 mg/L) from the 04/08/2024 (06:37 EST) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
13. The Beaver Branch NO2F value (0.004 mg/L) from the 04/08/2024 (06:47 EST) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
14. The Taylors Bridge NO2F value (0.006 mg/L) from the 04/08/2024 (06:54 EST) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).

15. The Scotton Landing PO₄F value (0.005 mg/L) from the 04/22/2024 (05:00 EST) diel sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
16. The Scotton Landing NH₄F value (0.018 mg/L) from the 04/22/2024 (17:30 EST) diel sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
17. The Division Street PO₄F value (0.004 mg/L) from the 05/07/2024 (04:34 EST) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
18. The Division Street NH₄F value (0.015 mg/L) from the 05/07/2024 (04:34 EST) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
19. The Beaver Branch NO₂F value (0.006 mg/L) from the 05/07/2024 (05:50 EST) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
20. The Taylors Bridge NO₂F value (0.005 mg/L) from the 05/07/2024 (05:57 EST) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
21. The Scotton Landing PO₄F value (0.006 mg/L) from the 05/13/2024 (12:00 EST) diel sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
22. The Scotton Landing PO₄F value (0.006 mg/L) from the 05/14/2024 (03:00 EST) diel sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
23. The Scotton Landing NH₄F value (0.015 mg/L) from the 05/13/2024 (19:30 EST) diel sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
24. The Scotton Landing NO₂F values (0.008, 0.008, 0.009, 0.008, 0.008 and 0.009 mg/L) from the 05/13/2024 (09:30, 12:00, 17:00, 19:30, 22:00 EST) and 05/14/2023 (08:00 EST) diel samples are estimated since the concentrations are below the range for accurate quantitation (>MDL, but <LOQ).
25. The Scotton Landing SiO₄F value (0.7 mg/L) from the 05/14/2024 (03:00 EST) diel sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
26. The Division Street NH₄F value (0.431) from the 06/24/2024 (06:37 EST) grab sample is suspect because it is outside of the typical annual range.
27. The Taylors Bridge NO₂F value (0.005 mg/L) from the 06/24/2024 (08:13 EST) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).

28. The Scotton Landing NH₄F value (0.016 mg/L) from the 06/24/2024 (06:00 EST) diel sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
29. The Scotton Landing NO₂F values (0.006, 0.008 and 0.005 mg/L) from the 06/24/2024 (06:00 and 23:30 EST) and 06/25/2024 (02:00 EST) diel samples are estimated since the concentrations are below the range for accurate quantitation (>MDL, but <LOQ).
30. The Scotton Landing NO₂3F values (0.028 and 0.021 mg/L) from the 06/24/2024 (06:00 EST) and 06/25/2024 (02:00 EST) diel samples are estimated since the concentrations are below the range for accurate quantitation (>MDL, but <LOQ).
31. The Scotton Landing PO₄F values (0.063, 0.013, 0.053 and 0.088 mg/L) from the 07/08/2024 (15:30 EST) and 07/09/2024 (01:30, 04:00, and 06:30 EST) diel samples are estimated since the concentrations are below the range for accurate quantitation (>MDL, but <LOQ).
32. The Scotton Landing NH₄F value (0.017 mg/L) from the 07/09/2024 (01:30 EST) diel sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
33. The Scotton Landing NO₂F value (0.009 mg/L) from the 07/09/2024 (04:00 EST) diel sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
34. The Scotton Landing SiO₄F value (0.4 mg/L) from the 07/09/2024 (01:30 EST) diel sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
35. The Scotton Landing NO₂3F value (0.024 mg/L) from the 08/06/2024 (01:00 EST) diel sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
36. The Division Street PO₄F value (0.005 mg/L) from the 08/20/2024 (06:19 EST) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
37. The Division Street NO₂F value (0.006 mg/L) from the 08/20/2024 (06:19 EST) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
38. The Beaver Branch NO₂F values (0.005, 0.005 and 0.006 mg/L) from the 08/20/2024 (06:57, 06:59 and 07:02 EST) grab samples are estimated since the concentrations are below the range for accurate quantitation (>MDL, but <LOQ).
39. The Blackbird Landing NH₄F value (0.016 mg/L) from the 09/03/2024 (06:09 EST) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
40. The Taylors Bridge NH₄F value (0.018 mg/L) from the 09/03/2024 (06:24 EST) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).

41. The Lebanon Landing NO₂F value (0.008 mg/L) from the 09/03/2024 (04:23 EST) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
42. The Taylors Bridge NO₂F value (0.007 mg/L) from the 09/03/2024 (06:24 EST) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
43. The Beaver Branch NH₄F value (0.023 mg/L) from the 09/03/2024 (06:16 EST) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
44. The Scotton Landing PO₄F value (0.612 mg/L) from the 09/09/2024 (18:00 EST) diel sample was rejected because the high standard is only 0.2 mg/L. The sample was not rerun for dilution at the lab since the value was noticed after the hold time was exceeded.
45. Scotton Landing NO₂F values (0.008 and 0.005 mg/L) from the 09/09/2024 (05:30 and 15:30 EST) diel samples are estimated since the concentrations are below the range for accurate quantitation (>MDL, but <LOQ).
46. Scotton Landing NO₂F values (0.009, 0.008, 0.007 and 0.007 mg/L) from the 10/07/2024 (06:30, 09:00 and 21:30 EST) and 10/08/2024 (07:30 EST) diel samples are estimated since the concentrations are below the range for accurate quantitation (>MDL, but <LOQ).
47. The Beaver Branch NH₄F value (0.019 mg/L) from the 10/22/2024 (05:19) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
48. The Lebanon Landing NO₂F value (0.009 mg/L) from the 10/22/2024 (04:21) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
49. The Blackbird Landing NO₂F value (0.005 mg/L) from the 10/22/2024 (05:09) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
50. The Taylors Bridge NO₂F value (0.0005 mg/L) from the 10/22/2024 (05:26) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
51. The Lebanon Landing NO₂F value (0.004 mg/L) from the 11/04/2024 (05:31) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
52. The Blackbird Landing NO₂3F value (0.024 mg/L) from the 11/04/2024 (06:53) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
53. The Beaver Branch NH₄F value (0.306) from the 11/04/2024 (06:59 EST) grab sample is suspect because it is outside of the typical annual range.
54. The Scotton Landing NO₂F value (0.012 mg/L) from the 11/06/2024 (03:30 EST) diel sample is likely underestimated due to the matrix effect.

55. The Division Street PO4F value (0.007 mg/L) from the 12/03/2024 (06:01) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
56. The Division Street NO2F value (0.005 mg/L) from the 12/03/2024 (06:01) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
57. The Blackbird Landing NO2F value (0.005 mg/L) from the 12/03/2024 (07:17) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
58. The Beaver Branch NH4F value (0.444) from the 12/03/2024 (07:24 EST) grab sample is suspect because it is outside of the typical annual range.
59. The Beaver Branch NO2F value (0.005 mg/L) from the 12/03/2024 (07:24) grab sample is estimated since the concentration is below the range for accurate quantitation (>MDL, but <LOQ).
60. The Taylors Bridge NO2F values (0.005, 0.005 and 0.005 mg/L) from the 12/03/2024 (07:34, 07:36 and 07:38) grab samples (G1, G2 and G3) are estimated since the concentrations are below the range for accurate quantitation (>MDL, but <LOQ).
61. Scotton Landing NO2F values (0.005, 0.006, 0.005, 0.005 and 0.009 mg/L) from the 12/09/2024 (16:30 and 19:00 EST) and 12/10/2024 (05:00, 07:30 and 10:00 EST) diel samples are estimated since the concentrations are below the range for accurate quantitation (>MDL, but <LOQ).

Major rain/storm events (near or exceeding 25.4 mm (1 inch) of rainfall) during 2024 took place on the following dates (data originate from the Delaware NERR St. Jones meteorological station):

January 06, 2024	(33.8 mm)
January 09, 2024	(53.1 mm)
January 28, 2024	(34.3 mm)
March 02, 2024	(37.8 mm)
March 06, 2024	(42.2 mm)
March 23, 2024	(52.6 mm)
April 01, 2024	(27.7 mm)
April 02, 2024	(22.9 mm)
April 03, 2024	(22.9 mm)
June 30, 2024	(73.4 mm)
July 12, 2024	(44.2 mm)
July 13, 2024	(31.5 mm)
July 16, 2024	(39.4 mm)
July 24, 2024	(52.6 mm)
November 20, 2024	(22.6 mm)
December 11, 2024	(36.3 mm)

Sample hold times for 2024: Nutrient samples are held at 4°C (samples for NH4F and NO23F are acidified) and CHLA_N and PHEA are held at -20°C. NERRS SOP allows nutrient samples to be held for up to 24 hours if held at 4°C with no preservation, for NH4F and NO23F up to 28 days if acidified and held at 4°C, and up to 28 days (CHLA for 30 days) if held at -20°C plus allows for up to 5 days for collecting, processing, and shipping samples. Samples held beyond that time period are flagged suspect <1> and coded (CHB). If measured values were below MDL, this resulted in <-4>

[SBL] (CHB) flagging/coding. Tier II parameters, with a few exceptions, are subject to the same sample hold times. In all cases, up to an additional 5 days is allowed for collecting, processing, and shipping samples. Samples held beyond that time period (indicated below by an asterisk*) are flagged suspect and coded CHB in the data set. Analysis dates for individual parameters are provided in the below table:

Sample Type	Sample Date/Time (EST)	PO4F	NH4F	NO2F	NO23F	CHLA/PHEA	SiO4F
Diel	01/08-09/2024 (all)	01/09/2024	01/16/2024	01/09/2024	01/16/2024	01/23/2024	01/23/2024*
Grab	01/23/2024 (all)	01/24/2024	01/26/2024	01/23/2024	01/31/2024	01/23/2024	01/23/2024
Grab	02/12/2024 (all)	02/13/2024	02/13/2024	02/13/2024	02/15/2024	02/19/2024	02/19/2024*
Diel	02/26-27/2024 (all)	02/27/2024	03/01/2024	02/27/2024	02/29/2024	02/27/2024	02/27/2024
Grab	03/04/2024 (all)	03/05/2024	03/08/2024	03/05/2024	03/07/2024	03/11/2024	03/12/2024*
Diel	03/04/2024 (06:30-21:30), 03/05/2024 (00:00-02:30)	03/05/2024	03/08/2024	03/05/2024	03/07/2024	03/11/2024	03/12/2024*
Diel	03/05/2024 (05:00-07:30)	03/05/2024	03/25/2024	03/05/2024	03/07/2024	03/11/2024	03/12/2024*
Grab	04/08/2024 (all)	04/10/2024	04/12/2024	04/10/2024	04/11/2024	04/15/2024	04/15/2024*
Diel	04/22-23/2024 (all)	04/23/2024	04/24/2024	04/23/2024	04/24/2024	04/30/2024	04/24/2024
Grab	05/07/2024 (all)	05/08/2024	05/14/2024	05/08/2024	05/14/2024	05/15/2024	05/14/2024*
Diel	05/07-08/2024 (all)	05/14/2024	05/21/2024	05/14/2024	05/21/2024	05/15/2024	05/15/2024*
Grab	06/24/2024 (all)	06/25/2024	07/01/2024	06/25/2024	07/01/2024	06/25/2024	06/25/2024
Diel	06/24-25/2024 (all)	06/25/2024	07/01/2024	06/25/2024	07/01/2024	06/25/2024	06/25/2024
Diel	07/08-09/2024 (all)	07/09/2024	07/11/2024	07/09/2024	07/11/2024	07/23/2024	07/22/2024*
Grab	07/22/2024 (all)	07/24/2024	07/25/2024	07/24/2024	07/25/2024	07/23/2024	07/22/2024
Diel	08/05/2024 (05:00-12:30)	08/06/2024	08/08/2024	08/06/2024	08/08/2024	08/13/2024	08/06/2024
Diel	08/05/2024 (15:00-22:30) 08/06/2024 (01:00-06:00)	08/06/2024	08/08/2024	08/06/2024	08/08/2024	08/13/2024	08/16/2024*
Grab	08/20/2024 (all)	08/21/2024	08/23/2024	08/21/2024	08/23/2024	08/27/2024	08/23/2024
Grab	09/03/2024 (all)	09/03/2024	09/06/2024	09/04/2024	09/06/2024	09/16/2024	09/17/2024*
Diel	09/09-10/2024 (all)	09/10/2024	09/13/2024	09/10/2024	09/13/2024	09/16/2024	09/17/2024*
Diel	10/07-08/2024 (all)	10/08/2024	10/10/2024	10/08/2024	10/10/2024	10/08/2024	10/14/2024
Grab	10/22/2024 (all)	10/23/2024	10/25/2024	10/23/2024	10/25/2024	10/28/2024	10/22/2024
Grab	11/04/2024 (all)	11/04/2024	11/08/2024	11/04/2024	11/08/2024	11/12/2024	11/15/2024*
Diel	11/05-06/2024 (all)	11/06/2024	11/08/2024	11/06/2024	11/08/2024	11/12/2024	11/15/2024*
Grab	12/03/2024 (all)	12/04/2024	12/06/2024	12/04/2024	12/06/2024	12/11/2024	12/13/2024*
Diel	12/09-10/2024 (all)	12/10/2024	12/13/2024	12/10/2024	12/13/2024	12/11/2024	12/13/2024