

Hudson River (HUD) NERR Meteorological Metadata
January 2007 - December 2007
Latest Update: July 29, 2009

I. Data Set & Research Descriptors

1. Principal Investigator: Sarah H. Fernald, Research Coordinator

Contact Persons:

Sarah H. Fernald, Research Coordinator, email: shfernal@gw.dec.state.ny.us

Address:

Hudson River NERR
Norrie Point Environmental Center
PO Box 315
256 Norrie Point Way
Staatsburg, NY 12580
Phone: 845-889-4745 x111
Fax: 845-889-4749

2. Entry verification:

Data are uploaded from the CR1000 (CR10X until 1/18/2007) data logger to a Personal Computer (IBM compatible). Files are exported from PC208W or LoggerNet in a comma-delimited format and uploaded to the CDMO where they undergo automated primary QAQC and become part of the CDMO's online provisional database. During primary QAQC, data are flagged if they are missing or out of sensor range. The edited file is then returned to the Reserve where it is opened in Microsoft Excel and processed using the CDMO's NERRQAQC Excel macro. The macro inserts station codes, creates metadata worksheets for flagged data, and graphs the data for review. It allows the user to apply QAQC flags and codes to the data, append files, and export the resulting data file to the CDMO for tertiary QAQC and assimilation into the CDMO's authoritative online database. For more information on QAQC flags and QAQC codes, see Sections 11 and 12.

The Research Coordinator is responsible for data management and data entry verification.

3. Research objectives:

The objective of this study is to monitor the meteorological conditions at the Tivoli Bays component site of the Hudson River National Estuarine Research Reserve. Measurements of air temperature, relative humidity, barometric pressure, precipitation, photosynthetically active radiation, and wind speed and direction are taken throughout the year at the Tivoli Bays Field Station. A water quality-monitoring program has been ongoing since 1991 at this component site, and the meteorological data will help provide ancillary data. This will help us to better understand the relationships between the atmospheric conditions and aquatic environments at this site.

4. Research methods:

For routine maintenance, sensors are investigated at least once a month to ensure there is no damage or blockage to the sensors. According to Campbell Scientific, sensors are to be calibrated every two 2 years for proper data collection. After that time, the sensors are removed from the tower, and shipped to their respective manufacturers for proper and professional calibration. In order to avoid missing data, a second set of sensors is calibrated and available to be installed on the tower to continue data collection

For data collection, the CR1000 datalogger is programmed to collect data in the following formats:

- i) 15-minute data are averages of 5-second readings for Air Temperature ($^{\circ}\text{C}$), Relative Humidity (%), Barometric Pressure (mb), Wind Speed (m/s), and Average Battery Voltage (Volts).
- ii) 15-minute data are totals of 15-minute readings for Total Precipitation (mm) and Total Photosynthetically Active Radiation (PAR) (mmoles/m^2).

Data are backed-up to a PC file appended hourly via serial connection to the CR1000. The data are downloaded and pre-processed as described in Section 2. QA/QC flags are applied on the following anomalous data criteria:

Air Temperature:

-Sample not greater than 45 C or less than 5 C

Relative Humidity:

-Sample not greater than 100% or less than 0%

Pressure:

-Pressure greater than 1060 mb or less than 900 mb

Wind Speed:

-Wind speed greater than 30 m/s

Wind Direction:

-Wind direction not greater than 360 degrees or less than 0 degrees

Rainfall:

-Precipitation not greater than 25 cm in 15 min

Photosynthetically Active Radiation (PAR)

-Sample not greater than 5000 mmol/m^2 or less than 0 mmol/m^2

Time:

-15-minute interval recorded

Campbell Scientific data telemetry equipment was installed at the field station on 11/14/2005 at 16:30 and transmits data to the NOAA GOES satellite, NESDIS ID #3B00B4F4. The transmissions are scheduled hourly and contain four (4) data sets reflecting fifteen minute data sampling intervals. Upon receipt by the CDMO, the data undergoes the same automated primary QAQC process detailed in Section 2 above. The “real-time” telemetry data become part of the

provisional dataset until undergoing secondary and tertiary QAQC and assimilation in the CDMO's authoritative online database. Provisional and authoritative data are available at <http://cdmo.baruch.sc.edu>.

5. Site location and character:

The Hudson River National Estuarine Research Reserve (HUDNERR) is a multi-component site totaling approximately 5,000 acres. Each component of the reserve is referenced by River Mile (RM) of the Hudson River in New York State proceeding north from the southern tip of Manhattan (RM 0). The reserve includes the following four component sites: Piermont Marsh, Rockland County (RM 24)(41°02'30"N 73°54'15"W), Iona Island, Rockland County (RM 45)(41°18'15"N 73°58'45"W), Tivoli Bays, Dutchess County (RM 98)(42°02'15"N 73°55'10"W), and Stockport Flats, Columbia County (RM 124)(42°02'30"N 73°46'00"W). The four component sites include open water, tidal wetland, and adjacent upland buffer habitats and are representative of the diverse plant and animal communities that occupy the salinity gradient within the Hudson River Estuary. Development within the watersheds of the four component sites ranges from predominantly urban/suburban to forested/agricultural.

The weather station (FS) is located at the Tivoli Bays component site in Annandale, NY (42°01'05.46"N 73°55'01.13"W). A 30 foot, aluminum tower is used to elevate some of the weather monitoring equipment. The tower is on the deck of an office building, on the west side, 9 feet off the ground. The wind anemometer, wind speed, and light sensors are located at the top of the tower, 39 feet off the ground. The datalogger and the barometric pressure sensor are enclosed within a fiberglass case attached to the tower, 12 feet off the ground. A heated rain gauge is next to the tower, attached to the building, 16 feet off the ground. The temperature/humidity sensor is next to the tower, attached to the deck handrail, 12 feet off the ground. GOES telemetry equipment includes a larger solar panel and battery, a larger enclosure to house the battery, a Campbell TX-312 transmitter, associated GPS for time synchronization and a Yagi antenna.

Although trees surround the area, the tree line begins approximately 60 feet from the tower in most directions. The trees are at similar heights to the tower, but the sensors are not shaded at that location. The tower is approximately 1.2 miles Southeast of the Tivoli South Bay water quality monitoring station, 2.3 miles Southeast of the Tivoli North Bay water quality monitoring station, and 0.2 miles Northwest of the Saw Kill Creek water quality monitoring station.

6. Data collection period:

Weather data have been collected at the Field Station at Tivoli Bays since July 1999. Weather data were collected for the entire year in 2007 from January 1 00:00 through December 31 23:45.

7. Distribution:

According to the Ocean and Coastal Resource Management Data Dissemination Policy for the NERRS System-wide Monitoring Program, NOAA/ERD retains the right to analyze, synthesize and publish summaries of the NERRS System-wide Monitoring Program data. The PI retains the right to be fully credited for having collected and processed the data. Following academic courtesy standards, the PI and NERR site where the data were collected will be contacted and fully acknowledged in any subsequent publications in which any part of the data are used. Manuscripts

resulting from the NOAA/OCRM supported research that are produced for publication in open literature, including refereed scientific journals, will acknowledge that the research was conducted under an award from the Estuarine Reserves Division, Office of Ocean and Coastal Resource Management, National Ocean Service, National Oceanic and Atmospheric Administration. The data set enclosed within this package/transmission is only as good as the quality assurance/quality control procedures outlined by the enclosed metadata reporting statement. The user bears all responsibility for its subsequent use/misuse in any further analyses or comparisons. The Federal government does not assume liability to the Recipient or third persons, nor will the Federal government reimburse or indemnify the Recipient for its liability due to any losses resulting in any way from the use of this data.

NERR weather data and metadata can be obtained from the Research Coordinator at the individual NERR site (please see Section 1 Principal investigators and contact persons), from the Data Manager at the Centralized Data Management Office (please see personnel directory under the general information link on the CDMO home page) and online at the CDMO home page <http://cdmo.baruch.sc.edu/>. Data are available in comma separated format.

8. Associated researchers and projects:

The Hudson River NERR water quality-monitoring program examines the physical and chemical constituents of the tributary waters and the tidal waters of the freshwater tidal marshes at the Tivoli Bays component site. Measurements include seston, dissolved oxygen, alkalinity, pH, temperature, salinity, conductivity, and concentrations of nitrate, phosphate, sulfate, and chloride. These data are used to identify long-term trends and to determine the relationship between meteorological conditions and the aquatic environments at this site.

Associated researchers working at the Tivoli Bays component site include scientists from the Cary Institute of Ecosystem Studies in Millbrook, NY, Yale School of Forestry and Environmental Studies in New Haven, CT, Bard College, Annandale-on-Hudson, NY, Simon's Rock College, Great Barrington, MA, Cornell University Center for the Environment, Cornell Institute for Resource Systems, Cornell Department of Natural Resources, Ithaca, NY, State University of New York College of Environmental Science and Forestry, Syracuse, NY and Rensselaer Polytechnic Institute in Troy, NY.

II. Physical Structure Descriptors

9. Sensor specifications, operating range, accuracy, date of last calibration:

Parameter: Temperature

Units: Celsius

Sensor type: Platinum resistance temperature detector (PRT)

Model #: HMP45C Temperature and Relative Humidity Probe

Operating Temperature: -40°C to +60°C

Range: -40°C to +60°C

Accuracy: ± 0.2 °C @ 20°C

Date of Last calibration: May 9, 2007

Parameter: Relative Humidity

Units: Percent

Sensor type: Vaisala HUMICAP© 180 capacitive relative humidity sensor

Model #: HMP45C Temperature and Relative Humidity Probe
Range: 0-100% non-condensing
Accuracy at 20°C: +/- 2% RH (0-90%) and +/- 3% (90-100%)
Temperature dependence of RH measurement: +/- 0.05% RH/°C
Date of Last calibration: May 9, 2007

Parameter: Barometric Sensor
Units: millibars (mb)
Sensor type: CS-105 Vaisala Barocap © silicon capacitive pressure sensor
Model #: PTB101B
Operating Range: Pressure: 600 to 1060 mb; Temperature: -40°C to +60°C;
Humidity: non-condensing
Accuracy: ± 0.5 mb @ 20°C; +/- 2 mb @ 0°C to 40°C; +/- 4 mb @ -20°C to 45°C; +/- 6 mb @ -40°C to 60°C
Stability: ± 0.1 mb per year
Date of Last calibration: May 9, 2007

Parameter: Wind speed
Units: meter per second (m/s)
Sensor type: 18 cm diameter 4-blade helicoids propeller molded of polypropylene
Model #: R.M. Young 05103 Wind Monitor
Range: 0-60 m/s (130 mph); gust survival 100 m/s (220 mph)
Accuracy: +/- 2%
Date of last calibration: December 6, 2007

Parameter: Wind direction
Units: degrees
Sensor type: balanced vane, 38 cm turning radius
Model #: R.M. Young 05103 Wind Monitor
Range: 360° mechanical, 355° electrical (5° open)
Accuracy: +/- 5%
Date of last calibration: December 6, 2007

Parameter: LI-COR Quantum Sensor
Units: mmols m⁻² (total flux)
Sensor type: High stability silicon photovoltaic detector (blue enhanced)
Model #: LI190SB
Light spectrum waveband: 400 to 700 nm
Temperature dependence: 0.15% per °C maximum
Stability: $<\pm 2\%$ change over 1 yr
Operating Temperature: -40°C to 65°C; Humidity: 0 to 100%
Sensitivity: typically 5 μ A per 1000 μ moles s⁻¹ m⁻²
Date of last calibration: May 9, 2007

Parameter: Precipitation (heated rain gauge)
Units: millimeters (mm)
Sensor type: Tipping Bucket Rain Gauge
Model #: TE525
Rainfall per tip: 0.01 inch
Operating range: Temperature: 0° to +/- 50°C; Humidity: 0 to 100%
Accuracy: +/- 1.0% up to 1 in./hr; +0, -3% from 1 to 2 in./hr; +0, -5% from 2 to 3 in./hr
Date of Last calibration: May 9, 2007

Transmitter

Model #: TX312

On-board memory: Non-volatile flash for setup parameters. 16 Kbytes for data.

Data Transmission Rates: 100, 300 and 1200 BPS

Transmit Power: 5.6 Watts for 100 and 300 bps, 11.2 watts for 1200 bps

Frequency range: 401.701 MHz – 402.09850 MHz

Channel bandwidth: 100/300 BPS 1.5 KHz; 1200 BPS 3 KHz

Time Keeping: Initial setting accuracy: ± 100 microseconds synchronized to GPS; Drift ± 10 milliseconds/day over operating temperature range; GPS scheduled updates are 1 at power up and once per day thereafter. Once every 28 hours required for continual operation.

Operating range: -40° to +60°C; Storage -50° to +70°C; 0-99% RH, non-condensing

Power requirements: 10.8 to 16 VDC, 5 mA during GPS fix and 2.6 Amps during transmission

The CR1000 has 2 MB of Flash EEPROM that is used to store the Operating System. Another 128 K Flash is used to store configuration settings. A minimum of 2 MB SRAM is (4 MB optional upgrade) available for program storage (16K), operating system use, and data storage. Additional storage is available by using a compact flash card in the optional CFM100 Compact Flash Module

Date Installed: January 18, 2007

10. Coded variable indicator and variable code definitions:

Sampling Station:

Field Station at Tivoli Bays

Sampling Site Code:

FS

Station Code:

hudsfsmet

11) QAQC flag definitions

QAQC flags provide documentation of the data and are applied to individual data points by insertion into the parameter's associated flag column (header preceded by an F_). During primary automated QAQC (performed by the CDMO), -5, -4, and -2 flags are applied automatically to indicate data that is above or below sensor range or missing. All remaining data are then flagged 0, as passing initial QAQC checks. During secondary and tertiary QAQC 1, -3, and 5 flags may be used to note data as suspect, rejected due to QAQC, or corrected.

- 5 Outside High Sensor Range
- 4 Outside Low Sensor Range
- 3 Data Rejected due to QAQC
- 2 Missing Data
- 1 Optional SWMP Supported Parameter
- 0 Passed Initial QAQC checks
- 1 Suspect Data
- 2 *Open - reserved for later flag*
- 3 *Open - reserved for later flag*
- 4 Historical Data: Pre-Auto QAQC
- 5 Corrected Data

12) QAQC code definitions

QAQC codes are used in conjunction with QAQC flags to provide further documentation of the data and are also applied by insertion into the associated flag column. There are three (3) different code categories, general, sensor, and comment. General errors document general problems with the deployment or YSI datasonde, sensor errors are sensor specific, and comment codes are used to further document conditions or a problem with the data. Only one general or sensor error and one comment code can be applied to a particular data point.

General Errors

GIM	Instrument Malfunction
GMT	Instrument Maintenance
GPF	Power Failure / Low Battery
GQR	Data Rejected Due to QA/QC Checks
GPR	Program Reload
GPD	Power Down

Sensor Errors

SIC	Incorrect Calibration Constant, Multiplier or Offset
SSN	Not a Number / Unknown Value
SNV	Negative Value
SOC	Out of Calibration
SSM	Sensor Malfunction
SSR	Sensor Removed

Comments

CAF	Acceptable Calibration/Accuracy Error of Sensor
CDF	Data Appear to Fit Conditions
CRE	Significant Rain Event
CSM	See Metadata

13) Other remarks/notes

Small negative PAR values are within range of the sensor and are due to normal errors in the sensor and the CR1000 Datalogger. The Maximum signal noise error for the Licor sensor is +/- 2.214 mmoles/m2 over a 15 minute interval.

Relative Humidity data greater than 100 are within range of the sensor accuracy of +/-3%.

CSM – data coded “See Metadata”

1/18/07 13:00 – 14:15

The weather station was powered down to begin switching the datalogger from a CR10x to a CR1000.

1/19/07 10:15, 12:15 – 13:15

The weather station was powered down to finish switching the datalogger from a CR10x to a CR1000. The PAR multiplier was added at 10:05 with a program reload.

5/9/07 8:45 – 9:15, 10:15, 12:30 – 14:30

The weather station was powered down to replace all probes with newly calibrated ones. The barometric pressure sensor was returned from calibration with the jumper missing, causing an incorrect reading of 600 mb. The rain gauge was calibrated from 12:30 to 14:30, while the station was logging data, so all precipitation values during this time were corrected to 0. The PAR multiplier was added at 10:10 with a program reload.

5/14/07 15:30

The jumper on the barometric pressure sensor was replaced, causing the readings to be correct.

7/10/2007 15:00

A new program was uploaded at 14:50.

10/25/07 20:45-12/6/07 13:45

The weather station was partially destroyed. The guy wire was accidentally caught on the bumper of a truck, which pulled down the upper section of the tower. The wind speed and wind direction sensors were smashed, no longer logging valid data. The fallen section of tower, which remained connected to the base by the wiring, partially blocked the light to the PAR sensor, and the suspect PAR data should be disregarded until the tower's repair. No other sensors were affected, and all other data are considered valid.

12/6/07 9:15 – 13:45

The weather station was powered down to rebuild the tower. Wind direction and PAR data are now considered valid. Wind Speed, however, was incorrectly wired at the top of the tower and not repaired until 1/10/08. Wind speed values should be disregarded for the remainder of 2007.

12/11/07 14:30-14:45

A new program was uploaded, causing a missed reading. The PAR multiplier was not added until 12/17/07 at 10:15. The multiplier was changed, but the program was not reloaded, so only PAR data were rejected.

If additional information on missing data is needed, contact the Research Coordinator at the reserve submitting the data.