Jacques Cousteau (JAC) NERR 2011 Nutrient Metadata

March 2011-December 2011

Latest Update: October 1, 2025

I. Data Set and Research Descriptors

1) Principal investigator(s) and contact persons

a) Reserve contact

Dr. Thomas M. Grothues (Oct 2018-present)
Associate Research Professor
Department of Marine and Coastal Sciences
Research Coordinator, Jacques Cousteau National Estuarine Research Reserve
Director, Rutgers University Marine Field Station
800 c/o 132 Great Bay Blvd.

Tuckerton, NJ 08087 (609) 249-8802

Dr. Michael J. Kennish (former Research Coordinator 2000-2018) Institute of Marine and Coastal Sciences Rutgers University New Brunswick, New Jersey 08901

b) Laboratory contact

Ronald J. Lauck, Jr.
Institute of Marine and Coastal Sciences
Rutgers University
New Brunswick, New Jersey 08901
Phone: 848-932-3410 ext.23410
e-mail: lauck@marine.rutgers.edu

c) Other contacts and programs

Gregg P. Sakowicz
Field Researcher/SWMP Technician
Jacques Cousteau National Estuarine Research Reserve
Rutgers University Marine Field Station
800 Great Bay Blvd.
C/o 132 Great Bay Blvd.
Tuckerton, NJ 08087

Phone: 609-296-5260 ext.267

e-mail: sakowicz@marine.rutgers.edu

2) Research objectives

a) Monthly grab sampling program

Monthly grab samples for the Jacques Cousteau National Estuarine Research Reserve (JAC NERR) are taken along a well-defined salinity gradient of the Mullica River-Great Bay estuarine system. The sites where the samples are taken along this salinity gradient include Lower Bank and Chestnut Neck in the Mullica River and Buoy 126 and Buoy 139 in Great Bay (see site descriptions below). These four sampling sites span a distance of more than 30 km. In addition, a monthly grab sample is taken in Little Egg Harbor estuary at Buoy 115 (see site description below). A major objective of this monitoring program is to determine the nutrient concentrations along the aforementioned salinity gradient over a long-term time series. Previous studies have shown that nitrogen standing stocks in the Mullica River-Great Bay Estuary largely consist of nitrate, ammonium, and nitrogen in organic combination. The nitrogen enters at the head of the estuary largely in inorganic form, but in Great Bay it is transformed mainly to organic combination. However, more data are needed to accurately assess the concentrations of the various nitrogen forms along the salinity gradient, and to determine seasonal variations in the concentrations over a protracted period of several years. It is also necessary to obtain continuous monthly measurements of phosphate, which is also a macronutrient of considerable importance to the system.

Monthly grab samples are needed to obtain accurate measurements of nitrate, ammonium, and phosphate because of their overriding importance to primary production in waters of the JAC NERR. These data can then be compared to chlorophyll *a* measurements to assess their relationship to phytoplankton biomass. A major goal of JAC NERR is to characterize biotic communities along the salinity gradient of the Mullica River-Great Bay Estuary, and it is therefore vital to obtain physical-chemical measurements (including nutrient concentrations) along the gradient. A part of this effort is to determine the nutrient concentrations along the salinity gradient, and how these concentrations are influencing biotic processes downestuary. In addition, a long-term objective of monthly grab sampling is to develop a nutrient (nitrogen) budget for JAC NERR. To develop a budget, data (concentrations) are needed on the various nitrogen species monitored at the SWMP sites as well as data collected on the nitrogen forms associated with atmospheric deposition. An accurate nutrient budget will be useful for analyzing the overall productivity of estuarine waters in the JAC NERR, which will be important to resource managers of the system.

b) Diel sampling program

Diel sampling is conducted via an ISCO automated sampler at Buoy 126 in Great Bay to assess nutrient concentrations and changes in concentrations over tidal cycles. In addition, these data augment monthly grab samples taken at Buoy 126 (see above). It is believed that nutrients entering from the watershed estuary are not utilized within the Mullica River because of the lack of light penetration. The depth of the river and the dark color from the tannins flowing down the river from the Pine Barrens hinder the utilization of these nutrients by planktonic organisms. Where the river empties into the bay, light penetration reaches the bottom and allows utilization of the nutrients by phytoplankton, making this region more productive. Diel sampling over the course of a lunar day at Buoy 126 will also be useful in the development of a nutrient budget for the system.

3) Research methods

a) Monthly grab sampling program

Monthly grab samples were taken at four stations within the Mullica River-Great Bay estuary and at one station in the Little Egg Harbor estuary. Samples were taken at four primary SWMP JAC NEER datasonde stations (Buoy 126, Buoy 139, Chestnut Neck and Lower Bank) and at one station in Little Egg Harbor estuary (Buoy 115), which is considered a secondary SWMP station for nutrient/pigments. Samples were collected at approximately 30-day intervals. Effort was made to obtain grab samples at or before slack low tide conditions (+3 hour before low tide), approximately one month after the previous sampling period. No distinction was made between neap and spring tide conditions. Waterrelated field parameters were measured in situ with a YSI 600 datasonde attached to a YSI 650-MDS handheld unit. Weather-related field parameters were assessed by observation and estimation. Replicate (N=2) samples were collected by hand with a bucket at an approximate depth of 10 cm. All samples were collected in amber, Nalgene, 500 ml sample bottles that were previously acid washed (15% H₂SO₄), rinsed (5x) with distilled-deionized water, and rinsed (1x) with ambient water prior to collection of the sample. Samples were immediately placed on ice in a cooler and returned to the laboratory at the Rutgers Marine Field Station. Once in the laboratory, samples were inverted several times to homogenize the sample and processed for nutrient and Chl a analysis. Samples were then frozen in a -15°C freezer and transported to Rutgers University, IMCS as soon as possible thereafter. The processed samples were then transported to Rutgers University, IMCS and stored in a – 20°C freezer until analyses were performed.

b) Diel sampling program

Monthly diel samples were taken at the principle long-term datasonde station Buoy 126. Samples were collected at approximately 30-day intervals. Sampling occurred during any tidal condition and no distinction was made between spring and neap tide conditions. Twelve samples were collected over a lunar day at 2-hour-and-15-minute intervals using an ISCO auto-sampler. Samples were taken at a fixed depth, approximately 2.0 meters from the bottom. All samples were collected in clear, plastic, 1000 ml ISCO sample bottles. Samples were retrieved as soon as possible after completion of the auto-sampler program. Samples were then transferred from the clear, plastic ISCO bottles to 500 ml amber Nalgene bottles that were previously acid washed (15% H₂SO₄), rinsed (5x) with distilled-deionized water, and rinsed (1x) with ambient water prior to collection of the sample. Samples were immediately placed on ice in a cooler and returned to the laboratory at Rutgers Marine Field Station. Once in the laboratory, samples were inverted several times to homogenize the sample and processed for filtered for nutrient and Chl a analysis. Samples were then frozen in a -15°C freezer and transported to Rutgers University, IMCS as soon as possible thereafter. The filtered samples were then transported to Rutgers University, IMCS and stored in a -20°C freezer until analyses were performed.

4) Site location and character

The Jacques Cousteau National Estuarine Research Reserve (JAC NERR) at Mullica River/Great Bay is located on the northeast coast of the United States on the Atlantic Ocean.

The estuary is near Tuckerton, New Jersey about 14 kilometers north of Atlantic City. There were four active sampling stations in 2009. All four locations can be characterized by having little macroalgae (few to no established beds in the immediate locale; only occasional seasonal and structurally-dependent fouling-type macroalgal communities), fast moving tidal currents, and tidal ranges of approximately 1 m (although this can vary significantly depending on moon phase, storm events, and coastal wind conditions (e.g.- "blow out tides" associated with strong offshore winds). All sites are in a relatively undisturbed area with minimal impact from development or pollution.

- a) Buoy 115 (B5) 39° 31.130' N, 74° 17.230' W- This most recent monitoring site is in Little Egg Harbor Bay, bordering the Edwin B. Forsythe Refuge on Holgate (Long Beach Island) about 3 km northeast of the Rutgers University Marine Field Station. Full-time water-quality monitoring of this non-SWMP station was discontinued in 2003 after ice-floes tore the hardware and housings from the structure, however nutrient/pigment data are still collected at this site which is considered a secondary SWMP NUT station.. The following site description is from 2002 (the more recent year-long dataset); we do not expect this description to differ significantly from present conditions: The depth of the bay at this site is approximately 3 meters. The bottom consists predominantly of sand with little shell or organic material. Salinity values average about 30.8 psu, with a range of 29.3 to 32.5 psu. Groundwater inputs from margins of the estuary, as well as surface flow from Mullica River, account for most of the freshwater entering that affects this site. The input of freshwater from local precipitation and marsh surface runoff is of secondary importance. Flocculent material, possibly decaying alga from up-current (during ebb tides) SAV (submerged aquatic vegetation) beds located in the Little Egg Harbor section of Barnegat Bay, was occasionally observed as flotsam and in the water column during the collection of samples at the B5 sampling station (jacb5nut) and should be considered a characteristic of this sampling station. This site is not monitored via multiparameter datasonde, so no environmental water quality (WO) data beyond what it obtained at the time of nutrient grab sample collection are available for 2011. Estimated tidal range is 2 m.
- **b) Buoy 126 (B6)** 39° 30'28.44"N, 74° 20'18.67"W- located 3 km from Little Egg Inlet on the eastern side of Great Bay and is 100 meters from the nearest land that is a natural marsh island. This is a naturally deep area that has never been dredged, but it is located about 0.5 km from an area in the Intracoastal Waterway that is dredged regularly. The datasonde at this location is attached to Intracoastal Waterway Buoy 126 and is the closest monitoring station to Little Egg Inlet. This site can be characterized by having strong tidal currents, 2-3 knots, fine to coarse sand bottom with an extensive blue mussel bed surrounding the area. Groundwater inputs from margins of the estuary as well as surface flow from Mullica River account for the majority of freshwater coming into the system at this site, followed by input from rainwater from the marsh surface. In 2011, the reported temperature at this station ranged from 4.2°C to 29.0°C, with an average of 16.6°C, but because the sonde was removed for ice-over conditions in early 2011, it is likely that the minimum temperature at this station was closer to 0°C and the average was slightly lower than the aforementioned value. The reported salinity at this station ranged from 18.7 ppt to 31.5 ppt, with an average of 27.7 ppt. It is important to note that fouling may have occasionally depressed some salinity readings and are "flagged" as such in the dataset, so the aforementioned average and range may not be accurate. The maximum tidal range, as recorded by the datasonde, was 2.30 m. It has been some time since the actual depth at this station has been surveyed (sediment deposition and erosion around the structure has effect on the actual

depth of the water column at this station), but in 2008 average depth at the B6 station was assessed at 3.91 m, with a range of 2.72 to 5.09 m. The results of a sonar depth-survey of reserve waters are expected in 2012, and we (the JAC NERR) plan to independently survey the area in the upcoming year as well.

c) Buov 139 (B9) - 39° 29'52.59"N, 74° 22'52.07"W*- is located 4 kilometers from Buov 126 on the western side of Great Bay and is located about 1.0-1.5 km from land. The datasonde at this location is attached to Intracoastal Waterway Buoy 139. The closest landform is an extensive salt marsh approximately 1.5 km wide, which borders the upland area. This area is dredged by the U.S. Army Corp of Engineers approximately every five to six years to maintain the channel at a depth of approximately 2.5 meters. The surrounding depth of the bay is approximately 1.5 to 2 meters. This site is characterized by having maximum currents of about 1.5 knots with a muddy sand bottom and with little structure or shell. Groundwater inputs from margins of the estuary as well as surface flow from Mullica River account for the majority of freshwater coming into the system at this site, followed by input from rainwater from the marsh surface and above. In 2011, the reported temperature at this station ranged from 3.3°C to 29.1°C, with an average of 17.3°C, but because the sonde was removed for ice-over conditions in early 2011, it is likely that the minimum temperature at this station was closer to 0C and the average was slightly lower than the aforementioned value. The reported salinity at this station ranged from 16.6 ppt to 30.8 ppt, with an average of 26.7 ppt. It is important to note that fouling may have occasionally depressed some salinity readings and are "flagged" as such in the dataset, so the aforementioned average and range may not be accurate. The maximum tidal range, as recorded by the datasonde, was 2.92 m. It has been some time since the actual depth at this station has been surveyed (sediment deposition and erosion around the structure has effect on the actual depth of the water column at this station), but in 2008 average depth at the B9 station was assessed at 3.18 m, with a range of 2.13 to 4.55 m. The results of a sonar depth-survey of reserve waters are expected in 2012, and we (the JAC NERR) plan to independently survey the area in the upcoming year as well.

*= these coordinates are a correction to the location reported in past years' metadata reports; the coordinates (39° 29'24.65"N, 74° 22'53.83"W) of the #141 channel marker were attributed to this (#139) channel marker.

d) Chestnut Neck (NE) - 39° 32'52.37"N, 74° 27'38.77"W - located 12 kilometers up the Mullica River from the mouth of the river. The river begins at a line drawn between Graveling Point and Oysterbed Point on the northwestern side of Great Bay. The Mullica River at this location is quite wide, about 250 meters. The datasonde is attached to the dock of a small marina along the southern shore of the river adjacent to the main channel. This location has never been dredged. The site is characterized by having tidal currents of less than one knot, during both ebb and flood tide, and has a mixed organic mud/sand bottom. Freshwater input is primarily from groundwater and watershed runoff. In 2011, the reported temperature at this station ranged from -0.9°C to 30.6°C, with an average of 17.0°C, but because the sonde was removed for ice-over conditions in early 2011, it is likely that the average was slightly lower than the aforementioned value. The reported salinity at this station ranged from 0.97 ppt to 38.85 ppt, with an average of 21.85 ppt. It is important to note that fouling may have occasionally depressed some salinity readings and are "flagged" as such in the dataset, so the aforementioned average and range may not be accurate. The maximum tidal range, as recorded by the datasonde, was 1.92 m. It has been some time since the actual depth at this station has been surveyed (sediment deposition and erosion around the structure has effect on the actual

depth of the water column at this station), but in 2008 average depth at the NE station was assessed at 2.32 m, with a range of 1.11 to 3.45 m. The results of a sonar depth-survey of reserve waters are expected in 2012, and we (the JAC NERR) plan to independently survey the area in the upcoming year as well.

e) Lower Bank (BA) - 39° 35'37.18"N, 74° 33'05.44"W- located 13 kilometers upriver of the Chestnut Neck location. The Mullica River at this site is about 200 m wide. The datasonde is located at the center of a bridge spanning the Mullica River. The northern bank of the river is sparsely developed with single-family houses and has a steep bank about 5 m high. The southern shore has an extensive marsh and fresh water wetland area about 3 km wide. This site can be characterized by having fast tidal currents, just over one knot, deep water, and fine mixed organic mud and sandy sediment. Freshwater input is primarily from groundwater and watershed runoff. In 2011, the reported temperature at this station ranged from -3.4°C to 32.8°C, with an average of 19.0°C, but because the sonde was removed for ice-over conditions in early 2011, it is likely that the minimum temperature at this station was closer to 0°C and the average was slightly lower than the aforementioned value. The reported salinity at this station ranged from 0.07 ppt to 21.16 ppt, with an average of 3.25 ppt. It is important to note that fouling may have occasionally depressed some salinity readings and are "flagged" as such in the dataset, so the aforementioned average and range may not be accurate. The maximum tidal range, as recorded by the datasonde, was 1.91 m. It has been some time since the actual depth at this station has been surveyed (sediment deposition and erosion around the structure has effect on the actual depth of the water column at this station), but in 2008 average depth at the BA station was assessed at 2.77 m, with a range of 1.43 to 3.98 m. The results of a sonar depthsurvey of reserve waters are expected in 2012, and we (the JAC NERR) plan to independently survey the area in the upcoming year as well.

5) Code variable definitions

```
jacb5nut = Jacques Cousteau Reserve nutrient data for Buoy 115
jacb6nut = Jacques Cousteau Reserve nutrient data for Buoy 126
jacb9nut = Jacques Cousteau Reserve nutrient data for Buoy 139
jacnenut = Jacques Cousteau Reserve nutrient data for Chestnut Neck
jacbanut = Jacques Cousteau Reserve nutrient data for Lower Bank
```

The monitoring codes are set as "1" to indicate grab samples and "2" to indicate diel samples. Replicates are also given specific codes. Grab samples in which duplicates sample are taken utilize a "1" for the first sample and a "2" for the second sample. Diel samples are always labeled with a "1" since only one sample is taken at each 2 hr interval.

6) Data collection period

GRAB SAMPLING

Site	Month	Date	Rep1 Time	Rep2 Time
B5	January	*	*	*
B5	February	*	*	*
B5	March	03/29/2011	11:20	11:22

B5 B5 B5 B5 B5 B5 B5 B5	April May June July August September October November December	04/25/2011 05/19/2011 06/03/2011 07/27/2011 08/17/2011 09/19/2011 10/25/2011 11/26/2011 12/12/2011	8:42 15:11 15:01 10:47 14:49 16:42 11:27 15:36 14:46	8:44 15:13 15:03 10:49 14:51 16:44 11:29 15:38 14:48
B6 B6 B6 B6 B6 B6 B6 B6 B6	January February March April May June July August September October November December	* 03/29/2011 04/25/2011 05/19/2011 06/03/2011 07/27/2011 08/17/2011 09/19/2011 10/25/2011 11/26/2011 12/12/2011	* 10:09 8:16 12:31 14:49 10:57 14:37 16:28 10:48 15:27 14:10	* 10:11 8:18 12:33 14:51 10:59 14:39 16:30 10:50 15:29 14:12
B9 B9 B9 B9 B9 B9 B9 B9 B9	January February March April May June July August September October November December	* 03/29/2011 04/25/2011 05/19/2011 06/03/2011 07/27/2011 08/17/2011 09/19/2011 10/25/2011 11/26/2011 12/12/2011	* 9:59 8:03 14:52 14:37 11:06 14:25 16:18 11:07 15:16 14:27	* 10:01 8:05 14:54 14:39 11:08 14:27 16:20 11:09 15:18 14:29
NE NE NE NE NE NE NE NE NE	April May	* 03/29/2011 04/25/2011 05/19/2011 06/03/2011 07/27/2011 08/17/2011 09/19/2011 10/25/2011 11/26/2011 12/12/2011	* 13:26 10:10 16:04 16:20 12:47 16:25 18:04 14:52 16:32 15:47	* 13:28 10:12 16:06 16:22 12:49 16:27 18:06 14:54 16:34 15:49

BA January	*	*	*
BA February	*	*	*
BA March	03/29/2011	14:02	14:04
BA April	04/25/2011	10:50	10:52
BA May	05/19/2011	16:33	16:35
BA June	06/03/2011	16:46	16:48
BA July	07/27/2011	13:17	13:19
BA August	08/17/2011	16:50	16:52
BA September	09/19/2011	18:31	18:33
BA October	10/25/2011	15:25	15:27
BA November	11/26/2011	16:37	16:39
BA December	12/12/2011	16:21	16:23

^{*=} no sample collected due to winter/ice-over conditions

DIEL (ISCO) SAMPLING

Site Month	Start Date	Start Time	End Date	End Time
B6 January	*	*	*	*
B6 February	*	*	*	*
B6 March	03/29/2011	10:00	03/30/2011	10:45
B6 April	04/24/2011	7:30	04/25/2011	8:15
B6 May	05/19/2011	15:30	05/20/2011	16:15
B6 June	06/2/2011	14:15	06/3/2011	15:00
B6 July	07/26/2011	23:15	07/28/2011	0:00
B6 August	08/17/2011	16:30	08/18/2011	17:15
B6 Septemb	er 09/18/2011	18:00	09/19/2011	18:45
B6 October	10/25/2011	14:15	10/26/2011	15:00
B6 Novemb	er 11/26/2011	15:00	11/27/2011	15:45
B6 December	er 12/12/2011	15:30	12/13/2011	16:15

^{*=} no sample collected due to winter/ice-over conditions

7) Associated researchers and projects

A few researchers have expressed interest in our 2011 nutrient data but prefer to wait until the review process is complete.

Water Quality (WQ) and Meteorological (MET) data associated with these Nutrient (NUT) data can be obtained via download from the at $\underline{www.nerrsdata.org}$. It is recommended that users utilize the new Advanced Query System ($\underline{www.nerrsdata.org/aqs}$) to merge these nutrient and water-quality data into one seamless file.

8) Distribution

The National Estuarine Research Reserve retains the right to be fully credited for having collected and processed the data. Following academic courtesy standards, the reserve site where the data were collected should be contacted and fully acknowledged in any subsequent publications in which any part of the data are used. These data sets are only as good as the quality assurance and quality control procedures outlined by the enclosed metadata reporting statement. The user bears all responsibility for its subsequent use or misuse in any further analyses or comparisons. The federal government does not assume liability to the recipient or third persons, nor will the federal government reimburse or indemnify the recipient for its liability due to any losses resulting in any way from the use of this data.

Suggested citation format:

National Estuarine Research Reserve System (NERRS). 2012. System-wide Monitoring Program. Data accessed from the NOAA NERRS Centralized Data Management Office website: www.nerrsdata.org; accessed 12 October 2012.

NERR nutrient data and metadata can be obtained from the Research Coordinator at the individual NERR site (please see Principal investigators and contact persons), from the Data Manager at the Centralized Data Management Office (please see personnel directory under the general information link on the CDMO home page) and online at the CDMO home page www.nerrsdata.org. Data are available in comma separated version format.

II. Physical Structure Descriptors

9) Entry verification

Monthly nutrient and plant pigment data files, in excel format, are sent to JAC NEER by the Rutgers University, IMCS, Ecosystems Lab. Files consist of sampling station ID, date and time and parameter values expressed in micro moles; these are converted to milligrams per liter (with the exception of Chlorophyll A, which is reported as micrograms per Liter). The Laboratory Supervisor, Ronald Lauck, verifies all parameter values in the excel file through cross comparison with the laboratory data sheets. The data are reviewed for values that appear erroneous or illogical. Any samples found to have questionable results are reanalyzed. JAC NEER staff (Gregg P. Sakowicz, SWMP Technician/Field Researcher) then performs the following:

The Analytical Laboratory at Rutgers University calculates and reports results in μM . For purposes of consistency in the NERR System, the Jacques Cousteau NERR calculates the concentrations as mg/l-1 based on atomic weights of 14.01, 30.97, and 12.01 for Nitrogen, Phosphorous, and Carbon, respectively. Therefore, Jacques Cousteau NERR staff multiplies the concentrations reported by the Rutgers University Laboratory by 0.01401, 0.03097, and 0.01201 to yield concentrations in mg/L as N, P, and C respectively.

Nutrient data are entered into a Microsoft Excel worksheet and processed using the NutrientQAQC Excel macro. The NutrientQAQC macro sets up the data worksheet, metadata worksheets, and MDL worksheet; adds chosen parameters and facilitates data entry; allows the user to set the number of significant figures to be reported for each parameter and rounds using banker's rounding rules; allows the user to input MDL values and then automatically flags/codes

measured values below MDL and inserts the MDL; calculates parameters chosen by the user and automatically flags/codes for component values below MDL, negative calculated values, and missing data; allows the user to apply QAQC flags and codes to the data; produces summary statistics; graphs selected parameters for review; and exports the resulting data file to the CDMO for tertiary QAQC and assimilation into the CDMO's authoritative online database.

10) Parameter titles and variable names by data category

Required NOAA/NERRS System-wide Monitoring Program water quality parameters are denoted by an asterisks "*".

Data Category	Parameter	Variable Name	Units of Measure
Phosphorus and	Nitrogen:		
-	*Orthophosphate	PO4F	mg/L as P
	*Nitrite + Nitrate, Filtered	NO23F	mg/L as N
	*Ammonium, Filtered	NH4F	mg/L as N
	Dissolved Inorganic Nitrogen	DIN	mg/L as N
	Total Dissolved Nitrogen	TDN	mg/L as N
Carbon:			
	Dissolved Organic Carbon	DOC	mg/L as C
Plant Pigments:			
	*Chlorophyll a	CHLA_N	μg/L
Field Parameters	:		
	Water Temperature	WTEM N	°C
	Specific Conductivity	\overline{N}	mS/cm ³
	Salinity	SALT_N	ppt
	Dissolved Oxygen	DO_S_N	% Saturation
	Dissolved Oxygen	DO_N	mg/L
	рН	PH_N	pH units

Notes:

- 1. Time is coded based on a 2400 clock and is referenced to Standard Time.
- 2. Reserves have the option of measuring either NO2 and NO3 or they may substitute NO23 for individual analyses if they can show that NO2 is a minor component relative to NO3. JAC NERR and analytical laboratory staff determined that analysis to isolate individual concentrations for NO2 and NO3 is not necessary. The concentration of NO2 is negligible when compared to the concentration of NO3.

11) Measured and calculated laboratory parameters

a) Variables measured directly

Nitrogen species: NO23F, NH4F, TDN

Phosphorus species: PO4F

Carbon species: DOC Other: CHLA

b) Computed variables

DIN: NO23F+NH4F

12) Limits of detection

Method Detection Limits (MDL), the lowest concentration of a parameter that an analytical procedure can reliably detect, have been established by the Rutgers University, IMCS, Ecosystems Laboratory. The MDL is determined as 3 times the standard deviation of a minimum of 7 replicates of a single low concentration sample. Table 1 presents the current MDL's; these values are reviewed and revised periodically. Methods are from Lachat Instruments QuikChem methods.

Table 1. Method Detection Limits (MDL) for measured water quality parameters.

Parameter	Variable	Method	MDL mg/L	Dates in Use
Ammonium	NH4F	31-07-06-1-B	0.001	January 2007- present
Nitrate/Nitrite	NO23F	30-107-04-1-C&D	0.001	January 2007-
0.1.1.1.	DO 4E	01 11 7 01 1 TT	0.002	present
Orthophosphate	PO4F	31-115-01-1-H	0.003	January 2007-
				present
Total Dissolved	TDN	see 13) laboratory	0.029	April 2004-
Nitrogen		methods		present
Dissolved Organic	DOC	SM 5310 B	0.084	April 2003-
Carbon				present
Chlorophyll a	CHLA	EPA 445.0	$0.01(\mu g/L)$	January 2003-
				present

13) Laboratory methods

i) Parameter: PO4F

Rutgers University, IMCS, Ecosystems Lab Laboratory Method Method Reference: Lachat Instruments, 1993. QuikChem Method 31-115-01-3-A. Method Descriptor: Samples were filtered with a 0.45 µm membrane filter and subjected to ammonium molybdate and antimony potassium tartate under acidic conditions to form a complex. The complex is reduced with ascorbic acid to form a blue complex that absorbs light at 880 nm.

Preservation Method: Stored in dark at -20°C for up to 30 days.

ii) Parameter: NO23F

Rutgers University, IMCS, Ecosystems Lab Laboratory Method Method Reference: Lachat Instruments, 1992. QuikChem Method 30-107-04-1-A. Method Descriptor: Samples were filtered with a 0.45 µm membrane filter. Nitrate is reduced to nitrite by passage of sample through a copperized cadmium column. The nitrite (reduced nitrate plus original nitrite) is then determined with sulfanilamide under acidic conditions to form a diazonium ion. The diazonium ion is coupled with N-(1-naphthyl)ethylenediamine dihydrochloride, which results in a pink dye that absorbs at 520 nm.

Preservation Method: Stored in dark at -20°C for up to 14 days.

iii) Parameter: NH4F

Rutgers University, IMCS, Ecosystems Lab Laboratory Method Method Reference: Lachat Instruments, 1993. QuikChem Method 31-107-06-1-A. Method Descriptor: Samples were filtered with a 0.45 µm membrane filter. The method used is based on the Berthelot reaction. Samples are subjected to hypochlorite-phenol, which results in indophenol blue. The indophenol blue is measured at 630 nm

Preservation Method: Stored in dark at -20°C for up to 3 days.

and is proportional to the ammonium concentration.

iv) Parameter: DIN

Rutgers University, IMCS, Ecosystems Lab Laboratory Method

Method Reference: N/A

Method Descriptor: Dissolved inorganic nitrogen is calculated by adding the ammonium concentration to the nitrate plus nitrite concentration. Ammonium and

nitrate plus nitrite concentrations are determined as stated above.

Preservation Method: N/A

v) Parameter: CHLA

Rutgers University, IMCS, Ecosystems Lab Laboratory Method

Method Reference: US.EPA 1997. Method 445.0

Method Descriptor: Samples with a known volume were filtered with a 0.45 μm membrane filter. Samples were dissolved in 5 ml 90% acetone/ 10% MgCO₃ solution.

Fluorescence determined using a Shimadzu RF-1501 spectrofluorometer.

Preservation Method: Filter is drawn dry, removed, placed in a glass tube with a phenolic screw cap, wrapped in aluminum foil and stored at -20°C for up to 30 days.

vi) Parameter: TDN

Rutgers University, IMCS, Ecosystems Lab Laboratory Method

Method Reference: N/A

High Temperature Combustion (HTC) measurements of DOC (using Shimadzu's NPOC method) and TDN are performed using a Shimadzu TOC 5000A total carbon analyzer (Shimadzu Corp, Japan) coupled with a Antek (PAC) 7000B nitrogen chemiluminescence detector (Antek Instruments).

vii) Parameter: DOC

Rutgers University, IMCS, Ecosystems Lab Laboratory Method

Method Reference: N/A

High Temperature Combustion (HTC) measurements of DOC (using Shimadzu's NPOC method) and TDN are performed using a Shimadzu TOC 5000A total carbon analyzer (Shimadzu Corp, Japan) coupled with a Antek (PAC) 7000B nitrogen chemiluminescence detector (Antek Instruments).

14) Field and laboratory QA/QC programs

a) Precision

i) Field variability

JAC NERR collects two successive grab samples for the monthly grab sample program.

ii) Laboratory variability

Rutgers University, IMCS, Ecosystems Lab analyzes a laboratory duplicate once for every nine samples.

iii) Inter-organizational splits

None

b) Accuracy

i) Sample spikes

Rutgers University, IMCS, Ecosystems Lab analyzes a matrix spike once for every ten samples.

ii) Standard reference material analysis

None

iii) Cross calibration exercises

None

15) QAQC flag definitions -

QAQC flags provide documentation of the data and are applied to individual data points by insertion into the parameter's associated flag column (header preceded by an F_). QAQC flags are applied to the nutrient data during secondary QAQC to indicate data that are out of sensor range low (-4), rejected due to QAQC checks (-3), missing (-2), optional and were not collected (-1), suspect (1), and that have been corrected (5). All remaining data are flagged as having passed initial QAQC checks (0) when the data are uploaded and assimilated into the CDMO ODIS as provisional plus data. The historical data flag (4) is used to indicate data that were submitted to the CDMO prior to the initiation of secondary QAQC flags and codes (and the use of the automated primary QAQC system for WQ and MET data). This flag is only present in historical data that are exported from the CDMO ODIS.

- -4 Outside Low Sensor Range
- -3 Data Rejected due to QAQC
- -2 Missing Data
- -1 Optional SWMP Supported Parameter
- 0 Data Passed Initial QAQC Checks
- 1 Suspect Data
- 4 Historical Data: Pre-Auto QAQC
- 5 Corrected Data

16) QAQC code definitions –

QAQC codes are used in conjunction with QAQC flags to provide further documentation of the data and are also applied by insertion into the associated flag column. There are three (3) different code categories, general, sensor, and comment. General errors document general problems with the sample or sample collection, sensor errors document common sensor or parameter specific problems, and comment codes are used to further document conditions or a problem with the data. Only one general or sensor error and one comment code can be applied to a particular data point. However, a record flag column (F Record) in the nutrient data allows multiple comment codes to be applied to the entire data record.

General errors

GCM	Calculated value could not be determined due to missing data
GCR	Calculated value could not be determined due to rejected data
GDM	Data missing or sample never collected
GQD	Data rejected due to QA/QC checks
GQS	Data suspect due to QA/QC checks

Sensor errors

SDL value below illillilliani fillit di filetiba detection	SBL	Value below minii	mum limit of method	detection
--	-----	-------------------	---------------------	-----------

SCB Calculated value could not be determined due to a below MDL component

SCC Calculation with this component resulted in a negative value

SNV Calculated value is negative

Replicate values differ substantially SRD

Value above upper limit of method detection SUL

Parameter Comments

CAB	Algal bloom
CDR	Sample diluted and rerun
CHB	Sample held beyond specified holding time
CIP	Ice present in sample vicinity

CIP Ice present in sample vicinity CIF Flotsam present in sample vicinity

Sample collected later/earlier than scheduled CLE

Significant rain event **CRE**

CSM See metadata

CUS Lab analysis from unpreserved sample

Record comments

CAB	Algal bloom
CHB	Sample held beyond specified holding time
CIP	Ice present in sample vicinity
CIF	Flotsam present in sample vicinity
CLE	Sample collected later/earlier than scheduled
CRE	Significant rain event
CSM	See metadata
CUS	Lab analysis from unpreserved sample
Cloud cover	
CCI	alaam (0, 100/)

CCL clear (0-10%)

> CSP scattered to partly cloudy (10-50%)

```
CPB
             partly to broken (50-90%)
    COC
             overcast (>90%)
    CFY
             foggy
    CHY
             hazy
             cloud (no percentage)
    CCC
Precipitation
    PNP
             none
    PDR
             drizzle
    PLR
             light rain
    PHR
             heavy rain
    PSQ
             squally
             frozen precipitation (sleet/snow/freezing rain)
    PFQ
    PSR
             mixed rain and snow
Tide stage
     TSE
             ebb tide
    TSF
             flood tide
    TSH
             high tide
    TSL
             low tide
Wave height
     WH0
             0 to < 0.1 meters
     WH1
             0.1 to 0.3 meters
     WH2
             0.3 to 0.6 meters
     WH3
             0.6 \text{ to} > 1.0 \text{ meters}
     WH4
             1.0 to 1.3 meters
     WH5
             1.3 or greater meters
Wind direction
             from the north
    N
    NNE
             from the north northeast
             from the northeast
    NE
    ENE
             from the east northeast
    Ε
             from the east
    ESE
             from the east southeast
    SE
             from the southeast
    SSE
             from the south southeast
     S
             from the south
     SSW
             from the south southwest
    SW
             from the southwest
     WSW
             from the west southwest
     W
             from the west
     WNW
             from the west northwest
    NW
             from the northwest
    NNW
             from the north northwest
Wind speed
     WS0
             0 to 1 knot
     WS1
             > 1 to 10 knots
     WS2
             > 10 to 20 knots
     WS3
             > 20 to 30 knots
     WS4
             > 30 to 40 knots
     WS5
             > 40 knots
```

17) Other remarks

Data may be missing due to problems with sample collection or processing. Laboratories in the NERRS System submit data that are censored at a lower detection rate limit, called the Method Detection Limit or MDL. MDLs for specific parameters are listed in the Laboratory Methods and Detection Limits Section (Section II, Part 12) of this document. Concentrations that are less than this limit are censored with the use of a QAQC flag and code, and the reported value is the method detection limit itself rather than a measured value. For example, if the measured concentration of NO23F was 0.0005 mg/l as N (MDL=0.0008), the reported value would be 0.0008 and would be flagged as out of sensor range low (-4) and coded SBL. In addition, if any of the components used to calculate a variable are below the MDL, the calculated variable is removed and flagged/coded -4 SCB. If a calculated value is negative, it is rejected and all measured components are marked suspect. If additional information on MDL's or missing, suspect, or rejected data is needed, contact the Research Coordinator at the Reserve submitting the data.

Note: The way below MDL values are handled in the NERRS SWMP dataset was changed in November of 2011. Previously, below MDL data from 2007-2010 were also flagged/coded, but either reported as the measured value or a blank cell. Any 2007-2011 nutrient/pigment data downloaded from the CDMO prior to November of 2011 will reflect this difference.

It is important to note that Buoy 115 (jacb5nut) in Southern Barnegat Bay is not a required SWMP station, but is collected as additional station as a compliment/comparison to the SWMP samples collected in the Mullica River/Great Bay complex.

No diel sampling was conducted during the months of January and February 2011 due to iceover conditions of local waters.

[SRD] (CSM)

A few discrepancies between replicate grab samples were observed and flagged in the dataset as "[SRD][CSM]" (denoting "Replicate values differ substantially" and "See metadata", respectively) code in the dataset. It is up to the user to retain or discard these data during analyses.

BA SALT N < -2 > [GDM] (CSM)

Salinity (SALT N) was not recorded at BA on 03/29/11 during grab sampling.

$\underline{\text{CHLA N} < -2 > (\text{CSM})}$

No Chlorophyll a data were reported by the analytical laboratory for BA from the 04/25/11 grab sampling period due to sample vial breakage.

No Chlorophyll a datum was reported by the analytical laboratory for the 04/25/11 06:00 diel sample due to sample vial breakage.

No data was submitted for the December 2011 Chlorophyll A samples; the vials went missing somewhere during sample transport/exchange of custody and were neither analyzed nor reported by the analytical laboratory.

CRE - Significant rain event

A CRE (significant rain event) comment was added to the August 2011 Grab and Diel sample data; while no rain occurred during the sample period, a significant rain event preceded the sampling period and may have affected sample values.

A CRE (significant rain event) comment was added to the April 2011 Grab and Diel sample data; while no rain occurred during the grab sample period, a significant rain event preceded the sampling period and may have affected sample values.

Field Parameters <-2> [GDM] (CSM)

Environmental data were not included for the November 2011 grab sample data from B5, B6, and B9; because of a narrow window of appropriate tidal state and a protracted time period in which to sample due to early sunset typical of the winter season, two technicians sampled (one at the downriver stations- B5, B6, and B9- and the other sampled the upriver stations- NE and BA), but only one "handheld YSI unit" (a YSI650MDS digital display paired with a 600XL sonde) was available.

Diel <-1> (CSM)

No physical ("water quality") parameters are included in this dataset for the diel sample program because these data can be obtained via download from the Buoy 126 station (jacb6wq) at www.nerrsdata.org. It is recommended that users utilize the new Advanced Query System (www.nerrsdata.org/aqs) to merge these nutrient and water-quality data into one seamless file.

F Record

While basic and notable weather information was inserted into the F_R ecord column for all grab samples, it is recommended that users of these data refer to the JAC NERR's meteorological dataset from the Nacote Creek Meteorological station (jacncmet) for weather information. The meteorological dataset can be accessed online at the CDMO home page http://cdmo.baruch.sc.edu/ or www.nerrsdata.org. It is recommended that users utilize the new Advanced Query System (www.nerrsdata.org/aqs) to merge these nutrient and waterquality data into one seamless file

Additionally, regarding inserting comment codes concerning weather, only significant rain events potentially affecting the data were inserted into the diel portion of the dataset. If users seek to correlate the diel samples with weather conditions, it is recommended that they refer to the JAC NERR's meteorological dataset. The meteorological dataset can be accessed online at the CDMO home page http://cdmo.baruch.sc.edu/ or www.nerrsdata.org.

Heavy construction on the Garden State Parkway bridge (just up-river of the Chestnut Neck sample site) was being performed intermittently in 2011 potentially affecting samples taken at all stations (except Buoy 115), and particularly those at Chestnut Neck.

The weather during the spring season in this region often includes high-pressure-induced NW winds that can cause "blow out tide" conditions in the estuary. During these blow-out tide events, high tides are depressed and low tides are exaggerated by the displacement of water offshore, causing significant drainage of water levels in estuaries and embayments. It is hypothesized that these extreme low tides may also pull water out of saturated marsh sediments, bringing along with it the nutrients otherwise entrained in those sediments, which may cause elevated/aberrant nutrient levels.

It is important to note that the B6 station sits within an interface between two bodies of water (Little Egg Harbor and Mullica River) that are often physiochemically (and visually) distinct, so some of the discrepancies between some replicates at this station may be accurate and "real" if the replicates were obtained from the two different "plumes" of water; this is something those performing collections attempt to avoid but visual cues may not be distinct enough to discern waters from each source at the time of collection.