

Reserve Name JOB NERR Meteorological Metadata
Months and year the documentation covers: 01/01/2009 to 12/31/2009
Latest Update: 05/07/2014

I. Data Set and Research Descriptors

1) Principal investigator(s) and contact persons

Jobos Bay National Estuarine Research Reserve
PO Box 159
Salinas, PR 00704-0159
Ph. 787-853-4617
Fx. 787-853-4618

Angel Dieppa, Research Coordinator
Ph. 787-853-4617, ext. 1004
Email. adieppa@gmail.com, adieppa@drna.gobierno.pr

Enid Malavé, Chemist
Ph. 787-853-4617, ext. 1005
Email. emalave1@gmail.com, emalave@jbnerr.org

2) Entry verification

Data are uploaded from the CR1000 data logger to a Personal Computer (IBM compatible). Files are exported from LoggerNet (or PC208W if needed) in a comma-delimited format and uploaded to the CDMO where they undergo automated primary QAQC and become part of the CDMO's online provisional database. During primary QAQC, data are flagged if they are missing or out of sensor range. The edited file is then returned to the Reserve where it is opened in Microsoft Excel and processed using the CDMO's NERRQAQC Excel macro. The macro inserts station codes, creates metadata worksheets for flagged data and summary statistics, and graphs the data for review. It allows the user to apply QAQC flags and codes to the data, append files, and export the resulting data file to the CDMO for tertiary QAQC and assimilation into the CDMO's authoritative online database. For more information on QAQC flags and QAQC codes, see Sections 11 and 12.

Angel Dieppa was responsible for all data management in 2009.

A Sutron Sat-Link2 transmits data to the NOAA GOES satellite, NESDIS ID # 3B018394 and NWS Location ID JOXP4. The transmissions are scheduled hourly and contain four (4) datasets reflecting fifteen minute data sampling intervals. The telemetry data is flagged as "Provisional" data and after going through QAQC process is considered "Authentic" dataset used for long term monitoring and study. This data can be viewed by going to <http://cdmo.baruch.sc.edu>.

3) Research objectives

The principal objective is to record long-term meteorological data to track changes in meteorological conditions that can be associated to changes in estuarine habitats and conditions and regionally as well. A secondary objective is to promote the access and use of reliable baseline information by federal and local agencies, universities, researchers, educators

and local communities to enhance the process by which they make decisions regarding their daily activities. This data is also invaluable in the identification and development of future monitoring and research activities.

This meteorological weather station is located at 0.40Km off the Jobos Bay coast and record data and information of the conditions affecting the estuary. The station is part of a System Wide Monitoring Program (SWMP) designed to evaluate the relative contributions of climate on coastal forcing and watershed inputs to hydrodynamics, nutrient dynamics, and other ecological processes within the estuary. Data is used as a reference of atmospheric conditions for ongoing research projects at the Reserve as a support from NERR and for other short and long-term environmental monitoring projects within the Reserve.

4) Research methods

Campbell Scientific data telemetry equipment was installed at the JOBJBMET station on 07/20/06 and transmits data to the NOAA GOES satellite, NESDIS ID #3B018394 (where 3B0297EC is the GOES ID for that particular station.) The transmissions are scheduled hourly and contain four (4) data sets reflecting fifteen minute data sampling intervals. Upon receipt by the CDMO, the data undergoes the same automated primary QAQC process detailed in Section 2 above. The “real-time” telemetry data become part of the provisional dataset until undergoing secondary and tertiary QAQC and assimilation in the CDMO’s authoritative online database. Provisional and authoritative data are available at <http://cdmo.baruch.sc.edu>.

From January 1, 2009 - December 31, 2009 the Campbell Scientific weather station (operated by the CR1000 datalogger) collected data every 15 minutes in the following format:

Air Temperature (°C), Relative Humidity (%), Barometric Pressure (mb), Wind Speed (m/s), Wind Direction (degrees), and Battery Voltage (volts) based on averages from 5-second data.

Maximum Air Temperature (°C), Minimum Air Temperature (°C), and their times from 5-second data. (these are not included in the data, but are available from the JOB NERR)

Maximum Wind Speed (m/s) and its time from 5-second data

Wind Direction Standard Deviation (degrees) from 5-second data

Precipitation (mm), Cumulative Precipitation (mm), and Photosynthetic Active Radiation (PAR; millimoles/m²) based on totals of 5-second data.

Recommended sensor calibration schedule:

- Temperature/Humidity- annual recalibration
- Rain Gauge- annual recalibration
- Wind Speed/Direction- bi-annual recalibration
- Barometric Pressure- bi-annual recalibration
- PAR- bi-annual recalibration

5) Site location and character

The Jobos Bay National Estuarine Research Reserve (JBNERR) is located on the southern coastal plain of the island of Puerto Rico, a reserve within the West Indies geographical area. JBNERR is composed of two major areas: (1) Mar Negro, located on the western margin of the Bay, and (2) Cayos Caribe (a chain of 17 tear-shaped islets located to the southeast) and Cayos Barca (a chain of 7 tear-shaped islets located to the southwest boundaries) both with a back-reef system. The Mar Negro area comprises the bulk of the Reserve, and consists of mangrove forests and a complex system of lagoons and channels interspersed with salt and mud flats. Coral reefs and sea grass beds, with small beach deposits and upland areas fringe Cayos Caribe and Cayos Barca mangrove islands.

A description of the specific sampling station follows:

The weather station is situated in front of the JBNERR Visitor's Center, located in the community of Aguirre in Salinas, Puerto Rico. Its coordinates are latitude 17° 57' 23.34" N and longitude 66° 13' 22.56" W. The tower base is about 9m above sea level, approximately 110m north from Jobos Bay's southern shoreline. The station is installed on a 10 meter tower in front of the Main Building, the wind and PAR sensors are above the building height. At 11 meters to the northwest side of the tower there is a tree with a height of 15 meters presenting a minor obstruction the sensors. In the southern region of Puerto Rico where JBNERR is located the winds persists from southeast and northeast, therefore the tree does not represent a significant obstruction for the winds. The height of the sensors are: Wind Sentry Anemometer (9.75 m high), Temperature/ Humidity sensor (2.7m high), Barometric Pressure sensor (2.7 m high), and LiCor Sensor (9.60 m high) are all located on a 10m aluminum tower following the descriptions outlined in the CDMO Manual V 5.1. The Tipping Bucket Rain gauge is located to the SW side of the tower over the ground. The top of the bucket is 35 centimeters above the ground. The sensors are wired to a CR1000 following the protocol in the CDMO Manual.

The weather station is at the following distance from SWMP stations used for water quality monitoring:

- 2.2 Km. from S09
- 4.2 Km. from S10
- 1.8 Km. from S19
- 3.1 Km. from S20

6) Data collection period

The weather station was installed in 1999. On 7/20/06 a new telemetry equipment was installed. During January 1st 00:00 to December 31st, 2009 23:45 data was collected, transmitted and saved in a computer where the meteorology station is connected.

7) Distribution

NOAA retains the right to analyze, synthesize and publish summaries of the NERRS System-wide Monitoring Program data. The PI retains the right to be fully credited for having collected and processed the data. The NERRS retains the right to be fully credited for having collected and process the data. Following academic courtesy standards, the NERR site where the data were collected should be contacted and fully acknowledged in any subsequent publications in which any part of the data are used. The data set enclosed within

this package/transmission is only as good as the quality assurance and quality control procedures outlined by the enclosed metadata reporting statement. The user bears all responsibility for its subsequent use/misuse in any further analyses or comparisons. The Federal government does not assume liability to the Recipient or third persons, nor will the Federal government reimburse or indemnify the Recipient for its liability due to any losses resulting in any way from the use of this data.

Requested citation format:

National Estuarine Research Reserve System (NERRS). 2012. System-wide Monitoring Program. Data accessed from the NOAA NERRS Centralized Data Management Office website: <http://cdmo.baruch.sc.edu/>; *accessed* 12 October 2012.

NERR water quality data and metadata can be obtained from the Research Coordinator at the individual NERR site (please see Principal Investigators and Contact Persons), from the Data Manager at the Centralized Data Management Office (please see personnel directory under the general information link on the CDMO home page) and online at the CDMO home page <http://cdmo.baruch.sc.edu/>. Data are available in comma delimited format.

8) Associated researchers and projects

The Jobos Bay NERR maintains four water quality monitoring stations as part of the System Wide Monitoring Program (SWMP) to monitor variability in the estuarine environment. Meteorological station collect continuous information that support water quality data intended to address short-term variability and long-term changes in estuarine water parameters within the bay (i.e., localized impacts of seasonal storms and hurricane events, variability due to tidal circulation, seasonal and interannual differences in rainfall, magnitude and influence of major events such hurricanes, spatial extent of oceanic and tidal forcing. Data will also be of fundamental baseline for future development of a hydrodynamic model for the Jobos Bay estuary with the help of CaRICOOS.

Our water quality monitoring program is a key component of SWMP. Variables measured include Temperature, Dissolved Oxygen, Turbidity, pH, Salinity, Chl-a fluorescence, and Depth in 4 permanent stations equipped with YSI datasondes. At the same stations, nitrogen, phosphorus, and chlorophyll are measured in a monthly basis.

SWMP data has been incorporated in the Conservation Effects Assessment Project (CEAP), a collaborative study of USDA, NOAA and JBNERR that pretends to implement best management practices in agricultural lands to improve water quality within the aquifer and Jobos Bay. Also, the Caribbean Regional Association for the Caribbean Regional Integrated Coastal Ocean Observing System (CaRICOOS) integrated and monitors Real Time data from our SWMP stations.

II. Physical Structure Descriptors

9) Sensor specifications

Parameter: Temperature

Units: Celsius

Sensor type: Platinum resistance temperature detector (PRT)

Model #: HMP45C Temperature and Relative Humidity Probe

Operating Temperature: -40°C to +60°C
Range: -40°C to +60°C
Accuracy: ± 0.2 °C @ 20°C
Date of Last Installation: 02/18/2004

Parameter: Relative Humidity
Units: Percent
Sensor type: Vaisala HUMICAP© 180 capacitive relative humidity sensor
Model #: HMP45C Temperature and Relative Humidity Probe
Range: 0-100% non-condensing
Accuracy at 20°C: $\pm 2\%$ RH (0-90%) and $\pm 3\%$ (90-100%)
Temperature dependence of RH measurement: $\pm 0.05\%$ RH/°C
Date of Last Installation: 02/18/2004

Parameter: Barometric Pressure
Units: millibars (mb)
Sensor type: Vaisala Barocap © silicon capacitive pressure sensor
Model #: CS-105
Operating Range: Pressure: 600 to 1060 mb; Temperature: -40°C to +60°C;
Humidity: non-condensing
Accuracy: ± 0.5 mb @ 20°C; ± 2 mb @ 0°C to 40°C; ± 4 mb @ -20°C to 45°C; ± 6 mb @ -40°C to 60°C
Stability: ± 0.1 mb per year
Date of Last Installation: 02/18/2004

Parameter: Wind speed
Units: meter per second (m/s)
Sensor type: 18 cm diameter 4-blade helicoids propeller molded of polypropylene
Model #: R.M. Young 05103 Wind Monitor
Range: 0-60 m/s (134 mph); gust survival 100 m/s (220 mph)
Accuracy: ± 0.3 m/s
Date of Last Installation: 02/18/2004

Parameter: Wind direction
Units: degrees
Sensor type: balanced vane, 38 cm turning radius
Model #: R.M. Young 05103 Wind Monitor
Range: 360° mechanical, 355° electrical (5° open)
Accuracy: ± 3 degrees
Date of Last Installation: 02/18/2004

Parameter: Photosynthetically Active Radiation
Units: mmol m⁻² (total flux)
Sensor type: High stability silicon photovoltaic detector (blue enhanced)
Model #: LI-COR Quantum Sensor LI190SB
Light spectrum waveband: 400 to 700 nm
Temperature dependence: 0.15% per °C maximum
Stability: $<\pm 2\%$ change over 1 yr
Operating Temperature: -40°C to 65°C; Humidity: 0 to 100%
Sensitivity: typically 5 μ A per 1000 μ moles s⁻¹ m⁻²
Date of Last Installation: 02/18/2004
Multiplier: 1.5

Parameter: Precipitation (non heated rain gauge)
Units: millimeters (mm)
Sensor type: Tipping Bucket Rain Gauge
Model #: RG-2000-C
Rainfall per tip: 0.01 inch
Date of Last calibration: 02/18/2004

The CR1000 has 2 MB of Flash EEPROM that is used to store the Operating System. Another 128 K Flash is used to store configuration settings. A minimum of 2 MB SRAM is (4 MB optional upgrade) available for program storage (16K), operating system use, and data storage. Additional storage is available by using a compact flash card in the optional CFM100 Compact Flash Module.

CR1000 installed: 7/21/2006

10) Coded variable definitions

Sampling station:	Sampling site code:	Station code:
Jobos Meteorology	jb	jobjbmet

11) QAQC flag definitions

QAQC flags provide documentation of the data and are applied to individual data points by insertion into the parameter's associated flag column (header preceded by an F_). During primary automated QAQC (performed by the CDMO), -5, -4, and -2, flags are applied automatically to indicate data that is above or below sensor range or missing. All remaining data are then flagged 0, as "good". During secondary and tertiary QAQC 1, -3, and 5 flags may be used to note data as suspect, rejected due to QAQC, or corrected.

- 5 Outside High Sensor Range
- 4 Outside Low Sensor Range
- 3 Data Rejected due to QAQC
- 2 Missing Data
- 1 Optional SWMP supported parameter
- 0 Passed Initial QAQC checks
- 1 Suspect Data
- 2 *Open - reserved for later flag*
- 3 *Open - reserved for later flag*
- 4 Historical Data: Pre-Auto QAQC
- 5 Corrected Data

12) QAQC code definitions

QAQC codes are used in conjunction with QAQC flags to provide further documentation of the data and are also applied by insertion into the associated flag column. There are three (3) different code categories, general, sensor, and comment. General errors document general problems with the deployment or CR1000, sensor errors are sensor specific, and comment codes are used to further document conditions or a problem with the data. Only one general or sensor

error and one comment code can be applied to a particular data point, but some comment codes (marked with an * below) can be applied to the entire record in the F_Record column.

General Errors

GIM	Instrument Malfunction
GIT	Instrument Recording Error, Recovered Telemetry Data
GMC	No Instrument Deployed due to Maintenance/Calibration
GMT	Instrument Maintenance
GPD	Power Down
GPF	Power Failure / Low Battery
GPR	Program Reload
GQR	Data Rejected Due to QA/QC Checks
GSM	See Metadata

Sensor Errors

SDG	Suspect due to sensor diagnostics
SIC	Incorrect Calibration Constant, Multiplier or Offset
SIW	Incorrect Wiring
SMT	Sensor Maintenance
SNV	Negative Value
SOC	Out of Calibration
SQR	Data rejected due to QAQC checks
SSD	Sensor Drift
SSN	Not a Number / Unknown Value
SSM	Sensor Malfunction
SSR	Sensor Removed

Comments

CAF	Acceptable Calibration/Accuracy Error of Sensor
CCU	Cause Unknown
CDF	Data Appear to Fit Conditions
CML	Snow melt from previous snowfall event
CRE*	Significant Rain Event
CSM*	See Metadata
CVT	Possible Vandalism/Tampering
CWE*	Significant weather event

13) Other remarks/notes

Data are missing due to equipment or associated specific sensors not being deployed, equipment failure, time of maintenance or calibration of equipment, or repair/replacement of a sampling station platform. Any NANs in the dataset stand for “not a number” and are the result of low power, disconnected wires, or out of range readings. If additional information on missing data is needed, contact the Research Coordinator at the reserve submitting the data.

Small negative PAR values are within range of the sensor and are due to normal errors in the sensor and the CR1000 Datalogger. The Maximum signal noise error for the LiCor sensor is +/- 2.214 mmoles/m² over a 15 minute interval.

Relative Humidity data greater than 100 are within range of the sensor accuracy of $\pm 3\%$.

Data recorded for all parameters (with the exception of cumulative precipitation) at the midnight timestamp (00:00) are the 15 minute averages and totals for the 23:45-23:59 time period of the previous day. Cumulative precipitation data at the midnight timestamp (00:00) are the sum of raw (unrounded) precipitation data from 00:00 to 23:59 of the previous day. Summing each individual 15-minute total precipitation value from the same period will result in small differences from cumulative precipitation due to rounding. It is especially important to note how data at the midnight timestamp are recorded when using January 1st and December 31st data.

Suspect Data:

As of April 1, 2008, all Reserves were required to align their wind direction sensor to True North. JOB wind sensor was aligned on March 18, 2011. All wind direction data from January 1, 2009 to December 31, 2009 are flagged as suspect. There was approximately 12 degrees offset between True and Magnetic North. Please contact JOB Reserve for more information.

All parameters from 1/1/2009 00:00 through 12/31/2009 23:45 are flagged as suspect and coded as SOC (sensor out of calibration). The sensors have been installed since 2/18/2004 and have not been calibrated since installation.

Relative humidity sensor did not reach 100% relative humidity values even under heavy rain events. Data are considered suspect.

All PAR data are considered suspect and out of calibration due to the sensor not being calibrated since 2004. Elevated nighttime PAR data are also considered suspect. Elevated nighttime readings are thought to be a result of moisture seeping into the sensor. Elevated nighttime readings do not occur every night, but do occur throughout the year.

From 2/4/2009 08:00-2/18/2009 14:45 and 5/5/2009 09:45- 5/11/2009 07:45, telemetered data had to be used in place of data downloaded from the station. These data are coded as {CSM} in the F_Record column. During the time telemetered data were used, there were occasion periods of lost transmissions. Those data are flagged and coded as <-2> GIT CSM. Data collected right after the missing timestamps are considered suspect. Although they do appear to be a full 15 minutes of 5 second readings, we cannot say for sure that they are. Cumulative precipitation values were still being stored during times when telemetered data were missing. Since TotPrp data were not transmitted during the data gaps, we cannot be sure that the CumPrp data are accurate, although they appear to be; therefore those data are considered suspect.

Suspect precipitation data due to telemetry gaps:

2/8/2009 15:00-2/9/2009 00:00 (total precipitation data were not recorded, but cumulative totals were).

5/6/2009 05:00-5/7/2009 00:00 (total precipitation data were not recorded, but cumulative totals were)

5/7/2009 15:00-5/8/2009 00:00 (total precipitation data were not recorded, but cumulative totals were)

5/8/2009 11:00-5/9/2009 00:00 (total precipitation data were not recorded, but cumulative totals were)

Suspect precipitation data following CCU data gaps:
5/13/2009 02:15-5/14/2009 00:00 (total precipitation data were not recorded, but cumulative totals were)

Missing Data:

Data are missing from 2/20/2009 17:15 – 2/24/2009 09:30 for unknown reasons (this may have been telemetered data, but it was not documented).

Data are missing from 5/13/2009 02:15 -5/13/2009 07:15 for unknown reasons (this may have been telemetered data, but it was not documented).

See above discussion of telemetered data for explanation of missing data coded as GIT CSM.

Rejected Data:

Because data are missing for unknown reasons 2/20/2009 02-2/24/2009 09:30 (see above Missing Data section), data at 09:45 are rejected due to possibly not being a full 15 minutes of 5 second data.

Because data are missing for unknown reasons 5/13/2009 02:15 -5/13/2009 07:15(see above Missing Data section), data at 07:30 are rejected due to possibly not being a full 15 minutes of 5 second data.

During 7/20/09 00:15 to 8/17/09 08:15 the Rain Bucket did not sample any rain event. The tipping bucket did not moved freely.

Data (cumulative precipitation) from a local rain sampler from NWS is available for those days.

DATE	Precipitation (mm)
7/21/09	38.90
7/22/09	0.380
8/12/09	0.760
8/13/09	0.254

Heavy rain events:

Date	Precipitation (mm)
5/06/09	54.6*
9/05/09	99.3
10/12/09	31.5
11/16/09	18.5
12/05/09	19.3

* These data are considered suspect due to gaps in telemetered data (see above Suspect Data).