

Reserve Name: JOB NERR Meteorological Metadata
Months and year the documentation covers: 01/01/2014 to 12/31/2014
Latest Update: 10/25/2016

I. Data Set and Research Descriptors

1) Principal investigator(s) and contact persons

Jobos Bay National Estuarine Research Reserve
PO Box 159
Salinas, PR 00704-0159
Ph. 787-853-4617
Fx. 787-853-4618

Angel Dieppa, Research Coordinator
Ph. 787-853-4617, ext. 1004
Email. adieppa@gmail.com, adieppa@drna.gobierno.pr

Enid Malavé, Chemist
SWMP Technician
Ph. 787-853-4617, ext. 1005
Email. emalave1@gmail.com, emalave@drna.gobierno.pr

2) Entry verification

Data are uploaded from the CR1000 data logger to a Personal Computer (IBM compatible). Files are exported from PC208W or LoggerNet in a comma-delimited format and uploaded to the CDMO where they undergo automated primary QAQC and become part of the CDMO's online provisional database. During primary QAQC, data are flagged if they are missing or out of sensor range. The edited file is then returned to the Reserve where it is opened in Microsoft Excel and processed using the CDMO's NERRQAQC Excel macro. The macro inserts station codes, creates metadata worksheets for flagged data and summary statistics, and graphs the data for review. It allows the user to apply QAQC flags and codes to the data, append files, and export the resulting data file to the CDMO for tertiary QAQC and assimilation into the CDMO's authoritative online database. For more information on QAQC flags and QAQC codes, see Sections 11 and 12.

A Campbell Sci. transmitter is used to deliver data to the NOAA GOES satellite, NESDIS ID # 3B018394 and NWS Location ID JOXP4. The transmissions are scheduled hourly and contain four (4) datasets reflecting fifteen minute data sampling intervals. The telemetry data is flagged as "Provisional" data and after going through QAQC process is considered "Authentic" dataset used for long term monitoring and study. This data can be viewed by going to <http://cdmo.baruch.sc.edu> or <http://nerrsdata.org>.

Data management is performed by Angel Dieppa and Enid Malavé.

3) Research objectives

The principal objective is to record long-term meteorological data to track changes in meteorological conditions that can be associated to changes in estuarine habitats and conditions and regionally as well. A secondary objective is to promote the access and use of

reliable baseline information by federal and local agencies, universities, researchers, educators and local communities to enhance the process by which they make decisions regarding their daily activities. This data is also invaluable in the identification and development of future monitoring and research activities.

This meteorological weather station is located at 0.40Km off the Jobos Bay coast and record data and information of the conditions affecting the estuary. The station is part of a System Wide Monitoring Program (SWMP) designed to evaluate the relative contributions of climate on coastal forcing and watershed inputs to hydrodynamics, nutrient dynamics, and other ecological processes within the estuary. Data is used as a reference of atmospheric conditions for ongoing research projects at the Reserve as a support from NERR and for other short and long-term environmental monitoring projects within the Reserve.

4) Research methods

Campbell Scientific data telemetry equipment was installed at the JOBJBMET station on 07/20/06 and transmits data to the NOAA GOES satellite, NESDIS ID #3B018394 (where 3B0297EC is the GOES ID for that particular station.) The transmissions are scheduled hourly and contain four (4) data sets reflecting fifteen minute data sampling intervals. Upon receipt by the CDMO, the data undergoes the same automated primary QAQC process detailed in Section 2 above. The “real-time” telemetry data become part of the provisional dataset until undergoing secondary and tertiary QAQC and assimilation in the CDMO’s authoritative online database. Provisional and authoritative data are available at <http://cdmo.baruch.sc.edu> or <http://nerrsdata.org>.

The 15 minute Data are collected in the following formats for the **CR1000**:

Averages from 5-second data:

Air Temperature (°C), Relative Humidity (%), Barometric Pressure (mb),
Wind Speed (m/s), Wind Direction (degrees), Battery Voltage (volts)
Maximum and Minimum Air Temperature (°C) and their times from 5-second
data (these data are available from the Reserve)
Maximum Wind Speed (m/s) and time from 5-second data
Wind Direction Standard Deviation (degrees)

Totals:

Precipitation (mm), PAR (millimoles/m²), and Cumulative Precipitation
(mm)

Recommended calibration frequency for the MET station sensors:

- Temperature/Humidity - yearly recalibration
- Rain Gauge - yearly recalibration
- Wind Speed/Direction - yearly or every 2 years inspection (depending on the sensor)
- Barometric Pressure - every 2 years recalibration
- PAR - every 2 years recalibration
- CR1000 - every 5 years (required beginning 2014, one year initial grace period)

5) Site location and character

The Jobos Bay National Estuarine Research Reserve (JBNERR) is located on the southern coastal plain of the island of Puerto Rico, a reserve within the West Indies geographical area. JBNERR is composed of two major areas: (1) Mar Negro, located on the western margin of the Bay, and (2) Cayos Caribe (a chain of 17 tear-shaped islets located to the southeast) and Cayos Barca (a chain of 7 tear-shaped islets located to the southwest boundaries) both with a

back-reef system. The Mar Negro area comprises the bulk of the Reserve, and consists of mangrove forests and a complex system of lagoons and channels interspersed with salt and mud flats. Coral reefs and sea grass beds, with small beach deposits and upland areas fringe Cayos Caribe and Cayos Barca mangrove islands.

A description of the specific sampling station follows:

The weather station is situated in front of the JBNERR Visitor's Center, located in the community of Aguirre in Salinas, Puerto Rico. Its coordinates are latitude 17 57' 23.34" and longitude 66 13' 22.56". The tower base is about 9m above sea level, approximately 110m north from Jobos Bay's southern shoreline. The station is installed in a 10 meter tower in front of the Main Building, the wind and PAR sensors are above the building height. At 11 meters to the northwest side of the tower there is a tree with a height of 15 meters presenting a minor obstruction to the sensors. In the southern region of Puerto Rico where JBNERR is located the winds persists from southeast and northeast, therefore the tree does not represent a significant obstruction for the winds. The high of the sensors are: Wind Sentry Anemometer (9.75 m high), Temperature/ Humidity sensor (2.7m high), Barometric Pressure sensor (2.7 m high), and PAR Sensor (9.60 m high) are all located on a 10m aluminum tower following the descriptions outlined in the CDMO Manual V 5.1. The Tipping Bucket Rain gauge is located to the SW side of the tower 1 meter over the ground. The sensors are wired to a CR1000 following the protocol in the CDMO Manual.

The weather station is at the following distance from SWMP stations used for water quality monitoring:

- 2.2 Km. from Station 09
- 4.2 Km. from Station 10
- 1.8 Km. from Station 19
- 3.1 Km. from Station 20

6) Data collection period

The weather station was installed in 1999. On 7/20/06 new telemetry equipment was installed. During January 1st to December 31st, 2014 data were collected and saved in a computer where the meteorology station is connected via wire and transmitted via NOAA-GOES near real time telemetry.

During year 2014 data is acquired following SWMP SOP's. This is in 15 minutes interval year round.

Data were downloaded from the station on the following dates in 2014:

File Start Date and Time	File End Date and Time
12/06/2013 09:30	01/15/2014 07:45
01/15/2014 08:00	01/29/2014 14:45
01/29/2014 15:00	02/19/2014 08:15
02/29/2014 08:30	03/06/2014 08:00
03/06/2014 08:15	03/20/2014 07:45
03/20/2014 08:00	04/03/2014 13:30
04/03/2014 13:45	04/22/2014 09:15
04/16/2014 08:15	05/14/2014 08:15
05/14/2014 08:30	05/29/2014 07:45

05/29/2014 08:00	06/13/2014 14:15
06/13/2014 14:30	07/08/2014 07:30
07/08/2014 07:45	08/05/2014 08:00
08/05/2014 08:15	08/20/2014 08:30
08/20/2014 08:45	09/03/2014 12:15
09/03/2014 12:30	09/17/2014 08:45
09/17/2014 09:00	10/03/2014 10:45
10/03/2014 11:00	10/31/2014 11:00
10/31/2014 11:15	11/14/2014 09:15
11/14/2014 09:30	12/01/2014 08:45
12/01/2014 09:00	12/18/2014 08:00
12/18/2014 08:15	01/14/2015 15:15

7) Distribution

NOAA retains the right to analyze, synthesize and publish summaries of the NERRS System-wide Monitoring Program data. The NERRS retains the right to be fully credited for having collected and process the data. Following academic courtesy standards, the NERR site where the data were collected should be contacted and fully acknowledged in any subsequent publications in which any part of the data are used. The data set enclosed within this package/transmission is only as good as the quality assurance and quality control procedures outlined by the enclosed metadata reporting statement. The user bears all responsibility for its subsequent use/misuse in any further analyses or comparisons. The Federal government does not assume liability to the Recipient or third persons, nor will the Federal government reimburse or indemnify the Recipient for its liability due to any losses resulting in any way from the use of this data.

Requested citation format:

NOAA National Estuarine Research Reserve System (NERRS). System-wide Monitoring Program. Data accessed from the NOAA NERRS Centralized Data Management Office website: <http://www.nerrsdata.org/>; accessed 12 October 2012.

NERR meteorological data and metadata can be obtained from the Research Coordinator at the individual NERR site (please see Principal Investigators and Contact Persons), from the Data Manager at the Centralized Data Management Office (please see personnel directory under the general information link on the CDMO home page) and online at the CDMO home page www.nerrsdata.org. Data are available in comma delimited format.

8) Associated researchers and projects

The Jobos Bay NERR maintains four water quality monitoring stations as part of the System Wide Monitoring Program (SWMP) to monitor variability in the estuarine environment. Meteorological station collect continuous information that support water quality data intended to address short-term variability and long-term changes in estuarine water parameters within the bay (i.e., localized impacts of seasonal storms and hurricane events, variability due to tidal circulation, seasonal and interannual differences in rainfall, magnitude and influence of major events such hurricanes, spatial extent of oceanic and tidal forcing).

Our water quality monitoring program is a key component of SWMP. Variables measured include Temperature, Dissolved Oxygen, Turbidity, pH, Salinity, Chl-a fluorescence, and Depth in 4 permanent stations equipped with YSI datasondes. At the same stations, nitrogen, phosphorus, and chlorophyll are measured in a monthly basis.

II. Physical Structure Descriptors

9) Sensor specifications

Parameter: Temperature

Units: Celsius

Sensor type: Platinum resistance temperature detector (PRT)

Model #: HMP45C Temperature and Relative Humidity Probe

Operating Temperature: -40°C to +60°C

Range: -40°C to +60°C

Accuracy: ± 0.2 °C @ 20°C

Date of previous calibration: 2/18/2004. Date Installed: 2/18/2004-2/11/2011

Date of last calibration: 4/25/2010 Date Installed: 2/11/2011-current as of 12/31/2014

Temp-RH SN F1640118

Parameter: Relative Humidity

Units: Percent

Sensor type: Vaisala HUMICAP® 180 capacitive relative humidity sensor

Model #: HMP45C Temperature and Relative Humidity Probe

Range: 0-100% non-condensing

Accuracy at 20°C: $\pm 2\%$ RH (0-90%) and $\pm 3\%$ (90-100%)

Temperature dependence of RH measurement: $\pm 0.05\%$ RH/°C

Date of previous calibration: 2/18/2004. Date Installed: 2/18/2004-2/11/2011

Date of last calibration: 4/25/2010 Date Installed: 2/11/2011-current as of 12/31/2014

Temp-RH SN F1640118

Parameter: Barometric Pressure

Units: millibars (mb)

Sensor type: Vaisala Barocap © silicon capacitive pressure sensor

Model #: CS-105

Operating Range: Pressure: 600 to 1060 mb; Temperature: -40°C to +60°C;

Humidity: non-condensing

Accuracy: ± 0.5 mb @ 20°C; ± 2 mb @ 0°C to 40°C; ± 4 mb @ -20°C to 45°C; ± 6 mb @ -40°C to 60°C

Stability: ± 0.1 mb per year

Date of previous calibration: 2/18/2004. Date Installed: 2/18/2004-2/11/2011

Date of last calibration: 4/23/2010 Date Installed: 2/11/2011-current as of 12/31/2014

Barometer SN Q43066

Parameter: Wind speed

Units: meter per second (m/s)

Sensor type: 18 cm diameter 4-blade helicoids propeller molded of polypropylene

Model #: R.M. Young 05103 Wind Monitor

Range: 0-60 m/s (134 mph); gust survival 100 m/s (220 mph)
Accuracy: +/- 0.3 m/s
Date of previous calibration: 2/18/2004. Date Installed: 2/18/2004-2/15/2011
Serial Number: WM100693
Date of last calibration: 3/31/2010 Date Installed: 2/15/2011-current as of 12/31/2014

Parameter: Wind direction
Units: degrees
Sensor type: balanced vane, 38 cm turning radius
Model #: R.M. Young 05103 Wind Monitor
Range: 360° mechanical, 355° electrical (5° open)
Accuracy: +/- 3 degrees
Date of previous calibration: 2/18/2004. Date Installed: 2/18/2004-2/15/2011
Serial Number: WM100693
Date of last calibration: 3/31/2010 Date Installed: 2/15/2011-current as of 12/31/2014

Parameter: Photosynthetically Active Radiation (PAR)
LI-COR Quantum Sensor
Units: mmol m⁻² (total flux)
Sensor type: High stability silicon photovoltaic detector (blue enhanced)
Model #: LI190SB
Light spectrum waveband: 400 to 700 nm
Temperature dependence: 0.15% per °C maximum
Stability: <±2% change over 1 yr
Operating Temperature: -40°C to 65°C; Humidity: 0 to 100%
Sensitivity: typically 5 µA per 1000 µmol s⁻¹ m⁻²
Date of previous calibration: 2/18/2004. Date Installed: 2/18/2004-2/15/2011
Multiplier: 1.5
Q43066: Date of last calibration: 2/19/2010 Date Installed: 2/15/2011-current as of 12/31/2014
Multiplier: 1.1187

Parameter: Precipitation (non heated rain gauge)
Units: millimeters (mm)
Sensor type: Tipping Bucket Rain Gauge
Model #: RG-2000-C
Rainfall per tip: 0.01 inch
Date of previous calibration: 2/18/2004. Date Installed: 2/18/2004-5/31/2011
Date of previous calibration: 5/31/2011 Date Installed: 05/31/2011 - 11/16/2012
Date of last calibration: 11/16/2012 Date Installed: 11/16/2012 - current as of 12/31/2014

The CR1000 has 2 MB of Flash EEPROM that is used to store the Operating System. Another 128 K Flash is used to store configuration settings. A minimum of 2 MB SRAM is (4 MB optional upgrade) available for program storage (16K), operating system use, and data storage. Additional storage is available by using a compact flash card in the optional CFM100 Compact Flash Module.

CR1000 installed: 7/21/2006
Date CR1000 Calibrated:
No new calibration since installed

CR1000 Firmware Version (s): unknown
CR1000 Program Version(s): JOBBMET_V5.53_060712.CR1

10) Coded variable definitions

Sampling station:	Sampling site code:	Station code:
Jobos Meteorology	jb	jobbmet

11) QAQC flag definitions

QAQC flags provide documentation of the data and are applied to individual data points by insertion into the parameter's associated flag column (header preceded by an F_). During primary automated QAQC (performed by the CDMO), -5, -4, and -2 flags are applied automatically to indicate data that is above or below sensor range, or missing. All remaining data are then flagged 0, as passing initial QAQC checks. During secondary and tertiary QAQC 1, -3, and 5 flags may be used to note data as suspect, rejected due to QAQC, or corrected.

- 5 Outside High Sensor Range
- 4 Outside Low Sensor Range
- 3 Data Rejected due to QAQC
- 2 Missing Data
- 1 Optional SWMP supported Parameter
- 0 Passed Initial QAQC Checks
- 1 Suspect Data
- 2 *Open - reserved for later flag*
- 3 *Open - reserved for later flag*
- 4 Historical Data: Pre-Auto QAQC
- 5 Corrected Data

12) QAQC code definitions

QAQC codes are used in conjunction with QAQC flags to provide further documentation of the data and are also applied by insertion into the associated flag column. There are three (3) different code categories, general, sensor, and comment. General errors document general problems with the CR1000, sensor errors are sensor specific, and comment codes are used to further document conditions or a problem with the data. Only one general or sensor error and one comment code can be applied to a particular data point, but some comment codes (marked with an * below) can be applied to the entire record in the F_Record column.

General Errors

GIM	Instrument Malfunction
GIT	Instrument Recording Error, Recovered Telemetry Data
GMC	No Instrument Deployed due to Maintenance/Calibration
GMT	Instrument Maintenance
GPD	Power Down
GPF	Power Failure / Low Battery

GPR	Program Reload
GQR	Data Rejected Due to QA/QC Checks
GSM	See Metadata

Sensor Errors

SDG	Suspect due to sensor diagnostics
SIC	Incorrect Calibration Constant, Multiplier or Offset
SIW	Incorrect Wiring
SMT	Sensor Maintenance
SNV	Negative Value
SOC	Out of Calibration
SQR	Data rejected due to QAQC checks
SSD	Sensor Drift
SSN	Not a Number / Unknown Value
SSM	Sensor Malfunction
SSR	Sensor Removed

Comments

CAF	Acceptable Calibration/Accuracy Error of Sensor
CCU	Cause Unknown
CDF	Data Appear to Fit Conditions
CML	Snow melt from previous snowfall event
CRE*	Significant Rain Event
CSM*	See Metadata
CVT*	Possible Vandalism/Tampering
CWE*	Significant weather event

13) Other remarks/notes

Data are missing due to equipment or associated specific sensors not being deployed, equipment failure, time of maintenance or calibration of equipment, or repair/replacement of a sampling station platform. Any NANs in the dataset stand for “not a number” and are the result of low power, disconnected wires, or out of range readings. If additional information on missing data is needed, contact the Research Coordinator at the reserve submitting the data.

Small negative PAR values are within range of the sensor and are due to normal errors in the sensor and the CR1000 Datalogger. The Maximum signal noise error for the LiCor sensor is +/- 2.214 mmoles/m² over a 15 minute interval.

Relative Humidity data greater than 100 are within range of the sensor accuracy of +/-3%.

Data recorded for all parameters (with the exception of cumulative precipitation) at the midnight timestamp (00:00) are the 15 minute averages and totals for the 23:45-23:59 time period of the previous day. Cumulative precipitation data at the midnight timestamp (00:00) are the sum of raw (unrounded) precipitation data from 00:00 to 23:59 of the previous day. Summing each individual 15-minute total precipitation value from the same period will result in small differences from cumulative precipitation due to rounding. It is especially important to note how data at the midnight timestamp are recorded when using January 1st and December 31st data. **Note: Cumulative precipitation is no longer available via export from the CDMO. Please contact the Reserve or the CDMO for more information or to obtain these data.**

Suspect Data:

ATemp/RH data are flagged and coded as suspect for the entire year due to being collected with an out of calibration sensor.

BP data are flagged and coded as suspect from 2/11/2014 through the end of the year due to being collected with an out of calibration sensor.

Wind data are flagged and coded as suspect from 2/15/2014 through the end of the year due to being collected with an out of calibration sensor.

PAR data are flagged and coded as suspect from 2/15/2014 through the end of the year due to being collected with an out of calibration sensor.

On 11/07/14 at 18:30 to 11/08/14 at 00:30 and 12/15/14 at 22:00 to 12/16/14 at 06:30 in addition to being suspect due to an out of calibration sensor, the data are suspect due to Elevated Nighttime PAR values.

Precipitation data are flagged and coded as suspect from 11/16/2014 through the end of the year due to being collected with an out of calibration sensor. Any significant rain events are coded with CRE (see table below).

Significant rain events:

<u>Date</u>	<u>Precipitation (mm)</u>	<u>Event associated with</u>
4/09/14	32.5	
5/11/14	29.7	Trough (Vaguada)
8/2/2014	21.60	Bertha
8/9/2014	20.32	
8/22/2014	67.31	
8/23/2014	26.16	
8/29/2014	19.05	
9/7/14	39.37	
11/7/14	99.56	
12/15/14	19.30	

*Significant rain events are those close to or over one inch cumulative value that may span 24 hours. Discrete total precipitation values are coded with CRE while the records from the beginning of the event through the midnight time stamp are coded as CRE for cumulative precipitation.