

North Inlet-Winyah Bay (NIW) NERR Water Quality Metadata
January 2015 – December 2015
Latest Update: May 23, 2017

I. Data Set and Research Descriptors

1) Principal investigator(s) and contact

Address: North Inlet-Winyah Bay NERR
PO Box 1630
Georgetown, SC 29440
phone: (843)-546-3623
fax: (843)-546-1632

Contact Persons:
Dr. Erik Smith, Research Coordinator
email: erik@belle.baruch.sc.edu; (843)-904-9035
Tracy Buck, Research Specialist
email: tracy@belle.baruch.sc.edu; (843)-904-9027

2) Entry verification

Deployment data are uploaded from the YSI data logger to a Personal Computer (IBM compatible). Files are exported from EcoWatch in a comma-delimited format (.CDF) and uploaded to the CDMO where they undergo automated primary QAQC; automated depth/level corrections for changes in barometric pressure (cDepth or cLevel parameters); and become part of the CDMO's online provisional database. All pre- and post-deployment data are removed from the file prior to upload. During primary QAQC, data are flagged if they are missing or out of sensor range. The edited file is then returned to the Reserve for secondary QAQC where it is opened in Microsoft Excel and processed using the CDMO's NERRQAQC Excel macro. The macro inserts station codes, creates metadata worksheets for flagged data and summary statistics, and graphs the data for review. It allows the user to apply QAQC flags and codes to the data, remove any overlapping deployment data, append files, and export the resulting data file for upload to the CDMO. Upload after secondary QAQC results in ingestion into the database as provisional plus data, recalculation of cDepth or cLevel parameters, and finally tertiary QAQC by the CDMO and assimilation into the CDMO's authoritative online database. Where deployment overlap occurs between files, the data produced by the newly calibrated sonde is generally accepted as being the most accurate. For more information on QAQC flags and codes, see Sections 11 and 12. Research Specialist, Tracy Buck edited and archived the 2015 data for Thousand Acre, Debidue Creek, Oyster Landing, and Clambank Creek.

3) Research objectives

The principal objective of this study is to record long-term water quality data for North Inlet/Winyah Bay in order to observe any physical changes or trends in water quality over time. Four sites were chosen; two to represent pristine sites and two to represent impacted sites. The Oyster Landing site is located near the center of the Reserve and is considered pristine. The Clambank site is located on a waterway that receives run-off from the undeveloped area of the reserve and is considered a pristine site. Debidue Creek and Thousand Acre are both located in waterways that receive run-off from heavily developed areas, and are therefore considered our impacted sites. Measurements were taken every 15 minutes over roughly two week collecting periods at the Oyster Landing, Debidue Creek, Clambank and Thousand Acre sites.

4) Research methods

YSI 6600 series sondes (Clambank Landing, Thousand Acre) and YSI EXO2 sondes (Oyster Landing, Debidue Creek) are currently mounted on either stand-alone pilings (Debidue Creek, Oyster Landing) or bridge/dock pilings (Thousand Acre, Clambank Creek). Each sonde is deployed in a 4 inch diameter PVC pipe which is strapped to the piling using stainless steel banding. The PVC pipe is offset from the pilings by inserting a 2x6 inch piece of treated lumber between the pipe and piling. This allows better flow over the sensors at the bottom of the pipes. The PVC pipe has a stainless steel stop bolt through its center 30 cm from the bottom of the pipe, ensuring that the sonde is seated 30 cm from the bottom of the creek. Directly above the stop bolt, 1 inch holes are drilled 0.5 cm apart within a 1 foot section of the pipe. This allows water flow over the sonde sensors. Two 2.5 inch holes are drilled perpendicular to each other at 1 foot intervals along the remaining length of the PVC pipe to allow for flushing. The bottom 4 feet of the pipe is painted inside and out with antifouling paint to minimize biofouling around the sensors. All pipes are switched out at least once a year (OL, CB, TA), while DC is usually switched out twice a year due to excessive fouling at that site.

Every 15 minutes measurements of specific conductivity, salinity, percent saturation, dissolved oxygen, water temperature, pH, turbidity, and water level are recorded (with the addition of chlorophyll at Oyster Landing). The two-week sampling interval was selected due to biofouling of the individual probes and expected battery life. Prior to deployment, the sondes are calibrated according to the procedures in the YSI Service Manual and the Standard Operating Procedures V4.1 provided by the NERR CDMO. Calibrations conducted prior to deployment of the instruments include a pH calibration using a two-point method with 7 and 10 unit standards. The turbidity calibration also uses a two-point method using 0 and 123 NTU standards. Specific Conductivity was calibrated using a one-point method with a 10 mS/cm standard that was purchased through YSI, Inc. Depth and dissolved oxygen are calibrated according to the barometric pressure at the time of calibration. Dissolved oxygen is calibrated using the air-saturated water method. The turbidity and ROX optical dissolved oxygen probe wipers are changed before each deployment. All of the sonde probes' non-measuring surfaces, wipers and probe guards are covered with copper tape to minimize biofouling. At the end of each sampling interval, the sondes are brought back to the laboratory to be downloaded and cleaned. The sondes are allowed to continue recording data for at least 1 hour under lab conditions in a water-saturated air environment. Before the instruments are cleaned, a post calibration reading was taken from each instrument in fresh standard to see if any of the instruments exhibit drift (see Section 13). Post calibration readings of depth and dissolved oxygen are taken once sonde readings have stabilized in a bucket of bubbling (air saturated) tap water. Two sondes are assigned to each of the four monitoring stations to allow the sondes to be switched out the same day, and minimize data loss.

A Sutron Sat-Link2 transmitter was installed at the Oyster Landing station on 07/07/06 and transmits data to the NOAA GOES satellite, NESDIS ID #3B031302. A Sutron Sat-Link2 transmitter was installed at the Debidue Creek station on 04/28/09 and transmits data to the NOAA GOES satellite, NESDIS ID #3B049722. The transmissions are scheduled hourly and contain four (4) data sets reflecting fifteen minute data sampling intervals. Upon receipt by the CDMO, the data undergoes the same automated primary QAQC process detailed in Section 2 above. The "real-time" telemetry data become part of the provisional dataset until undergoing secondary and tertiary QAQC and assimilation in the CDMO's authoritative online database. Provisional and authoritative data are available at www.nerrsdata.org.

5) Site location and character

The North Inlet-Winyah Bay National Estuarine Research Reserve is located on the Southeastern Atlantic coast of the United States in two tidal estuaries, North Inlet and Winyah Bay, near Georgetown, South Carolina. The North Inlet estuary, located approximately 10 km east of Georgetown, is a bar-built Class C type estuary (Pritchard, 1955). The North Inlet estuary is composed of numerous winding tidal creeks, and is considered a pristine tidal estuary due to minimal anthropogenic impacts. The watershed drains a 24.8 km² area of mostly pine forest and a moderately developed residential watershed to the north. The Winyah Bay estuary, classified as a Class B type estuary by Pritchard (1955), which originates in the Blue Ridge Mountains of North Carolina, is one of the largest river-estuary ecosystems on the Eastern Seaboard. It is located 14.4 km south of North Inlet. Winyah Bay drains the sub-basins of 6 major rivers, which are heavily impacted by agriculture, mining, and industry. The rivers drain approximately 46,736 km² of uplands and marshes. Descriptions of the four sampling stations are as follows:

A) **Clambank Creek** (CB) - (lat 33:20:02, long 79:11:35). The Clambank Creek monitoring site is located roughly in the center of the reserve property. This site is surrounded by a *Spartina* marsh and drains associated uplands. Salinity can range from near fresh water concentrations following large rainfall events, to full strength seawater during most of the year. The creek width and depth at MHW at the sampling site are 40 m and 2.4 m respectively. The average depth of the creek at MHW is 2.0 m with an average tidal range of approximately 1.4 meters. The bottom is comprised mostly of oyster shell hash and some fine sediment. This site is considered a pristine site and is influenced by its close proximity to North Inlet.

B) **Debidue Creek** (DC) - (lat 33:21:37, long 79:10:03). The Debidue Creek monitoring site is considered an impacted site that is located approximately 1 km south of the Debidue Colony. The Colony is a large development built on man-made canals that directly drain into the northern portion of Debidue Creek. The DC site is also located in an ocean-dominated *Spartina* marsh that was formerly surrounded by pine-dominated uplands. Salinity can range from 0 to full strength seawater and an average tidal range of approximately 2 m. The approximate depth and width at MHW at the site is 2.2 and 70 m respectively. The bottom is comprised mostly of oyster shell hash with some fine sediment and detritus.

C) **Oyster Landing** (OL) - (lat. 33:20:58, long. 79:11:20). The Oyster Landing monitoring site is considered a fairly pristine and undisturbed area located at the end of the Oyster Landing pier, which is also where the NI-WB Bay NERR weather station site is located. The pier stretches into the upper reaches of Crabhaul Creek in the mid western portion of North Inlet. The sampling site is located approximately 2.8 km from the headwaters of Crabhaul Creek. The creek directly drains pine-forested uplands and wetlands. Salinity can range from 0 to full strength seawater depending on rainfall events and upland drainage. The average tidal range is approximately 1.44 m. The creek has an average depth of 2 m MHW and average width of 150 m MHW. The bottom is comprised mostly of oyster shell hash with some fine sediment and detritus.

D) **Thousand Acre** (TA) - (lat. 33:17:57, long. 79:15:22) The Thousand Acre monitoring site is located in Thousand Acre marsh tidal creek and is on the NW corner of the west bridge of Thousand Acre marsh (this site was relocated 07-19-99 to the current location due to heavy siltation and degrading data quality). The present site is about 15 m from the mouth of the creek. At the sampling site, creek depth is approximately 2 m MHW and creek width is approximately 10 m. The creek empties into the northeastern side of the mid portion of Winyah Bay and directly drains pine forested upland and wetlands. Salinity ranges from 0 to 30 ppt. and tidal range is approximately 1m. The bottom is composed mostly of fine sediments and detritus. Georgetown, 5 km upstream from the Thousand Acre site and on the southern side of Winyah Bay, is the homeport for a number of heavy industries including a steel plant, paper mill, chemical plant, and a coal fired power plant. A public sewage treatment plant, which discharges into the bay, is also located in Georgetown.

6) Data collection period – Included in annual metadata document.

Thousand Acre data collection began January 1, 1995. Debidue Creek sampling began March 5, 1998. Oyster Landing data collection began in 1995; however, it was not considered a SWMP site until 1996 when the collection site was switched from Caledonia to Oyster Landing. Clambank sampling began in February 1981 through June 1995; however, it was not considered a SWMP site until sampling resumed on August 17, 2001. All sampling is ongoing.

Deployment dates and times (in Eastern Standard Time) for 2015 follow:

Site: **Clambank Creek**

Deploy Date	Time	Retrieve Date	Time
12/08/2014	09:45	01/07/2015	13:45
01/07/2015	14:45	01/27/2015	13:15
01/27/2015	13:30	02/13/2015	13:00

02/13/2015	13:15	03/09/2015	10:45
03/09/2015	11:15	03/24/2015	11:00
03/24/2015	11:15	04/07/2015	09:30
04/07/2015	09:45	04/21/2015	09:45
04/21/2015	10:00	05/06/2015	12:45
05/06/2015	13:00	05/17/2015	08:15
05/17/2015	08:30	06/04/2015	08:45
06/04/2015	09:15	06/19/2015	09:45
06/19/2015	10:00	07/02/2015	08:30
07/02/2015	09:00	07/16/2015	08:15
07/16/2015	08:30	08/05/2015	11:15
08/05/2015	11:45	08/18/2015	11:30
08/18/2015	11:45	09/01/2015	10:30
09/01/2015	13:00	09/16/2015	09:30
09/16/2015	09:45	09/30/2015	10:45
09/30/2015	11:00	10/09/2015	15:00
10/09/2015	15:15	10/21/2015	13:15
10/21/2015	13:45	11/04/2015	15:15
11/04/2015	15:30	11/17/2015	11:00
11/17/2015	11:15	12/03/2015	12:00
12/03/2015	12:15	12/16/2015	10:30
12/16/2015	10:45	01/12/2016	10:00

Site: **Debidue Creek**

Deploy Date	Time	Retrieve Date	Time
12/08/2014	09:30	01/07/2015	09:45
01/07/2015	10:15	02/13/2015	15:00
02/13/2015	15:15	03/09/2015	10:15
03/09/2015	10:30	03/24/2014	10:30
03/24/2015	10:45	04/07/2015	09:15
04/07/2015	09:30	04/21/2015	09:30
04/21/2015	09:45	05/06/2015	11:15
05/06/2015	11:30	05/15/2015	09:00
05/15/2015	09:30	06/04/2015	08:30
06/04/2015	08:45	06/19/2015	09:15
06/19/2015	09:45	07/02/2015	08:15
07/02/2015	08:30	07/16/2015	08:00
07/16/2015	08:15	08/05/2015	11:00
08/05/2015	11:15	08/18/2015	09:45
08/18/2015	10:00	09/01/2015	10:15
09/01/2015	10:30	09/16/2015	09:00
09/16/2015	09:15	09/30/2015	10:15
09/30/2015	10:45	10/21/2015	13:00
10/21/2015	13:15	11/04/2015	14:15
11/04/2015	14:45	11/17/2015	10:30
11/17/2015	10:45	12/03/2015	12:30

12/03/2015	12:45	12/16/2015	10:00
12/16/2015	10:15	01/12/2016	09:15

Site: **Oyster Landing**

Deploy Date	Time	Retrieve Date	Time
11/25/2014	10:30	01/07/2015	11:00
01/07/2015	11:15	01/27/2015	13:00
01/27/2015	13:30	02/26/2015	13:45
02/26/2015	14:00	04/21/2015	10:45
04/21/2015	11:00	05/17/2015	09:30
05/17/2015	10:00	06/09/2015	11:30
06/09/2015	12:00	07/02/2015	10:00
07/02/2015	10:15	08/05/2015	12:45
08/05/2015	13:00	09/01/2015	11:30
09/01/2015	12:00	09/16/2015	10:45
09/16/2015	11:15	09/30/2015	12:00
09/30/2015	12:15	10/24/2015	17:00
10/24/2015	17:15	11/04/2015	16:30
11/04/2015	16:45	11/17/2015	12:30
11/17/2015	12:45	12/16/2015	11:30
12/16/2015	11:45	01/12/2016	11:30

Site: **Thousand Acre**

Deploy Date	Time	Retrieve Date	Time
12/08/2014	10:15	01/07/2014	10:30
01/07/2015	10:45	01/27/2015	14:00
01/27/2015	14:15	02/13/2015	13:45
02/13/2015	14:00	03/09/2015	11:30
03/09/2015	11:45	03/24/2015	11:30
03/24/2015	11:45	04/07/2015	10:00
04/07/2015	10:15	04/21/2015	10:15
04/21/2015	10:30	05/06/2015	11:45
05/06/2015	12:00	05/17/2015	09:00
05/17/2015	09:15	06/04/2015	09:15
06/04/2015	09:30	06/19/2015	10:30
06/19/2015	10:45	07/02/2015	09:15
07/02/2015	09:30	07/16/2015	08:45
07/16/2015	09:00	08/05/2015	12:00
08/05/2015	12:15	08/18/2015	11:00
08/18/2015	11:15	09/01/2015	11:00
09/01/2015	11:15	09/17/2015	10:00
09/17/2015	10:15	09/30/2015	11:15
09/30/2015	11:30	10/09/2015	14:15

10/09/2015	14:30	10/21/2015	13:45
10/21/2015	14:15	11/04/2015	15:45
11/04/2015	16:00	11/17/2015	11:45
11/17/2015	12:00	12/03/2015	13:15
12/03/2015	13:30	12/16/2015	11:00
12/16/2015	11:15	01/12/2016	10:30

7) Distribution

NOAA retains the right to analyze, synthesize and publish summaries of the NERRS System-wide Monitoring Program data. The NERRS retains the right to be fully credited for having collected and process the data. Following academic courtesy standards, the NERR site where the data were collected should be contacted and fully acknowledged in any subsequent publications in which any part of the data are used. The data set enclosed within this package/transmission is only as good as the quality assurance and quality control procedures outlined by the enclosed metadata reporting statement. The user bears all responsibility for its subsequent use/misuse in any further analyses or comparisons. The Federal government does not assume liability to the Recipient or third persons, nor will the Federal government reimburse or indemnify the Recipient for its liability due to any losses resulting in any way from the use of this data.

Requested citation format:

National Estuarine Research Reserve System (NERRS). 2012. System-wide Monitoring Program. Data accessed from the NOAA NERRS Centralized Data Management Office website: www.nerrdata.org; accessed 12 October 2012.

NERR water quality data and metadata can be obtained from the Research Coordinator at the individual NERR site (please see Principal Investigators and Contact Persons), from the Data Manager at the Centralized Data Management Office (please see personnel directory under the general information link on the CDMO home page) and online at the CDMO home page www.nerrdata.org. Data are available in comma delimited format.

8) Associated researchers and projects

A water chemistry program is associated with the NIW core-monitoring program. Variables sampled include: chlorophyll, dissolved organic carbon, nitrate-nitrite, orthophosphate, and ammonia. (See documentation on the NIW WWW home page <http://www.northinlet.sc.edu/> for further details). Thousand Acre is our permanent monitoring station for the NERR monitoring program, but Oyster Landing and Debidue Creek were also sampled beginning in 1998. Clambank Landing was added as a sampling station in August of 2001. These stations are also included in our NIW core-monitoring program. Susan Denham (Research Specialist) is responsible for the collection and management of this data.

The NERR weather station is also located at the Oyster Landing site. Air temperature and humidity, barometric pressure, solar radiation (total and PAR), wind speed and direction, and precipitation are measured. Tracy Buck (Research Specialist) is responsible for the collection and management of this data.

A study of the optical characteristics of dissolved organic matter (DOM) is currently being conducted at Oyster Landing in association with the NIW NERR water quality and water chemistry sampling. Absorbance from 250 - 450 nm are quantified on filtered sub-samples of water collected during (ISCO) diel nutrient sampling and used to determine carbon-normalized DOM absorbance and spectral slope. Study objectives include using DOM optical characteristics as a tracer for the input of aromatic-rich DOM from higher plant and terrestrially-derived DOM sources to estuarine waters. Dr. Erik Smith (NIW NERR Research Coordinator) is the principle investigators on this project.

II. Physical Structure Descriptors

9) Sensor specifications

NIW NERR deployed YSI 6600EDS and EXO2 dataloggers in 2015. 6600EDS dataloggers were deployed:

Clambank Landing (CB) – 01/01/2015 – present

Debidue Creek (DC) – 01/01/2015 – 01/07/2015

Thousand Acre (TA) - 01/01/2015 – present

Each 6600EDS sonde used a 6560 conductivity/temperature probe, a 6150 ROX optical dissolved oxygen probe, a 6589 pH probe, and a 6136 turbidity probe.

EXO2 dataloggers were deployed at:

Oyster Landing (OL) – 01/01/2015 – present

Debidue Creek (DC) – 01/07/2015 - present

Each EXO2 datalogger uses a 599090 central wiper, a 599870 conductivity/temperature sensor, a 599702 wiped pH sensor, a 599100 optical dissolved oxygen probe, a 599101 turbidity probe. Oyster Landing has the addition of a 599102 BGA PC probe, and a 599104 fDOM probe (data not submitted).

Wiped conductivity / temperature probes (Model 599827) were introduced in 2015. At Oyster Landing, wiped CT was used 01/07/2015 – 01/27/2015, 06/09/2015 – current. At Debidue Creek, wiped CT was used 12/03/2015 – current.

YSI 6600 EDS-S Multi-parameter Water Quality Logger:

Parameter: Temperature

Units: Celsius (C)

Sensor Type: Thermistor

Model#: 6560

Range: -5 to 50 C

Accuracy: +/- 0.15

Resolution: 0.01 C

Parameter: Conductivity

Units: milli-Siemens per cm (mS/cm)

Sensor Type: 4-electrode cell with autoranging

Model#: 6560

Range: 0 to 100 mS/cm

Accuracy: +/- 0.5% of reading + 0.001 mS/cm

Resolution: 0.001 mS/cm to 0.1 mS/cm (range dependant)

Parameter: Salinity

Units: parts per thousand (ppt)

Sensor Type: Calculated from conductivity and temperature

Range: 0 to 70 ppt

Accuracy: +/- 1.0% of reading pr 0.1 ppt, whichever is greater

Resolution: 0.01 ppt

Sensor Type: Optical probe w/ mechanical cleaning

Model#: 6150 ROX

Range: 0 to 500% air saturation

Accuracy: 0-200% air saturation: +/- 1% of the reading or 1% air saturation, whichever is greater 200-500% air saturation: +/- 15% or reading

Resolution: 0.1% air saturation

Units: milligrams/Liter (mg/L)

Sensor Type: Optical probe w/ mechanical cleaning
Model#: 6150 ROX
Range: 0 to 50 mg/L
Accuracy: 0-20 mg/L: +/-0.1 mg/l or 1% of the reading, whichever is greater
20 to 50 mg/L: +/- 15% of the reading
Resolution: 0.01 mg/L

Parameter: Non-vented Level - Shallow (Depth)
Units: feet or meters (ft or m)
Sensor Type: Stainless steel strain gauge
Range: 0 to 30 ft (9.1 m)
Accuracy: +/- 0.06 ft (0.018 m)
Resolution: 0.001 ft (0.001 m)

Parameter: pH – bulb probe
Units: pH units
Sensor Type: Glass combination electrode
Model#: 6561
Range: 0 to 14 units
Accuracy: +/- 0.2 units
Resolution: 0.01 units

Parameter: Turbidity
Units: nephelometric turbidity units (NTU)
Sensor Type: Optical, 90 degree scatter, with mechanical cleaning
Model#: 6136
Range: 0 to 1000 NTU
Accuracy: +/- 2% of reading or 0.3 NTU (whichever is greater)
Resolution: 0.1 NTU

YSI EXO Sonde:

Parameter: Temperature
Units: Celsius (C)
Sensor Type: Thermistor
Model#: 599870-01
Range: -5 to 50 C
Accuracy: -5 to -35: +/- 0.01, -35 to -50: +/- .005
Resolution: 0.01 C

Parameter: Conductivity
Units: milli-Siemens per cm (mS/cm)
Sensor Type: 4-electrode cell with autoranging
Model#: 599870-01
Range: 0 to 200 mS/cm
Accuracy: 0 to 100: +/- 0.5% of reading or 0.001 mS/cm; 100 to 200: +/- 1% of reading
Resolution: 0.001 mS/cm to 0.1 mS/cm (range dependant)

Parameter: Salinity
Units: practical salinity units (psu)/parts per thousand (ppt)
Sensor Type: Calculated from conductivity and temperature
Range: 0 to 70 psu
Accuracy: +/- 1.0% of reading pr 0.1 ppt, whichever is greater
Resolution: 0.01 psu

Parameter: Dissolved Oxygen % saturation
Sensor Type: Optical probe w/ mechanical cleaning
Model#: 599100-01
Range: 0 to 500% air saturation
Accuracy: 0-200% air saturation: +/- 1% of the reading or 1% air saturation, whichever is greater 200-500% air saturation: +/- 5% or reading
Resolution: 0.1% air saturation

Parameter: Dissolved Oxygen mg/L (Calculated from % air saturation, temperature, and salinity)
Units: milligrams/Liter (mg/L)
Sensor Type: Optical probe w/ mechanical cleaning
Model#: 599100-01
Range: 0 to 50 mg/L
Accuracy: 0-20 mg/L: +/-0.1 mg/l or 1% of the reading, whichever is greater
20 to 50 mg/L: +/- 5% of the reading
Resolution: 0.01 mg/L

Parameter: Non-vented Level - Shallow (Depth)
Units: feet or meters (ft or m)
Sensor Type: Stainless steel strain gauge
Range: 0 to 33 ft (10 m)
Accuracy: +/- 0.013 ft (0.04 m)
Resolution: 0.001 ft (0.001 m)

Parameter: pH
Units: pH units
Sensor Type: Glass combination electrode
Model#: 599701(guarded) or 599702(wiped)
Range: 0 to 14 units
Accuracy: +/- 0.01 units within +/- 10° of calibration temperature, +/- 0.02 units for entire temperature range
Resolution: 0.01 units

Parameter: Turbidity
Units: formazin nephelometric units (FNU)
Sensor Type: Optical, 90 degree scatter
Model#: 599101-01
Range: 0 to 4000 FNU
Accuracy: 0 to 999 FNU: 0.3 FNU or +/-2% of reading (whichever is greater); 1000 to 4000 FNU +/-5% of reading
Resolution: 0 to 999 FNU: 0.01 FNU, 1000 to 4000 FNU: 0.1 FNU

Parameter: Chlorophyll
Units: micrograms/Liter
Sensor Type: Optical probe
Model#: 599102-01
Range: 0 to 400 ug/Liter
Accuracy: Dependent on methodology
Resolution: 0.1 ug/L chl a, 0.1% FS

Depth Qualifier:

The NERR System-Wide Monitoring Program utilizes YSI data sondes that can be equipped with either vented or non-vented depth/level sensors. Readings for both vented and non-vented sensors are automatically compensated

for water density change due to variations in temperature and salinity; but for all non-vented depth measurements, changes in atmospheric pressure between calibrations appear as changes in water depth. The error is equal to approximately 1.03 cm for every 1 millibar change in atmospheric pressure, and is eliminated for vented sensors because they are vented to the atmosphere throughout the deployment time interval.

Beginning in 2006, NERR SWMP standard calibration protocol calls for all non-vented depth sensors to read 0 meters at a (local) barometric pressure of 1013.25 mb (760 mm/hg). To achieve this, each site calibrates their depth sensor with a depth offset number, which is calculated using the actual atmospheric pressure at the time of calibration and the equation provided in the SWMP calibration sheet or digital calibration log. This offset procedure standardizes each depth calibration for the entire NERR System. If accurate atmospheric pressure data are available, non-vented sensor depth measurements at any NERR can be corrected.

In 2010, the CDMO began automatically correcting depth/level data for changes in barometric pressure as measured by the Reserve's associated meteorological station during data ingestion. These corrected depth/level data are reported as cDepth and cLevel, and are assigned QAQC flags and codes based on QAQC protocols. Please see sections 11 and 12 for QAQC flag and code definitions.

NOTE: older depth data cannot be corrected without verifying that the depth offset was in place and whether a vented or non-vented depth sensor was in use. No SWMP data prior to 2006 can be corrected using this method. The following equation is used for corrected depth/level data provided by the CDMO beginning in 2010: $((1013-BP)*0.0102)+Depth/Level = cDepth/cLevel$.

Salinity Units Qualifier:

In 2013, EXO sondes were approved for SWMP use and began to be utilized by Reserves. While the 6600 series sondes report salinity in parts per thousand (ppt) units, the EXO sondes report practical salinity units (psu). These units are essentially the same and for SWMP purposes are understood to be equivalent, however psu is considered the more appropriate designation. Moving forward the NERR System will assign psu salinity units for all data regardless of sonde type.

Turbidity Qualifier:

In 2013, EXO sondes were approved for SWMP use and began to be utilized by Reserves. While the 6600 series sondes report turbidity in nephelometric turbidity units (NTU), the EXO sondes use formazin nephelometric units (FNU). These units are essentially the same but indicate a difference in sensor methodology, for SWMP purposes they will be considered equivalent. Moving forward, the NERR System will use FNU/NTU as the designated units for all turbidity data regardless of sonde type. If turbidity units and sensor methodology are of concern, please see the Sensor Specifications portion of the metadata.

Chlorophyll Fluorescence Disclaimer:

YSI chlorophyll sensors (6025 or 599102-01) are designed to serve as a proxy for chlorophyll concentrations in the field for monitoring applications and complement traditional lab extraction methods; therefore, there are accuracy limitations associated with the data that are detailed in the YSI manual including interference from other fluorescent species, differences in calibration method, and effects of cell structure, particle size, organism type, temperature, and light on sensor measurements.

10) Coded variable definitions –

Sampling station:	Sampling site code:	Station code:
Clambank Creek	CB	niwcbwq
Debidue Creek	DC	niwdcwq

Oyster Landing	OL	niwolwq
Thousand Acre	TA	niwtawq

11) QAQC flag definitions –

QAQC flags provide documentation of the data and are applied to individual data points by insertion into the parameter's associated flag column (header preceded by an F_). During primary automated QAQC (performed by the CDMO), -5, -4, and -2 flags are applied automatically to indicate data that is missing and above or below sensor range. All remaining data are then flagged 0, passing initial QAQC checks. During secondary and tertiary QAQC 1, -3, and 5 flags may be used to note data as suspect, rejected due to QAQC, or corrected.

- 5 Outside High Sensor Range
- 4 Outside Low Sensor Range
- 3 Data Rejected due to QAQC
- 2 Missing Data
- 1 Optional SWMP Supported Parameter
- 0 Data Passed Initial QAQC Checks
- 1 Suspect Data
- 2 *Open - reserved for later flag*
- 3 Calculated data: non-vented depth/level sensor correction for changes in barometric pressure
- 4 Historical Data: Pre-Auto QAQC
- 5 Corrected Data

12) QAQC code definitions –

QAQC codes are used in conjunction with QAQC flags to provide further documentation of the data and are also applied by insertion into the associated flag column. There are three (3) different code categories, general, sensor, and comment. General errors document general problems with the deployment or YSI datasonde, sensor errors are sensor specific, and comment codes are used to further document conditions or a problem with the data. Only one general or sensor error and one comment code can be applied to a particular data point, but some comment codes (marked with an * below) can be applied to the entire record in the F_Record column.

General Errors

GIC	No instrument deployed due to ice
GIM	Instrument malfunction
GIT	Instrument recording error; recovered telemetry data
GMC	No instrument deployed due to maintenance/calibration
GNF	Deployment tube clogged / no flow
GOW	Out of water event
GPF	Power failure / low battery
GQR	Data rejected due to QA/QC checks
GSM	See metadata

Corrected Depth/Level Data Codes

GCC	Calculated with data that were corrected during QA/QC
GCM	Calculated value could not be determined due to missing data
GCR	Calculated value could not be determined due to rejected data
GCS	Calculated value suspect due to questionable data
GCU	Calculated value could not be determined due to unavailable data

Sensor Errors

SBO	Blocked optic
SCF	Conductivity sensor failure
SCS	Chlorophyll spike

SDF	Depth port frozen
SDG	Suspect due to sensor diagnostics
SDO	DO suspect
SDP	DO membrane puncture
SIC	Incorrect calibration / contaminated standard
SNV	Negative value
SOW	Sensor out of water
SPC	Post calibration out of range
SQR	Data rejected due to QAQC checks
SSD	Sensor drift
SSM	Sensor malfunction
SSR	Sensor removed / not deployed
STF	Catastrophic temperature sensor failure
STS	Turbidity spike
SWM	Wiper malfunction / loss

Comments

CAB*	Algal bloom
CAF	Acceptable calibration/accuracy error of sensor
CAP	Depth sensor in water, affected by atmospheric pressure
CBF	Biofouling
CCU	Cause unknown
CDA*	DO hypoxia (<3 mg/L)
CDB*	Disturbed bottom
CDF	Data appear to fit conditions
CFK*	Fish kill
CIP*	Surface ice present at sample station
CLT*	Low tide
CMC*	In field maintenance/cleaning
CMD*	Mud in probe guard
CND	New deployment begins
CRE*	Significant rain event
CSM*	See metadata
CTS	Turbidity spike
CVT*	Possible vandalism/tampering
CWD*	Data collected at wrong depth
CWE*	Significant weather event

13) Post deployment information –

Site: **Clambank Landing**

Post Cal Date	Sp.Con. (10 mS/cm)	Salinity (psu)	pH (7)	pH (10)	Depth	Turbidity (0 NTU)	BP (mm Hg)	ODO% (% air sat.)
01/07/2015	9.178	5.16	7.44	9.16	0.059	0.3	764.2	100.1
01/27/2015	9.962	5.63	7.13	10.06	-0.063	0.1	757.3	100.3
02/13/2015	9.817	5.55	7.14	9.96	0.094	1296.0	767.5	101.0
03/09/2015	10.000	5.66	7.01	9.99	0.095	0.6	766.6	102.6
03/24/2015	10.050	5.68	7.24	10.19	0.075	0.1	765.5	101.1
04/07/2015	10.080	5.70	7.06	10.09	0.106	0.3	766.9	100.7
04/21/2015	10.150	5.74	7.13	10.08	-0.025	-0.6	757.8	100.2
05/06/2015	10.020	5.65	7.06	10.03	0.041	0.8	760.9	100.7
05/17/2015	10.060	5.69	6.96	10.00	0.012	0.0	760.7	99.6

06/04/2015	9.000	5.04	7.07	10.02	0.027	0.1	762.3	99.6
06/19/2015	9.242	5.20	7.25	10.14	0.025	0.3	761.2	98.3
07/02/2015	9.144	5.13	7.10	10.02	0.006	0.4	760.4	100.1
07/16/2015	9.609	5.41	7.31	9.92	-0.018	-0.2	759.9	100.2
08/05/2015	8.456	4.73	7.23	9.37	-0.063	-0.1	755.5	99.3
08/18/2015	9.280	5.21	7.15	10.03	0.029	51.0	761.8	100.0
09/01/2015	9.700	5.47	7.11	10.04	0.042	-0.5	763.0	99.2
09/16/2015	9.324	5.24	7.10	10.05	0.090	-0.2	766.9	101.1
09/30/2015	9.770	5.51	7.10	10.01	-0.065	0.2	755.2	98.9
10/09/2015	10.000	5.65	7.04	10.08	-0.018	-0.2	758.7	100.7
10/21/2015	9.838	5.55	7.09	10.08	0.149	0.1	767.9	101.8
11/04/2015	9.866	5.57	7.04	10.09	0.109	0.2	767.7	100.6
11/17/2015	9.946	5.63	7.14	10.07	0.094	-0.7	766.9	101.6
12/03/2015						0.0	766.5	47.6
12/16/2015	9.884	5.58	7.00	9.90	0.028	0.1	762.5	100.7
01/12/2016	9.699	5.48	7.16	9.82	0.085	0.7	766.6	100.1

Site: **Debidue Creek**

Post Cal Date	Sp.Con. (10 mS/cm)	Salinity (psu)	pH (7)	pH (10)	Depth	Turbidity (0 NTU)	BP (mm Hg)	ODO% (% air sat.)
01/07/2015	9.43	5.31	7.16	9.96	0.091	-0.20	764.0	101.2
02/13/2015	9.85	5.57	7.06	10.11	0.083	0.15	767.5	103.6
03/09/2015	10.07	5.70	7.16	10.13	0.086	0.09	766.6	100.6
03/24/2015	10.06	5.69	7.07	10.04	0.072	0.39	765.5	101.0
04/07/2015	10.01		7.13	10.11	0.091	0.10	766.9	101.0
04/21/2015	9.62	5.42	7.15	10.13	-0.020	0.09	758.2	99.3
05/06/2015	10.01	5.65	7.12	10.08	0.013	-0.07	761.0	101.3
05/15/2015			7.12	10.04	0.016	-0.06	761.1	102.3
06/04/2015	9.41	5.32	7.02	10.06	0.044	1.30	762.3	100.0
06/19/2015	9.99	5.65	7.12	10.09	0.018	-0.13	761.2	98.7
07/02/2015	9.02	5.06	7.05	10.13	0.012	0.70	760.7	99.3
07/16/2015	9.46	5.32	7.21	10.18	0.001	0.27	759.9	100.1
08/05/2015			7.15	10.20	-0.060	0.27	755.8	109.3
08/18/2015	8.87	4.97	7.05	10.08	0.025	-0.31	761.6	98.3
09/01/2015	9.94	5.61	7.08	10.06	0.040	0.03	763.0	99.4
09/16/2015	9.24	5.19	7.16	10.16	0.105	-0.07	767.3	100.2
09/30/2015	9.95	5.62	7.06	10.04	-0.068	0.04	755.0	98.7
10/21/2015	9.93	5.60	7.05	10.07	0.109	0.01	767.9	102.8
11/04/2015	9.97	5.63	7.09	10.06	0.110	0.00	767.9	101.2
11/17/2015	9.88	5.59	7.09	10.05	0.093	-0.01	766.8	101.1
12/03/2015	9.95	5.63	7.02	9.90	0.082	0.18	766.4	100.3
12/16/2015	10.08	5.70	6.98	9.93	0.011	0.16	762.5	100.1
01/12/2016	9.99	5.65	7.15	10.21	0.105	-0.05	768.1	100.8

Site: **Oyster Landing**

Post Cal	Sp.Con.	Salinity	pH	pH	Depth	Turbidity	BP	ODO%	Chlorophyll
----------	---------	----------	----	----	-------	-----------	----	------	-------------

Date	(10mS/cm)	(psu)	(7)	(10)		(0 NTU)	(mm Hg)	(% air sat.)	(0 mg/L)
01/07/2015	9.880	5.59	7.11	10.12	0.196	-0.07	774.4	102.4	0.00
01/27/2015	9.985	5.65	7.07	10.02	-0.039	0.71	757.0	99.7	-0.09
02/26/2015	10.018	5.67	7.16	10.20	0.150	0.59	770.5	102.1	-0.01
04/21/2015	9.949	5.62	7.17	10.20		0.95	758.2	99.2	-0.10
05/17/2015	10.000	5.65	7.09	10.12	0.014	-0.62	760.9	100.2	0.50
06/09/2015	112.000		7.19	10.19	-0.020	0.06	757.6	99.0	-0.02
07/02/2015	10.020	5.66	7.09	10.14	0.013	-0.08	760.8	98.7	-0.14
08/05/2015	9.940		7.25	10.18	-0.015	0.96	758.5	99.8	-0.04
09/01/2015	10.020	5.66	7.15	10.19	0.040	0.47	763.0	98.1	-0.04
09/16/2015	10.000	5.65	7.20	10.15	0.099	0.12	767.8	99.9	0.07
09/30/2015	9.987	5.64	7.14	10.08	-0.070	-0.11	754.8	98.1	0.01
10/24/2015	9.930	5.60	7.12	10.11	0.060	0.52	763.8	100.5	-0.06
11/04/2015	9.990	5.64	7.10	10.08	0.110	0.38	768.0	101.5	0.00
11/17/2015	9.970	5.64	7.08	10.09	0.108	0.46	766.9	100.9	-0.01
12/16/2015	9.980	5.64	7.07	10.02	0.009	-0.19	762.5	99.3	-0.05
01/12/2016	9.998	5.66	7.11	10.17	0.133	0.18	768.1	101.2	

Site: **Thousand Acre**

Post Cal Date	Sp.Con. (10 mS/cm)	Salinity (psu)	pH (7)	pH (10)	Depth	Turbidity (0 NTU)	BP (mm Hg)	ODO% (% air sat.)
01/07/2015	NA							
01/27/2015	9.89	5.60	6.97	9.97	-0.099	0.9	757.3	100.3
02/13/2015	10.05	5.69	7.04	10.05	0.147	-0.4	767.5	105.5
03/09/2015	10.00	5.66	7.07	9.99	0.176	-0.1	767.1	102.4
03/24/2015	9.93	5.61	7.12	10.08	0.066	-0.4	765.5	99.7
04/07/2015	10.07	5.70	7.01	10.01	0.081	0.4	766.9	100.7
04/21/2015	9.98		6.93	10.00	0.120	0.5	769.0	100.2
05/06/2015	9.92	5.60	6.98	9.96	-0.014	1.0	760.9	100.5
05/17/2015	10.12	5.72	7.08	10.02	-0.009	0.8	760.7	102.4
06/04/2015	9.76	5.51	7.14	9.61	-0.010	0.0	762.2	100.0
06/19/2015	9.45	5.32	7.48	9.23	0.018	-0.1	761.7	99.3
07/02/2015	9.65	5.43	7.13	9.82	-0.040	0.5	759.8	100.3
07/16/2015	8.23	4.58	7.53	9.85	0.001	0.0	759.9	101.7
08/05/2015	8.03	4.46	7.54	7.74	-0.079	2.4	755.5	100.7
08/18/2015	9.56	5.38	7.07	10.04	0.022	0.8	761.8	100.3
09/01/2015	9.99	5.64	7.16	9.81	0.016	0.3	763.0	101.2
09/17/2015	9.76	5.49	7.13	9.66	0.051	0.0	763.6	96.8
09/30/2015	10.03	5.67	7.11	10.06	-0.064	0.0	755.4	99.2
10/09/2015	10.02	5.66	6.91	10.04	-0.012	0.2	758.7	101.1
10/21/2015	9.96	5.62	7.00	9.99	0.100	0.1	767.1	103.2
11/04/2015	9.97	5.63	7.03	10.07	0.105	0.3	767.7	102.7
11/17/2015	10.01	5.66	7.09	10.08	0.085	-1.4	766.7	100.7
12/03/2015	10.01	5.65	7.07	10.03	0.084	0.0	766.4	103.3

12/16/2015	10.02	5.66	7.03	10.03	0.006	-0.8	762.5	100.1
01/12/2016	9.87	5.58	6.95	10.06	0.078	2.0	765.8	101.2

14) Other remarks/notes –

- A) Data are missing due to equipment or associated specific probes not being deployed, equipment failure, time of maintenance or calibration of equipment, or repair/replacement of a sampling station platform. Any NaNs in the dataset stand for “not a number” and are the result of low power, disconnected wires, or out of range readings. If additional information on missing data is needed, contact the Research Coordinator at the reserve submitting the data.
- B) In instances where dissolved oxygen data at Debidue Creek is coded <-3> [SDO] (CSM), it is suspected that sharp drops in dissolved oxygen values are caused by excessive biofouling in the deployment tube depleting oxygen levels during periods of low flow at slack tide, and then this slug of water passing over the sensors as the tide changes. A new deployment tube made out of anti-fouling material was deployed at Debidue Creek on 06/16/2015, which eliminated this effect of biofouling on dissolved oxygen levels.
- C) In instances where rainfall affected data, the first period where the effects were seen was coded as CRE (significant rain event) for each parameter affected.
- D) In instances where strong winds or a combination of wind and rain affected data, the first period where the effects were seen was coded as CWE (significant weather event) for each parameter affected.
- E) pH data at Debidue Creek during the 12/16 deployment is marked <1> (CSM). The pH failed calibration and an older probe that had been in storage was used (rather than changing out the tip on the probe that failed). Despite passing calibration, this older pH probe showed a pretty significant offset compared to the preceding data.
- F) The following are daily rainfall totals > 2.54 mm for the year of 2015 recorded at the NIWB-NERR weather station at Oyster Landing. Note that significant rainfall amounts can affect all measured parameters, most noticeably salinity, turbidity and pH. Please note that tropical events are associated with heavy winds that may also affect tidal depth.

Date	Total Daily Precip (mm)
01/12/2015	30.23
01/18/2015	7.62
01/23/2015	17.53
01/24/2015	35.56
02/04/2015	6.35
02/05/2015	7.11
02/17/2015	10.67
02/23/2015	17.53
02/24/2015	3.05
02/25/2015	23.37
02/26/2015	19.30
03/01/2015	3.30

03/05/2015	5.59
03/19/2015	3.81
03/22/2015	12.45
03/23/2015	16.00
03/27/2015	8.64
04/13/2015	52.32
04/14/2015	18.80
04/15/2015	9.40
04/19/2015	22.86
04/26/2015	16.26
04/29/2015	19.05
05/07/2015	26.67
05/08/2015	4.32
05/09/2015	10.16
05/10/2015	69.34
06/02/2015	4.83
06/03/2015	36.58
06/06/2015	3.05
06/09/2015	10.16
06/24/2015	12.19
06/25/2015	35.56
06/28/2015	19.05
07/02/2015	10.16
07/03/2015	3.30
07/04/2015	6.10
07/06/2015	6.10
07/11/2015	45.21
07/13/2015	22.35
07/14/2015	3.81
07/15/2015	5.08
07/23/2015	11.43
08/03/2015	3.81
08/04/2015	101.35
08/18/2015	5.33
08/19/2015	36.32
08/20/2015	5.59
08/25/2015	6.60
08/27/2015	45.97
08/30/2015	14.99
08/31/2015	29.97
09/06/2015	31.24
09/07/2015	39.62
09/08/2015	4.06
09/09/2015	3.05
09/10/2015	8.13

09/17/2015	2.54
09/18/2015	3.56
09/24/2015	44.20
09/25/2015	25.91
10/01/2015	29.46
10/02/2015	84.58
10/03/2015	42.93
10/04/2015	212.60
10/05/2015	38.86
10/10/2015	37.08
10/11/2015	11.94
10/27/2015	15.24
10/28/2015	6.35
11/02/2015	13.21
11/03/2015	51.82
11/08/2015	11.18
11/09/2015	19.05
11/10/2015	6.35
11/19/2015	17.78
12/02/2015	3.05
12/07/2015	23.37
12/14/2015	3.56
12/18/2015	11.43
12/22/2015	22.35
12/23/2015	2.54
12/28/2015	6.60
12/31/2015	7.62