

Padilla Bay (PDB) NERR Meteorological Metadata

January through December 2012

Latest Update: 07 February 2024

I. Data Set and Research Descriptors

1) Principal investigator(s) and contact persons –

Dr. Douglas Bulthuis, Research Coordinator
phone: (360) 428-1089; email: bulthuis@padillabay.gov

Heath Bohlmann, Environmental Specialist
phone: (360) 428-1046; email: hbohlmann@padillabay.gov

Address:
Padilla Bay NERR
10441 Bayview-Edison Road
Mount Vernon, WA 98273-9668
Phone: (360) 428-1558

2) Entry verification –

Data are uploaded from the CR1000 data logger to a Personal Computer (IBM compatible). Files are exported from LoggerNet in a comma-delimited format and uploaded to the CDMO where they undergo automated primary QAQC and become part of the CDMO's online provisional database. During primary QAQC, data are flagged if they are missing or out of sensor range, or outside 2 or 3 standard deviations from the historical seasonal mean. The edited file is then returned to Padilla Bay NERR where it is opened in Microsoft Excel and processed using the CDMO's NERRQAQC Excel macro. The macro inserts station codes, creates metadata worksheets for flagged data and summary statistics, and graphs the data for review. It allows the user to apply QAQC flags and codes to the data, append files, and export the resulting data file to the CDMO for tertiary QAQC and assimilation into the CDMO's authoritative online database. Files are compiled quarterly and submitted after the secondary QAQC is completed. A final yearly file is compiled from the quarterly files, run once again through the QAQC process and submitted with metadata to CDMO. For more information on QAQC flags and QAQC codes, see Sections 11 and 12. Heath Bohlmann completed this process for entry verification and data verification and compiled this metadata for the 2012 data.

3) Research objectives –

The principal objective is to measure and record meteorological data at Padilla Bay for use in studies investigating correlations between meteorological data and water quality data, biological data, or other phenomenon in Padilla Bay and its watershed.

4) Research methods –

The weather parameters, air temperature, relative humidity, barometric pressure, wind speed and direction, photosynthetically active radiation, and precipitation were measured with a Campbell Scientific weather station at the Padilla Demonstration Farm near the southeast shore of Padilla Bay. Fifteen minute data were stored in a data logger and downloaded monthly. The sensors were visually inspected for debris or damage when the data were downloaded. Due to the location of the weather station in the middle of flat farm fields, the

sensors require very little cleaning. The most common problem occurs seasonally from air borne seeds partially blocking the rain gauge funnel. To mitigate this problem weeds near the site were cut before they set seed. While at the station downloading data, a Kestrel 4000 Pocket Weather Tracker is used to make a general, comparative check of the Campbell station sensors. Suspicious data are also checked against other local weather data posted on Washington State University's website (<http://weather.wsu.edu>)*. All sensors were calibrated on a regular basis unless otherwise noted in section 9.

Campbell Scientific data telemetry equipment was installed at the Padilla Demonstration Farm station on 11/11/05 and transmits data to the NOAA GOES satellite, NESDIS ID #3B005706. The transmissions are scheduled hourly and contain four (4) data sets reflecting fifteen minute data sampling intervals. Upon receipt by the CDMO, the data undergoes the same automated primary QAQC process detailed in Section 2 above. The "real-time" telemetry data become part of the provisional dataset until undergoing secondary and tertiary QAQC and assimilation in the CDMO's authoritative online database. Provisional and authoritative data are available at <http://cdmo.baruch.sc.edu>.

The 15 minute Data are collected in the following formats for the **CR1000**:

Averages from 5-second data:

Air Temperature (°C), Relative Humidity (%), Barometric Pressure (mb), Wind Speed (m/s), Wind Direction (degrees), Battery Voltage (volts)
Maximum and Minimum Air Temperature (°C) and their times from 5-second data (these data are available from the reserve)
Maximum Wind Speed (m/s) and time from 5-second data
Wind Direction Standard Deviation (degrees)

Totals:

Precipitation 15 min. (mm), PAR 15 min. (millimoles/m²), and Cumulative Daily Precipitation (mm)

5) Site location and character –

Padilla Bay (48° 30' N; 122° 30' W) is a shallow embayment in northern Puget Sound located in the greater Puget Sound-Georgia Basin estuary. It is an "orphaned" estuary in that the Skagit River, which formed the delta mud flats of Padilla Bay, no longer enters the bay directly. The tide flats are dominated by the eelgrass *Zostera marina*, which covers approximately 3,000 ha. *Zostera japonica*, a recent invader to the region, now covers about 800 ha of the bay. Tides are mixed semi-diurnal with a mean range of 1.5 m. Salinity varies from about 15 to 31 PSU. Most of the land in the 9300 ha Padilla Bay watershed is agricultural, and is drained by four sloughs which empty into the bay. Some freshwater from the Skagit now enters Padilla Bay from the south through the Swinomish Channel which connects Padilla Bay to Skagit Bay. Other major freshwater flows into this area of the Puget Sound-Georgia Basin estuary are from the Fraser and Nooksack Rivers to the north. Padilla Bay is bordered on the east and south by flat, diked farmland; farther to the east are foothills of the Cascade Range. March Point, on the western edge of the reserve, is the site of two large oil refineries. To the north and west are the San Juan Islands of northern Puget Sound.

The weather station is located near the southeast corner (122° 28' 9.49" W; 48° 27' 49.85" N) of Padilla Bay on a 40 hectare demonstration farm that is owned by the Reserve. Flat fields that are farmed for seasonal crops surround the site. Access is off of Bayview-Edison Road about 150 m down a gravel driveway. Base elevation of the weather station in orthometric height is 2.2m above mean sea level.

The sensors are mounted on a 3 m tower that is secured to a concrete pad as specified by the manufacturer, Campbell Scientific. The relative humidity/temperature sensor is mounted 2 m high and the wind and PAR sensors are at the top of the tower 3 m above ground level. The barometric pressure sensor is mounted 1 m above the ground (inside the CR1000 enclosure). The rain gauge is mounted on a cement cylinder approximately 3 feet high. Surrounding the site is a six foot high chain link fence for security. The weather station is about 300 m from the diked edge of the bay and approximately 4 km SE of the Bayview Channel YSI deployment site and about 4 km south of the Padilla Bay NERR Laboratory.

6) Data collection period –

January 01 at 00:00 to December 31 at 23:45, 2012. Data have been collected at the Padilla Farm weather station since January 1, 2001. Collection dates and times of raw data files are as follows:

12/09/2011 09:00 – 01/06/2012 13:15
1/6/2012 13:30 - 02/02/2012 13:45
2/2/2012 14:00 -03/06/2012 12:45
3/06/2012 11:00 - 04/12/2012 10:15
4/12/2012 10:30 - 05/02/2012 13:00
5/02/2012 13:15 - 05/30/2012 12:00
5/30/2012 12:45- 06/06/2012 13:45
6/6/2012 14:00 - 07/17/2012 14:00
7/17/2012 14:15 -08/9/2012 7:30
8/9/2012 7:45 - 09/04/2012 13:00
9/4/2012 13:15 - 10/02/2012 12:45
10/2/2012 13:00 -11/06/2012 09:00
11/6/2012 9:15 - 12/04/2012 13:30
12/4/2012 13:45 - 01/02/2013 14:45

7) Distribution –

NOAA/ERD retains the right to analyze, synthesize and publish summaries of the NERRS System-wide Monitoring Program data. The PI retains the right to be fully credited for having collected and processed the data. Following academic courtesy standards, the PI and NERR site where the data were collected will be contacted and fully acknowledged in any subsequent publications in which any part of the data are used. Manuscripts resulting from this NOAA/OCRM supported research that are produced for publication in open literature, including refereed scientific journals, will acknowledge that the research was conducted under an award from the Estuarine Reserves Division, Office of Ocean and Coastal Resource Management, National Ocean Service, National Oceanic and Atmospheric Administration. The data set enclosed within this package/transmission is only as good as the quality assurance and quality control procedures outlined by the enclosed metadata reporting statement. The user bears all responsibility for its subsequent use/misuse in any further analyses or comparisons. The Federal government does not assume liability to the Recipient or third persons, nor will the Federal government reimburse or indemnify the Recipient for its liability due to any losses resulting in any way from the use of this data.

NERR weather data and metadata can be obtained from the Research Coordinator at the individual NERR site (please see Principal investigators and contact persons), from the Data Manager at the Centralized Data Management Office (please see personnel directory under the general information link on the CDMO home page) and online at the CDMO home page <http://cdmo.baruch.sc.edu/>. Data are available in comma separated format.

8) Associated researchers and projects

In coordination with the SWMP weather data collected at Padilla Bay, water quality and nutrient data are also collected. The water quality part of SWMP consists of placing YSI 6600 datasondes at four sites in Padilla Bay. The sondes collect such parameters as water temperature, salinity, dissolved oxygen, depth, pH, and turbidity. The nutrient component of SWMP consists of monthly grab samples taken at each of the same four sites and monthly diel sampling taken at one of the sites (Bayview Channel Site). The nutrients analyzed include, but are not limited to, nitrate, nitrite, ammonium, silicate, orthophosphate, and chlorophyll a.

Other projects currently conducted at Padilla Bay include a zooplankton monitoring project with monthly sampling occurring at the three water quality/ nutrient sampling sites within the bay. In August 2009 Padilla Bay started long term monitoring of the rocky intertidal habitat in partnership with the Multi-Agency Rocky Intertidal Network (MARINe). See the MARINe website for further information on this monitoring project: <http://www.marin.gov/index.htm>. In 2011, Padilla Bay started a long term monitoring project of vegetative characteristics of two species of eelgrass: *Zostera marina* and *Z. japonica* on transects extending from the shoreline to the lower limit of distribution of eelgrasses. Dr. John Rybczyk, Western Washington University, established and maintains eighteen Surface Elevation Tables (SETs) throughout Padilla Bay. Padilla Bay sponsors graduate research in the bay through the Padilla Bay Research Assistantships in Estuarine Science and Coastal Zone Management. NOAA/OCRM/ERD sponsors graduate research in the NERRS, including Padilla Bay, through the Graduate Research Fellowship program. See the Padilla Bay NERR web site, <http://padillabay.gov/researchoverview.asp>, or contact the Research Coordinator (see I. above) for further information about these projects and other monitoring or research in Padilla Bay.

II. Physical Structure Descriptors

9) Sensor specifications –

Parameter: Temperature

Units: Celsius

Sensor type: Platinum resistance temperature detector (PRT)

Model #: HMP45C Temperature and Relative Humidity Probe

Operating Temperature: -40°C to +60°C

Range: -40°C to +60°C

Accuracy: ± 0.2 °C @ 20°C

Calibration Frequency: 1 year

Instrument #: X1130021

Date of calibration: 04/06/2011

Dates of sensor use: 05/04/2011 – 05/30/2012

Instrument #: X113020

Date of calibration: 03/28/2012

Dates of sensor use: 05/30/2012 – 06/06/2013

Parameter: Relative Humidity

Units: Percent

Sensor type: Vaisala HUMICAP® 180 capacitive relative humidity sensor

Model #: HMP45C Temperature and Relative Humidity Probe

Range: 0-100% non-condensing

Accuracy at 20°C: $\pm 2\%$ RH (0-90%) and $\pm 3\%$ (90-100%)

Temperature dependence of RH measurement: $\pm 0.05\%$ RH/°C

Calibration Frequency: 1 year

Instrument #: X1130021

Date of calibration: 04/06/2011

Dates of sensor use: 05/04/2011 – 05/30/2012

Instrument #: X113020

Date of calibration: 03/28/2012

Dates of sensor use: 05/30/2012 – 06/06/2013

Parameter: Barometric Pressure

Units: millibars (mb)

Sensor type: Vaisala Barocap © silicon capacitive pressure sensor

Model #: CS-105

Operating Range: Pressure: 600 to 1060 mb; Temperature: -40°C to +60°C;

Humidity: non-condensing

Accuracy: ± 0.5 mb @ 20°C; ± 2 mb @ 0°C to 40°C; ± 4 mb @ -20°C to 45°C; ± 6 mb @ -40°C to 60°C

Stability: ± 0.1 mb per year

Calibration Frequency: 2 years

30/2012

Instrument #: R1630013

Date of calibration: 03/15/2010

Dates of sensor use: 06/18/2010 – 05/30/2012

Instrument #: X0350002

Date of calibration: 04/05/2012

Dates of sensor use: 05/30/2012 – 08/01/2014

Parameter: Wind speed

Units: meter per second (m/s)

Sensor type: 12 cm diameter cup wheel assembly, 40 mm diameter hemispherical cups

Model #: R.M. Young 03001-5 Wind Sentry

Range: 0-50 m/s (112 mph); gust survival 60 m/s (134 mph)

Accuracy: $\pm 2\%$

Offset: 0.2

Calibration Frequency: 1 year

Sensor B (serial number unknown):

Date of calibration: 04/15/2011

Dates of sensor use: 05/04/2011 – 05/30/2012

Sensor A (serial number unknown):

Date of calibration: 03/28/2012

Dates of sensor use: 5/30/2012 – 06/06/2013

Parameter: Wind direction

Units: degrees

Sensor type: balanced vane, 16 cm turning radius

Model #: R.M. Young 03001-5 Wind Sentry
Range: 360° mechanical, 355° electrical (5° open)
Accuracy: +/- 5%
Calibration Frequency: 1 year
Sensor B (serial number unknown):
Date of calibration: 04/15/2011
Dates of sensor use: 05/04/2011 – 05/30/2012
Sensor A (serial number unknown):
Date of calibration: 03/28/2012
Dates of sensor use: 5/30/2012 – 06/06/2013

Parameter: Photosynthetically Active Radiation (PAR)
Units: mmol m⁻² (total flux)
Sensor type: LI-COR Quantum Sensor. High stability silicon photovoltaic detector (blue enhanced)
Model #: Quantum LI190SB
Light spectrum waveband: 400 to 700 nm
Temperature dependence: 0.15% per °C maximum
Stability: <±2% change over 1 yr
Operating Temperature: -40°C to 65°C; Humidity: 0 to 100%
Sensitivity: typically 5 µA per 1000 µmol s⁻¹ m⁻²
Calibration Frequency: 2 years
Previous Sensor serial #: Q35859
PAR Multiplier: 1.468
Date of calibration: 03/11/2010
Dates of sensor use: 6/18/2010 - 05/30/2012
Current Sensor serial #: Q46096
PAR Multiplier: 1.2467
Date of calibration: 01/17/2012
Dates of sensor use: 05/30/2012 – 06/06/2014

Parameter: Precipitation
Units: millimeters (mm)
Sensor type: Tipping Bucket Rain Gauge
Model #: RG-2000-C
Rainfall per tip: 0.01 inch
Operating range: Not specified
Accuracy: +/- 1.0% at 14 inches per hour
Calibration Frequency: 1 year
Instrument #: PDBRG3
Date of previous calibration: 3/7/2011
Date of last calibration: 3/27/2012
Sensor in use 01/21/2010 – 04/01/2013

CR1000 Measurement and Control System
Serial Number: 5097
Date CR1000 Installed: Aug/01/2006 – Jan/09/2015
Date CR1000 Calibrated: 2006

The CR1000 has 2 MB of Flash EEPROM that is used to store the Operating System. Another 128 K Flash is used to store configuration settings. A minimum of 2 MB SRAM is (4 MB optional upgrade) available for program storage (16K), operating system use, and data

storage. Additional storage is available by using a compact flash card in the optional CFM100 Compact Flash Module.

CR1000 Firmware Version (s): CR1000.Std.19 (06/18/2010)

CR1000 Program Version(s): PDBPFMET_V6.1_062210.CR1, PDBPFMET_6.2_053012

10) Coded variable definitions - List the sampling station, sampling site code, and station code used in the data.

Sampling station:	Sampling site code:	Station code:
Padilla Farm	PF	pdbpfmet

11) QAQC flag definitions –

QAQC flags provide documentation of the data and are applied to individual data points by insertion into the parameter's associated flag column (header preceded by an F_). During primary automated QAQC (performed by the CDMO), -5, -4, and -2 flags are applied automatically to indicate data that is above or below sensor range, or missing. All remaining data are then flagged 0, as passing initial QAQC checks. During secondary and tertiary QAQC 1, -3, and 5 flags may be used to note data as suspect, rejected due to QAQC, or corrected.

- 5 Outside High Sensor Range
- 4 Outside Low Sensor Range
- 3 Data Rejected due to QAQC
- 2 Missing Data
- 1 Optional SWMP supported parameter
- 0 Passed Initial QAQC Checks
- 1 Suspect Data
- 2 *Open - reserved for later flag*
- 3 *Open - reserved for later flag*
- 4 Historical Data: Pre-Auto QAQC
- 5 Corrected Data

12) QAQC code definitions –

QAQC codes are used in conjunction with QAQC flags to provide further documentation of the data and are also applied by insertion into the associated flag column. There are three (3) different code categories, general, sensor, and comment. General errors document general problems with the CR1000, sensor errors are sensor specific, and comment codes are used to further document conditions or a problem with the data. Only one general or sensor error and one comment code can be applied to a particular data point, but some comment codes (marked with an * below) can be applied to the entire record in the F_Record column.

General Errors

GIM	Instrument Malfunction
GIT	Instrument Recording Error, Recovered Telemetry Data
GMC	No Instrument Deployed due to Maintenance/Calibration
GMT	Instrument Maintenance
GPD	Power Down
GPF	Power Failure / Low Battery

GPR	Program Reload
GQR	Data Rejected Due to QA/QC Checks
GSM	See Metadata

Sensor Errors

SDG	Suspect due to sensor diagnostics
SIC	Incorrect Calibration Constant, Multiplier or Offset
SIW	Incorrect Wiring
SMT	Sensor Maintenance
SNV	Negative Value
SOC	Out of Calibration
SQR	Data rejected due to QAQC checks
SSN	Not a Number / Unknown Value
SSM	Sensor Malfunction
SSR	Sensor Removed

Comments

CAF	Acceptable Calibration/Accuracy Error of Sensor
CDF	Data Appear to Fit Conditions
CML	Snow melt from previous snowfall event
CRE*	Significant Rain Event
CSM*	See Metadata
CCU	Cause Unknown
CVT*	Possible Vandalism/Tampering
CWE*	Significant weather event

13) Other remarks/notes –

General Data Comments

Data are missing due to equipment or associated specific sensors not being deployed, equipment failure, time of maintenance or calibration of equipment, or repair/replacement of a sampling station platform. Any NANs in the dataset stand for “not a number” and are the result of low power, disconnected wires, or out of range readings. If additional information on missing data is needed, contact the Research Coordinator at the reserve submitting the data.

Data recorded for all parameters (with the exception of cumulative precipitation) at the midnight timestamp (00:00) are the 15 minute averages and totals for the 23:45-23:59 time period of the previous day. Cumulative precipitation data at the midnight timestamp (00:00) are the sum of raw (unrounded) precipitation data from 00:00 to 23:59 of the previous day. Summing each individual 15-minute total precipitation value from the same period will result in small differences from cumulative precipitation due to rounding. It is especially important to note how data at the midnight timestamp are recorded when using January 1st and December 31st data. **Note: Cumulative precipitation is no longer available via export from the CDMO. Please contact the Reserve or the CDMO for more information or to obtain these data.**

Note that the 3001 Wind Monitor has an offset of 0.2 and does not record values of 0.

All Parameters

All data are missing 05/30/2012 12:15 – 12:30 due to a power down for maintenance to replace the air temperature/relative humidity, barometric pressure, wind, and PAR sensors, <-2> [SMT](CSM). Following the program upload at 12:45, <-3> [GPR](CSM), AT/RH, BP, Wind, and PAR data are rejected due to continued sensor maintenance from 13:00 – 14:00, <-3>[SMT](CSM). Total and cumulative precipitation were not rejected for the program reload as no precipitation fell during maintenance.

Rh Data

Relative Humidity data greater than 100 are within range of the sensor accuracy of +/-3% and are flagged and coded as suspect, <1> (CAF). Values greater than 103 are rejected <-3>.

RH Data from the following dates were rejected due to values recorded above the acceptable sensor range.

01/15/2012 08:30 <-3> [SQR] (CSM)

01/15/2012 08:45 <-3> [SQR] (CSM)

TotPrcp:

Maintenance tips occurred on 03/21/2012 12:45 – 13:00 and 05/02/2012 13:15. These were corrected back to 0.0, <5>[SMT](CSM).

The rain gauge was removed for calibration on 03/27/2012 11:00 – 14:30, <-3> [SSR](CSM). Cumulative precipitation was not flagged until the end of the day since no rain fall occurred during calibration.

Rain recorded on the following date/time may be inaccurate; no precipitation recorded at other local stations* and this is during a very dry period. Farming practices (watering/spraying) have on occasion been observed in rainfall amounts in the past.

08/08/2012 06:45 <1> (CSM)

CumPrcp:

Maintenance tips occurred on 03/21/2012 12:45 - 03/22/2012 00:00. These were corrected from 12:45 through the end of the day to reflect cumulative rainfall amounts that occurred before maintenance, <5>[SMT](CSM).

The rain gauge was removed for calibration on 03/27/2012 11:00 – 14:30, <-3> [SSR](CSM). Cumulative precipitation was not flagged until the end of the day since no rain fall occurred during calibration.

Maintenance tips occurred on 05/02/2012 13:15 - 05/03/2012 00:00. These were corrected back to 0.0, <5>[SMT](CSM).

Rain recorded on the following date/time may be inaccurate; no precipitation recorded at other local stations* and this is during a very dry period. Farming practices (watering/spraying) have on occasion been observed in rainfall amounts in the past.

08/08/2012 06:45 through 08/09/2012 00:00 <1> (CSM)

PAR Data

Small negative PAR values are within range of the sensor and are due to normal errors in the sensor and the CR1000 Datalogger. The Maximum signal noise error for the Licor sensor is +/- 2.214 mmoles/m² over a 15 minute interval. These values are automatically flagged and coded as <1> (CAF).

Elevated nighttime PAR values were recorded during some nights over of the year. Nighttime PAR values <2.214 but >0 are marked as suspect, <1>(CSM), and nighttime values >2.214 were rejected, <-3>(CSM). Data rejection times at dusk and dawn were based on having a < 2.0 change in the PAR value in conjunction with a preceding fall or subsequent rise in values. The cause for the elevated values is suspected to be moisture intrusion into the sensor body.

* Meteorological Data References:

Meteorological data used for comparison can be found at the AgWeatherNet network. To access raw data for the AgWeatherNet network, go to the AgWeatherNet web site URL as follows: www.weather.wsu.edu.

Station: **WSU Mt Vernon** Lat: 48.43849, Lng: -122.38566, Elevation: 7.01m, Distance from Padilla Bay Farm MET station: 6.5 km.

Station: **Sakuma** Lat: 48.49735, Lng: -122.37847, Elevation: 8.53m, Distance from Padilla Bay Farm MET station: 8 km.

Station: **Fir Island** Lat: 48.35654, Lng: -122.42188, Elevation: 0m, Distance from Padilla Bay Farm MET station: 16 km.