

Reserve Name WKB NERR Meteorological Metadata
Months and year the documentation covers – 01/07 through 12/07
Latest Update: March 9, 2010

I. Data Set and Research Descriptors

- 1) **Principal investigator(s) and contact persons –**
Tim Lankford – SWMP Technician (left 02/08)
Eric Brunden – Stewardship Coordinator
eric.brunden@dcnr.alabama.gov
Scott Phipps – Research Coordinator
scott.phipps@dcnr.alabama.gov

Address: Weeks Bay NERR
11300 Highway 98
Fairhope, AL 36532

2) Entry verification

Data are uploaded from the CR1000 data logger to a Personal Computer (IBM compatible). Files are exported from LoggerNet in a comma-delimited format and uploaded to the CDMO where they undergo automated primary QAQC and become part of the CDMO's online provisional database. During primary QAQC, data are flagged if they are missing or out of sensor range. The edited file is then returned to the Reserve where it is opened in Microsoft Excel and processed using the CDMO's NERRQAQC Excel macro. The macro inserts station codes, creates metadata worksheets for flagged data, and graphs the data for review. It allows the user to apply QAQC flags and codes to the data, append files, and export the resulting data file to the CDMO for tertiary QAQC and assimilation into the CDMO's authoritative online database. These data are also converted to graphic representation and posted on the Internet at <http://cast-net.disl.org/monitoringdata/nep/index.htm> hourly with the cooperation of the Mobile Bay NEP and the Dauphin Island Sea Lab.

For more information on QAQC flags and QAQC codes, see Sections 11 and 12. Scott Phipps is responsible for all data management.

3) Research objectives –

The principle objective is to record long-term meteorological data for Weeks Bay in order to 1) observe any environmental changes or trends over time, 2) use as a reference for research projects at the reserve, and 3) give meteorological context to our fifteen minute SWMP water quality data.

4) Research methods –

Campbell Scientific data telemetry equipment was installed at the WKB station on 07/31/06 and transmits data to the NOAA GOES satellite, NESDIS ID 3B01A578. The transmissions are scheduled hourly and contain four (4) data sets reflecting fifteen minute data sampling intervals. Upon receipt by the CDMO, the data undergoes the same automated primary QAQC process detailed in Section 2 above. The “real-time” telemetry data become part of the provisional dataset until undergoing secondary and tertiary QAQC and assimilation in the

CDMO's authoritative online database. Provisional and authoritative data are available at <http://cdmo.baruch.sc.edu>.

The Campbell Scientific CR1000 datalogger uses 5-second data downloaded from the weather station sensors to calculate 15-minute data. The CR1000 stores only 15 minute data. Parameters measured are air temperature, relative humidity, barometric pressure, rainfall, wind speed, wind direction, total PAR, and total precipitation. Maximum and minimum relative humidity and barometric pressure and minimum wind speed are no longer collected with the CR1000 program. Periodically, sensors on the weather station are inspected for damage or debris. If any are found, it is repaired and/or cleaned. Sensors are removed and calibrated on an annual or bi-annual basis. Temperature sensor was last calibrated 8/6/2007, barometric pressure and PAR on 6/8/07, anemometer and precipitation on 3/27/07. There were no other analyses done on the meteorological data at present.

5) Site location and character

The Weeks Bay National Estuarine Research Reserve is located near the Gulf coast, southeast of the city of Fairhope, Alabama. Weeks Bay (30° 23' N, 87° 50' W) is a small, shallow, microtidal sub-estuary, located on the eastern shore of Mobile Bay in the northern Gulf of Mexico. The bay is nearly diamond shaped, and its longitudinal axis (3.4 km long) runs nearly north-south from the head, where the Fish River flows in, to the mouth, where water is exchanged with Mobile Bay. Its widest point (3.1 km) is located near the center of the estuary, where the Magnolia River discharges into eastern side of Weeks Bay. Average depth is 1.4 m, although there are two areas where depths are significantly greater. The first is in the mouth of the bay, where the average depth is 6 m; the second is about 100 m upstream of the mouth of the Fish River, where the average depth is 3.5 m. Tides are principally diurnal, and have a mean range of 0.4 m. The Fish River drainage basin encompasses 14300 hectares and contributes approximately 73% to the total incoming freshwater flow with the Magnolia River supplying the rest. Mean combined discharge is 9 cubic meters per second; although freshets up to 4 times larger occur throughout the year. These characteristics result in a freshwater residence time of 13 days under average discharge conditions, with a range from 0.5 to 100 days. Salinity in Weeks Bay varies substantially both temporally and spatially. During periods of high flow in the river, salinity in the bay may be fresh from the head to the mouth, except in the deeper holes of the estuary that are not as easily flushed. However, during periods of low flow in the river, wind velocity and tidal stage are strong factors influencing salinity structure. Salinity greater than 25 ppt is infrequently observed in Weeks Bay and is usually restricted to the southern portion of the estuary near the mouth.

The weather station is located on a reserve owned bulkhead (lat 30 deg 24.89'N, long 87 deg 49.56'W) just south of the highway 98 bridge, on the west side of the mouth of the Fish River. Wind sentry, tipping bucket rain gauge, temperature/RH probe, Li-Cor quantum sensor and barometric pressure sensor are mounted along an aluminum tower between 4.8 and 7.6 meters above water surface. Specific sensor heights above mean high tide are as follows: Barometric pressure is at 4.8m, Temp/RH sensor is at 5m, PAR and rain gauge are at 7.4m, and the Wind Sentry is at 7.6m. Approximately 100 meters upstream is a YSI datalogger deployment site for the continuous monitoring of water quality.

6) Data collection period

Weather data has been collected from January 1, 2001 through December 31, 2007.
This metadata is applicable only to data collected from January 1, 2007 00:00 through December 31, 2007 23:45.

7) Distribution

NOAA/ERD retains the right to analyze, synthesize and publish summaries of the NERRS System-wide Monitoring Program data. The PI retains the right to be fully credited for having collected and processed the data. Following academic courtesy standards, the PI and NERR site where the data were collected will be contacted and fully acknowledged in any subsequent publications in which any part of the data are used. Manuscripts resulting from this NOAA/OCRM supported research that are produced for publication in open literature, including refereed scientific journals, will acknowledge that the research was conducted under an award from the Estuarine Reserves Division, Office of Ocean and Coastal Resource Management, National Ocean Service, National Oceanic and Atmospheric Administration. The data set enclosed within this package/transmission is only as good as the quality assurance and quality control procedures outlined by the enclosed metadata reporting statement. The user bears all responsibility for its subsequent use/misuse in any further analyses or comparisons. The Federal government does not assume liability to the Recipient or third persons, nor will the Federal government reimburse or indemnify the Recipient for its liability due to any losses resulting in any way from the use of this data.

NERR weather data and metadata can be obtained from the Research Coordinator at the individual NERR site (please see Principal investigators and contact persons), from the Data Manager at the Centralized Data Management Office (please see personnel directory under the general information link on the CDMO home page) and online at the CDMO home page <http://cdmo.baruch.sc.edu/>. Data are available in comma separated format.

8) Associated researchers and projects

The System-Wide Monitoring Program (SWMP) also includes 4 hydrographic stations within Weeks Bay where dataloggers collect water temperature, salinity and conductivity, pH, dissolved oxygen turbidity and depth. These data are collected every 15 minutes continuously. At the 4 hydrographic stations, nutrient data are collected once a month at low tide and at one site twelve samples are collected for nutrients over a tidal cycle (low tide to low tide). Nutrient data collected are total dissolved phosphorus, nitrate, nitrite, ammonia, and chlorophyll. Both nutrient and hydrographic (water quality) data are maintained at the CDMO.

The Geological Survey of Alabama, in cooperation with the United States Geological Survey, maintains two rain gauges within the Weeks Bay watershed. One is located at the highway 98 Magnolia River overpass; the other is located at the highway 104 Fish River overpass.

The following researchers have directly requested and received meteorological data generated from the Weeks Bay weather station for use as either primary or ancillary information significant to their respective projects:

Caffrey, Jane. University of West Florida. Modeling estuarine ecosystem trophic status using continuous nitrate and water quality data.

Canion, Andrew. University of South Alabama.

Murrah, Adam. Mississippi State University.

II. Physical Structure Descriptors

9) Sensor specifications

Parameters: Temperature and Relative Humidity
Units: Celsius for temperature and percent for relative humidity
Sensor type: Campbell Scientific
Model #: HMP45C
Operating Temperature: -40-+60°C
Temperature Measurement Range: -40 to +60°C
Temperature Accuracy: ± 0.2 °C @ 20°C
Relative Humidity Measurement Range: 0-100% non-condensing
RH Accuracy: at 20°C: $\pm 2\%$ RH(0-90%) and $\pm 3\%$ (90-100%)
Temperature dependence of RH measurement: $\pm 0.05\%$ RH/°C
Date of Last calibration: 08/06/07

Parameters: Wind Speed and Wind Direction
Units: Wind speed - meter per second (m/s); Wind direction – compass degrees
Sensor type: RM Young Wind Monitor (marine version)
Model # 5106m
Range: 0-50 m/s; 360° mechanical
Date of last calibration: 3/27/07

Parameter: LI-COR Quantum Sensor
Units: mmol m⁻² (total flux)
Sensor type: High stability silicon photovoltaic detector (blue enhanced)
Model #: LI190SB
Light spectrum waveband: 400 to 700 nm
Temperature dependence: 0.15% per °C maximum
Stability: $<\pm 2\%$ change over 1 yr
Operating Temperature: -40°C to 65°C; Humidity: 0 to 100%
Sensitivity: typically 5 μ A per 1000 μ moles s⁻¹ m⁻²
Date of last calibration: 06/08/07

Parameter: Precipitation
Units: millimeters (mm)
Sensor type: Tipping Bucket Rain Gauge
Model #: TE525
Rainfall per tip: 0.01 inch
Operating range: Temperature: 0° to 50°C; Humidity: 0 to 100%
Accuracy: $\pm 1.0\%$ up to 1 in./hr; $\pm 0, -3\%$ from 1 to 2 in./hr; $\pm 0, -5\%$ from 2 to 3 in./hr

Date of Last calibration: 03/27/08

The CR1000 has 2 MB of Flash EEPROM that is used to store the Operating System. Another 128 K Flash is used to store configuration settings. A minimum of 2 MB SRAM is (4 MB optional upgrade) available for program storage (16K), operating system use, and data storage. Additional storage is available by using a compact flash card in the optional CFM100 Compact Flash Module.
CR1000 installed: 7/31/2006

10) Coded variable definitions - List the sampling station, sampling site code, and station code used in the data.

Sampling station:	Sampling site code:	Station code:
Weeks Bay	wb	wkbwbmet

11) QAQC flag definitions

QAQC flags provide documentation of the data and are applied to individual data points by insertion into the parameter's associated flag column (header preceded by an F_). During primary automated QAQC (performed by the CDMO), -5, -4, and -2 flags are applied automatically to indicate data that is above or below sensor range, or missing. All remaining data are then flagged 0, as passing initial QAQC checks. During secondary and tertiary QAQC 1, -3, and 5 flags may be used to note data as suspect, rejected due to QAQC, or corrected.

- 5 Outside High Sensor Range
- 4 Outside Low Sensor Range
- 3 Data Rejected due to QAQC
- 2 Missing Data
- 1 Optional SWMP supported parameter
- 0 Passed Initial QAQC checks
- 1 Suspect Data
- 2 Open-reserved for later flag
- 3 Open-reserved for later flag
- 4 Historical Data: Pre-Auto QAQC
- 5 Corrected Data

12) QAQC code definitions – This section details the secondary QAQC Code definitions used in combination with the QAQC flags above. Include the following excerpt.

QAQC codes are used in conjunction with QAQC flags to provide further documentation of the data and are also applied by insertion into the associated flag column. There are three (3) different code categories, general, sensor, and comment. General errors document general problems with the deployment or YSI datasonde, sensor errors are sensor specific, and comment codes are used to further document conditions or a problem with the data. Only one general or sensor error and one comment code can be applied to a particular data point.

General Errors

GIM Instrument Malfunction

GMT	Instrument Maintenance
GPF	Power Failure / Low Battery
GQR	Data Rejected Due to QA/QC Checks
GPR	Program Reload
GPD	Power Down

Sensor Errors

SIC	Incorrect Calibration Constant, Multiplier or Offset
SSN	Not a Number / Unknown Value
SNV	Negative Value
SOC	Out of Calibration
SSM	Sensor Malfunction
SSR	Sensor Removed

Comments

CAF	Acceptable Calibration/Accuracy Error of Sensor
CDF	Data Appear to Fit Conditions
CRE	Significant Rain Event
CSM	See Metadata

13) Other remarks/notes

Data are missing due to equipment or associated specific sensors not being deployed, equipment failure, time of maintenance or calibration of equipment, or repair/replacement of a sampling station platform. Missing data codes from 09/22/07 0400 to 12/05/07 reflect actual missing data and falsely coded data that appears robust. Missing data is due to the loss of downloaded SWMP tables. GOES tables which do not include min and max value calculations are incorporated during this time period. The GOES tables are incomplete presumably due to periods of time in which the weather station was out of contact with the satellite. If additional information on missing data is needed, contact the Research Coordinator at the reserve submitting the data.

Small negative PAR values are within range of the sensor and are due to normal errors in the sensor and the CR1000 Datalogger. The Maximum signal noise error for the Licor sensor is +/- 2.214 mmol/m² over a 15 minute interval.

Relative Humidity data greater than 100 are within range of the sensor accuracy of +/-3%.