

Wells (WEL) NERR Nutrient Metadata
(January 2003-December 2003)
Latest Update: July 22, 2025

I. Data Set & Research Descriptors

1. Principal investigator(s) and contact persons

Reserve Contacts:

Michele Dionne, Research Director
Wells National Estuarine Research Reserve
342 Laudholm Farm Road
Wells, Maine 04090
Phone: 207-646-1555 x 136
Email: dionne@WellsNERR.org

Cayce Dalton, SWMP Program
(Note: Jim Dochtermann and Scott Orringer were SWMP Research Associates at time of sample collection, but do not presently work at Wells NERR.)
Wells National Estuarine Research Reserve
342 Laudholm Farm Road
Wells, Maine 04090
Phone: 207-646-1555 x 103
Email: cayce@WellsNERR.org

Laboratory Contact:

Pallavi Mittal (Research Technician)
Estuarine and Coastal Chemistry Laboratory
Ocean Process Analysis Laboratory
Institute for the Study of Earth, Oceans, and Space (EOS)
University of New Hampshire
Room 381 Morse Hall
39 College Road
Durham, NH 03824-3525
Phone: 603 862 1542
Fax: 603 862 0243
email: pmittal@cisunix.unh.edu
website: <http://www.opal.sr.unh.edu/>

Carol Pollard
Virginia Institute of Marine Science
College of William and Mary
P.O. Box 1346 (for regular mailing)

Rt. 1208, Greate Road (for shipping)
Gloucester Point, Virginia 23062-1346
Phone: (804) 684-7213
Fax: 804.684.7097
Email: pollard@vims.edu
Website: <http://www.vims.edu/>

Other Contacts and Programs: None

2. Research Objectives

Monthly Grab Program:

The monthly grab samples provide data for 5 additional water quality variables to supplement the 30-minute interval data stream from the YSI 6600's. Grabs are collected from a similar depth stratum as the YSI datalogger (within 1m of the depth of the probes) at each site. These variables (nitrate, nitrite, ammonium, phosphate, silicate and chlorophyll a) are important indicators of estuarine trophic status and point and non-point sources of nutrient enrichment. Although limited, these data enable estimation of average trophic status, and may demonstrate seasonal patterns. Our datalogger monitoring design allows for gradient analysis from head of tide to inlet in the Webhannet estuary, allowing comparison of the Little River and Webhannet River estuaries at their inlets, where they exchange water directly with the Atlantic Ocean. Monthly grab data provide the basis for investigation of questions regarding watershed and marine inputs of nutrients in Wells NERR estuaries, and nutrient influence on trophic status as indicated by chlorophyll a.

Diel Sampling Program:

At the Webhannet Inlet site, the monthly grab samples are augmented with a 24-hour sampling series (at 2 hr intervals for a total of 24 samples – 2 replicate samples per 2 hr interval). These data can provide estimates of temporal variation in nutrients and chlorophyll on the scale of hours, providing a context for interpretation of data collected less frequently. This finer scale information will also inform interpretation SWMP grab sample data. These data can be used to investigate the relationship between nutrients, chlorophyll, and dissolved oxygen, an integrator of water column metabolism.

3. Research Methods

Monthly Grab Program:

Monthly grab samples are collected at 3 sites in the Webhannet River Estuary and 1 site in the Little River Estuary. These sites coincide with the four data sonde sites: Head of Tide (HT), Mile Road (ML), and Inlet (IN) in the Webhannet River; and the Mouth (LM) in the Little River. All grab samples are taken within a 24-hour period, and efforts are made to sample between +/- 3 hours slack-low tide. Efforts are also made to allow for a previous dry period of 72 hours prior to sampling, however this was not always possible due to lengthy periods of inclement weather. Sampling events are staggered each month at the optimal low tide, to the best of the research staff's ability. Replicate (N=2) 1-liter

samples are collected with a homemade grab sampler at a depth of 0.5 meters below the water surface at the HT, ML, and LM sites. Replicate (N=2) samples at the IN site are taken by pumping the sample up through the ISCO sampler. All samples are collected in 1-liter wide-mouth amber nalgene bottles that were previously washed with Fisher brand Versa-Clean and water, acid washed (10%), rinsed (3x) with distilled-deionized water, dried, and rinsed (3x) with ambient water prior to collection of the sample. Samples are immediately placed on ice in a dark cooler, and returned to the laboratory for immediate processing.

Diel Sampling Program:

Diel samples are collected once a month, during the same 24-hour period as our grab sample collection, at the Webhannet River Inlet (IN) datalogger site. An ISCO 6700 automated sampler is deployed on a floating dock at the Wells Harbor Pier. As with the grab samples, efforts are made to begin the automated sampling between +/- 3 hours slack-low tide. Efforts are also made to allow for a previous dry period of 72 hours prior to sampling, however this was not always possible due to lengthy periods of inclement weather. Sampling events are staggered each month at the optimal low tide, to the best of the research staff's ability. Two replicate samples of 1-liter each are taken every 2-hours over the 24-hour period for a total of 24 samples. All samples are pumped into ISCO 1-liter polypropylene wedge sample bottles that were previously washed with Fisherbrand Versa-Clean and water, acid washed (10%), rinsed (3x) with distilled-deionized water and dried prior to collection of the sample. The ISCO sampler is filled with ice prior to deployment, and at the end of the 24-hour period the sample bottles are immediately capped, kept in the dark, and returned to the laboratory for immediate processing.

Once back in the Wells NERR laboratory, samples are shaken and processed for nutrient and Chlorophyll-a analysis. All samples are filtered at the Wells NERR. The Chl-a analysis is completed on-site at the Wells NERR laboratory with a Turner Designs 10-AU field fluorometer, and the nutrient analysis takes place at the University of New Hampshire Estuarine and Coastal Chemistry Laboratory.

The nutrient processing methodology includes filtering 50 ml of a sample through 25 mm, 0.45 µm HV Millipore Durapore® membrane filters using a Becton, Dickinson and Co. (BD) 60ml polyethylene syringe with Luer-Lok® tip locked to a Millipore Swinnex 25 mm polypropylene filter holder. If a sample is particularly turbid, a 25 mm PALL A/E Glass Fiber Filter is used to filter the sample prior to filtering through the 0.45 µm Millipore filter. The liquid volume of the filtered sample is collected into a Fisherbrand 50 ml polypropylene centrifuge tube (after rinsing collection tube (3x) with sample) and placed in the freezer until brought down to the University of New Hampshire for analysis.

The Chl-a processing methodology here at the Wells NERR Research Laboratory follows the non-acidification method, "A Procedure For Measuring Extracted Chlorophyll a Free From The Errors Associated With Chlorophyll b and Pheopigments", adapted from the EPA Method 445.0: "In Vitro Determination of Chlorophyll a and Pheophytin a in Marine and Freshwater Algae by Fluorescence." This methodology includes filtering 600-1000 ml of a sample through 47 mm Whatman® GF/F filters using a vacuum pump

and filter flask apparatus, and to determine the Chl-a concentration we use a Turner Designs 10-AU Field Fluorometer.

All laboratory glassware, centrifuge tubes, syringes, filter holders, 1-liter graduated cylinders, and forceps were previously washed with Fisherbrand Versa-Clean and water, acid washed (10%), rinsed (3x) with distilled-deionized water and dried prior to filtration of the sample; and rinsed (3x) between samples with distilled-deionized water to avoid any contamination.

4. Site location and character

The Wells National Estuarine Research Reserve is located in York County, within the Town of Wells, on the coast of southern Maine and faces the Atlantic Ocean. The Wells NERR is approximately 31 km (20 miles) south of Portland, Maine and 110 km (70 miles) north of Boston, Massachusetts. The Reserve encompasses 1,690 acres along the Gulf of Maine coastline of tidally-flushed wetlands, riparian and transitional upland fields and forests within the Little River Estuary and the larger Webhannet River Estuary. Both estuaries arise in the sandy glacial outwash plain about eight miles inland. Both rivers empty into Wells Bay, a sandy basin stretching for approximately ten miles along the Atlantic coast. Bordering each river's inlet are double spit barrier beaches attached to the mainland. The backbarrier system in the Webhannet River Estuary is approximately 5 sq. km and is composed of large intertidal marshes (predominantly *S. patens* and *S. alterniflora*), intertidal sand and mud flats, and tidal channels. The watershed for the Webhannet River estuary covers an area of 35 sq. km and has a total of 6 streams, brooks or creeks, which enter the estuary. These tributaries flow across sand and gravel deposits near the headwaters and the impermeable sandy muds of the Presumpscot Formation in the lower reaches.

The watershed for the Little River estuary covers an area of 84 sq. km and has a total of 2 tributaries. The backbarrier system in the Little River Estuary is approximately 2.51 sq. km and is composed of large intertidal marshes (predominantly *S. patens* and *S. alterniflora*), intertidal sand and mud flats, and tidal channels. The Webhannet River is connected to the ocean via Wells Inlet, which has a spring tidal prism of 28,200,000 cub. m (Ward 1993). The Little River is connected to the ocean by an unstructured, double spit system and is one of the few tidal inlets along the southern Maine coast that is not stabilized by either natural outcrops or artificial jetties. The force and volume of tidal action affect the salinity level of both rivers. In the Wells region, the annual mean wave height is almost 20 inches. These estuarine systems are dominated by semi-diurnal tides having a range of 8.5 to 9.8 feet. The volume of freshwater influx into both estuaries is moderate to low (on the order of 0.5 cubic meters/second), especially in the summer, because of the rivers' relatively small drainage areas and the presence of deep glacial deposits. The relatively low flows from these two rivers taken in with the 20 inch per year average runoff of the area surrounding the estuaries combine to form a fresh water flow, which is dwarfed by tidal flushing. Twelve-foot tides dwarf the freshwater flow into the Webhannet estuary, which has a drainage area of 14.1 square miles. The Merrilland River and Branch Brook meet south of Route 9 to form the Little River, which drains an area of 10.75 sq. miles. The Webhannet estuary, fed by both Blacksmith and

Depot Brooks, is adjacent to the harbor and greatly developed land. It offers a valuable opportunity for comparison with the relatively pristine Little River estuary. The land use of the Webhannet estuary include a total of 15% for wetland, fresh water, and tidal marsh; a total of 63.7 % for woodland; and a total of 18.6% for developed land compared to a total of 5.7% development in the Little River estuary (WNERR RMA 1996; Holden 1997).

The following information regarding annual weather patterns in the area was supplied by Maine State Climatologist Professor Gregory A. Zielinski extracted from "Monthly Station Normals of Temperature, Precipitation, Heating and Cooling Degree Days 1971-2000", Climatology of the United States No. 81, National Oceanic and Atmospheric Administration, National Climatic Data Center, Asheville, NC. and "Daily Normals of Temperature, Precipitation, and Heating and Cooling Degree Days, 1971-2000", Climatology of the United States No. 84: "Average monthly temperatures range from 21.6F in January to 66.7F in July with daily highs averaging just below freezing in January and lows around 11F. Daily highs in July average around 76F and daily lows around 57F. The sea breeze often keeps daily highs lower during the summer than areas inland. Annual average temperature is 44.6F. Annual precipitation is 47.07 inches, including the water equivalent of snowfall, with monthly averages ranging from 3.01 inches in July to 4.77 inches in October. August receives just 3.02 inches on average. Annual snowfall is around 66 inches." According to Zielinski, "cool ocean temperatures keep down the number of afternoon showers and especially thunderstorms resulting in low summer precipitation amounts."

There are three sampling sites in the Webhannet River estuary. These are located at the Head of Tide (HT), Mile Road (ML), and at the Inlet (IN). The tidal range at each of these sites is 2.6-2.9 meters. There is one sampling site in the Little River estuary, the Little River Mouth (LM). The tidal range of the Little River estuary is 2.6-3.0 meters (Mariano and FitzGerald, 1988).

The Head of Tide site is located 4 miles south of the Wells Reserve, just downstream of the Webhannet Falls (freshwater) and 10 feet east of Route One (43 deg 17' 54.25227" Latitude, 70 deg 35' 13.82728" Longitude). Route One is used heavily with traffic all year, especially during the summer tourist months. This site has soft mud, sand, and a rocky substrate, and the low and high tide depth is relatively shallow. The salinity range here is 0-31 ppt, with a mean of 3.6 ppt. These headwaters of the Webhannet are relatively undeveloped. This site is located just 10 feet east of the Route One bridge, and is our roving site.

The Mile Road site is located 3.5 miles south of the Wells Reserve, on Mile Road roughly 300' north of the bridge (N43 deg 18.300' Latitude, W 70 deg 34.583 Longitude). This site has soft mud and a rocky substrate, and the low and high tide depth is relatively shallow. The salinity range here is 3.6-33.4 ppt, with a mean of 27.0 ppt. The Mile Road site is our creek site.

The Inlet site is located 1.5 miles south of the Wells Reserve, at the Wells Harbor pier (43 deg 19' 12.44804" Latitude, 70 deg 33' 13.82728" Longitude). The mouth of the Webhannet estuary forms an extensive wetland/salt marsh area, which is surrounded by development. Wells Harbor, which was most recently dredged in 1971, has moorings for approximately 200 commercial fishing and recreational boats. The mouth of the river flows between two jetties to the Atlantic Ocean. This channel was dredged in 1974. This site has a predominately sand substrate and is characterized by strong current during incoming and outgoing tides. The maximum depth of the Inlet site is 3 meters. The salinity range here is 7-35 ppt, with a mean of 31 ppt. The Inlet site is heavily impacted at the Wells Harbor dock and is our long-term monitoring site.

The Little River Mouth site is located 1,270.78 meters upstream from the mouth of the estuary, and 813.94 meters direct from the Wells NERR Coastal Ecology Center (43 deg 20.413 Latitude, 70 deg 32.441 Longitude). The tidal range of the Little River estuary is 2.6-3.0 meters (Mariano and FitzGerald, 1988). The Little River sites existed in a shallow and relatively pristine system with a sandy to mud bottom and a salinity range of 0 - 32 ppt. There are two major freshwater inputs, the Merriland and Branch Brook Rivers, which converge to form the Little River. The Little River Mouth site is our comparative system site.

Note: Both original sites were abandoned due to problems with heavy sediment movement in the inlet of the Little River. We were forced to relocate the site twice. The first location (N 43 deg 20.176 Latitude, W 70 deg 32.497 Longitude) was located in the main channel of the river, just inland of a spit, beside a bank. The second location (N 43 deg 20.083 Latitude, W 70 deg 32.585 Longitude) was located 1/8 mi. southwest of the first site, within an inlet, just inland of a spit. The second site was located in an area of much lower current than the first site and often drains completely during low tides. It was also placed within a pool next to incipient low marsh peat that retains calm water during low tides.

5. Code variable definitions

Site definitions:

wel = Wells NERR

welinnut = Webhannet River Inlet

welmlnut = Mile Road

welhtnut = Head of Tide

wellmnut = Little River Mouth

nut = nutrient sampling program

These abbreviations are combined to form the sample name as follows:

welinnut = sample taken from Webhannet River Inlet as part of the Wells NERR nutrient sampling program

Monitoring Programs: 1= Grab Sampling Program, 2= Diel Sampling Program

6. Data collection period

Diel Sampling

Site	Start Date	Start Time	End Date	End Time
IN	01/08/03	10:30	01/09/03	08:30
IN	02/19/03	10:30	02/20/03	08:30
IN	03/25/03	10:35	03/26/03	08:35
IN	04/21/03	11:20	04/22/03	09:20
IN	05/19/03	10:30	05/20/03	08:30
IN	06/18/03	12:30	06/19/03	10:30
IN	07/15/03	10:30	07/16/03	08:30
IN	08/20/03	15:00	08/21/03	13:00
IN	09/29/03	13:35	09/30/03	11:35
IN	10/22/03	13:35	10/23/03	11:35
IN	11/18/03	13:30	11/19/03	11:30
IN	12/18/03	11:00	12/19/03	09:00

Grab Sampling

Site	Start/End Date	Start Time	End Time
IN	01/09/03	08:30	08:32
IN	02/20/03	08:35	08:37
IN	03/26/03	09:20	09:22
IN	04/22/03	11:50	11:52
IN	05/20/03	10:35	10:37
IN	06/19/03	10:45	10:47
IN	07/16/03	09:35	09:37
IN	08/21/03	13:55	13:57
IN	09/30/03	10:40	10:42
IN	10/22/03	15:38	15:40
IN	11/19/03	12:45	12:47
IN	12/19/03	11:00	11:02

Site	Start/End Date	Start Time	End Time
HT	none taken in January		
HT	none taken in February		
HT	03/26/03	13:00	13:02
HT	04/22/03	11:25	11:27
HT	05/20/03	10:00	10:02
HT	06/19/03	10:15	10:17
HT	07/16/03	09:05	09:07

HT	08/21/03	13:20	13:22
HT	09/30/03	09:45	09:47
HT	10/22/03	15:00	15:02
HT	11/19/03	12:20	12:22
HT	Ice prevented grab sampling.		

Site	Start/End Date	Start Time	End Time
ML	01/9/03	08:15	08:17
ML	02/20/03	08:12	08:14
ML	03/26/03	13:15	13:17
ML	04/22/03	11:35	11:37
ML	05/20/03	10:15	10:17
ML	06/19/03	10:25	10:27
ML	07/16/03	09:20	09:22
ML	08/21/03	13:35	13:37
ML	09/30/03	10:00	10:02
ML	10/22/03	15:18	15:20
ML	11/19/03	12:34	12:36
ML	12/19/03	13:15	13:20

Site	Start/End Date	Start Time	End Time
This site did not exist before March, 2003			
LM	03/26/03	14:35	14:37
LM	04/22/03	13:55	14:57
LM	05/20/03	12:35	12:37
LM	06/19/03	12:05	12:07
LM	07/16/03	11:05	11:07
LM	08/21/03	15:25	15:27
LM	09/30/03	11:27	11:29
LM	10/22/03	16:35	16:37
LM	11/19/03	13:38	13:40
LM	12/19/03	15:20	15:22

7. Associated researchers and projects

Please visit our website <http://www.wellsnerr.org/research.htm> for further information on the Wells NERR research program. The Research Program at the Wells NERR conducts and supports research, monitoring, workshops, and research/resource management planning of relevance at local, regional and national levels. The overall aim of our work is to produce science-based information needed to sustain or restore Gulf of Maine coastal habitats and resources, especially those found in salt marsh estuaries and watersheds. During 2000-2001 twenty-three different studies (involving 79 scientists, students, and staff from the Reserve, 26 academic institutions and 19 resource

management groups) focused on several related themes: 1) the quality of water resources in salt marsh estuaries and watersheds 2) land conservation strategies to protect coastal watersheds 3) factors controlling salt marsh accretion, erosion and plant community vigor 4) the value of salt marsh as habitat for fish, shellfish and birds, and 5) restoration of salt marsh habitat degraded through human actions.

Estuarine Water Resource Quality

Water quality is monitored continuously at several stations with automated instruments as part of a NERRS systemwide monitoring program, as well as bimonthly at 15-20 stations through our WET volunteer monitoring program. The WET program also monitors two important biological parameters: fecal coliform bacterial contamination (an indicator of human health risk) and phytoplankton productivity (an indicator of estuarine health). These data have 1) allowed us to identify several bacterial "hot spots" that we will be working to eliminate, 2) are used to identify and open areas safe for shellfishing, and 3) have uncovered a relation between tides and low dissolved oxygen (a stressful condition for marine life) that needs further study. Our water quality work has contributed to the designation of several Priority Watersheds in coastal Southern Maine by the Maine Department of Environmental Protection.

Coastal Conservation Strategies

The Stewardship program has been developed in response to requests for support from the conservation community to increase the quantity, quality and ecological integrity of conserved lands in our region. Research staff organize and facilitate meetings, workshops, and communications for about 20 partner conservation groups. A key element of the Stewardship program is the Conservation Resource Center, a Reserve staffed GIS facility with a growing database able to provide maps of property, natural features and other data needed to develop effective conservation goals and strategies. Successful projects completed by the Stewardship Program include a conservation lands map of Southern Maine coastal towns and a series of Conservation Strategy Reports for 7 coastal watersheds within these towns. The Reserve has a particular interest in educating communities about the ecologic and economic benefits of land conservation, especially along estuarine and riverine shorelines.

Salt Marsh Habitats and Communities

Factors that control the dynamics and vigor of salt marsh plant communities and marsh peat formation consequently determine the ability of a salt marsh to persist in the face of sea level rise. Through a combination of experimental manipulations and long-term monitoring, a number of multi-year studies are currently producing data to answer questions concerning the sustainability of salt marsh habitats in this region. These studies are looking at nutrient-plant relations, plant community responses to physical and hydrologic disturbance, and the relative contribution of short-term natural events (e.g., storms) and human activities (dredging, tidal restriction) on patterns of sediment accretion and erosion. The Reserve's marshes and beaches are already among the best studied sites in the U.S. with regard to long term accretion and erosion (over thousands of years).

Habitat Value for Fish, Shellfish, and Birds

The Reserve combines long-term monitoring with periodic surveys and short-term experiments to identify species and measure trends and changes in populations of fish, crustaceans, clams and birds. We have 10 years of data on upland and shore birds with which to assess the status of resident and migratory avian populations, and 8 years of wading bird data that we use as a gross level indicator of salt marsh health, which appears to be stable. Our periodic larval, juvenile and adult fish surveys have produced the best available data for fish utilization of salt marsh estuaries in the Gulf of Maine. In the coming year we plan to develop a long-term monitoring program for finfish that will be coordinated with other sites within the Gulf of Maine and along the east coast. Since 1994 we have been conducting surveys and field experiments to look at the survival and growth of hatchery seed, juvenile and adult softshell clam with regard to habitat characteristics and predation by the invasive green crab.

Salt Marsh Degradation and Restoration

Salt marsh ecosystems in the Gulf of Maine have sustained themselves in the face of sea-level rise and other natural disturbances for nearly five thousand years. Since colonial times large areas of salt marsh (up to half of the total area) have been lost through diking, draining and filling. Today, the remaining marshland is fairly well protected from outright destruction, but during the past 100 years, and especially since the 1950's, salt marshes have been divided into fragments by roads, causeways, culverts and tide gates. Most of these fragments have severely restricted tidal flow, leading to chronic habitat degradation and greatly reduced access for fish and other marine species. Since 1991, the Wells Reserve has been studying the impact of these restrictions on salt marsh functions and values, and the response of salt marshes to tidal restoration. We have been working to promote an awareness of the damage being done and the benefits of salt marsh restoration throughout the Gulf of Maine.

Research Program Update:

In addition to the Reserve-sponsored projects outlined above, numerous visiting investigators will be involved in on-site research. Topics include: the effects of land use, sea level, and climate on estuarine productivity; the relationship between soil nutrients and plant community patterns; the influence of soil salinity on plant community interactions; the effect of tidal restriction on marsh peat accretion; the comparative ecology of fringe marshes and back barrier marshes; habitat use by upland birds, and the ecology of Lyme disease.

The Wells NERR Research Dept. is working on the following projects: "Ecological processes, energy pathways, and the impact of human activities on Maine marsh-estuarine secondary production: a salt marsh panne model". We used stable isotopic tracers (^{15}N additions and naturally abundant ^{13}C) coupled with secondary production measurements (nekton, invertebrates) to track energy flow on the high marsh surface in southern Maine salt marsh systems. The project is still under way.

"Ecological Functions of Fringing Salt Marshes Susceptible to Oil Spills in Casco Bay, Maine". We examined the ecological function of 9 different fringing marsh systems in

Casco Bay that ranged from undisturbed to disturbed. Physical parameters measured included sedimentation rates, total suspended solids, and tidal range. Biological parameters included primary production, macroinvertebrate community composition and secondary production (4cm sediment cores), and resident and transient nekton community composition (fyke net). The project is still under way.

"BENTHIC HABITAT CORRELATES OF JUVENILE FISH DISTRIBUTION IN THE BIGELOW BIGHT AND ADJACENT ESTUARIES: LINKAGES BETWEEN FISH, HABITATS, SUBSTRATE AND HUMAN ACTIVITY". This project was a collaboration between the Wells N.E.R.R. and several members of the local fishing community. Through the use of beam trawls, gill nets, fish traps, van veen ponar, and a sediment profile imager (SPI camera), we are attempting to correlate benthic habitat type to juvenile groundfish and invertebrate assemblages in estuarine, nearshore, and offshore habitat. Stations were also established near dredge spoil dump sites as well as sewage outflow to determine the impacts of human activity on the coast to benthic habitat. The project is still under way.

The Wells NERR Research Dept. also completed the work on the following project: In partnership with the York Rivers Association and the Town of York, the Wells Reserve conducted a survey of the York River watershed. In this survey, volunteers looked for sources of pollution within a 250-foot buffer of the river and its tributaries (erosion, trash and debris and runoff from roads and lawns could have a negative impact on water quality). Most pollutants entering water bodies come from such undefined sources. Therefore, this type of survey is the best way to begin to address the problems of pollution in a water body. The idea of the project was to work with the community and landowners to help them understand the problems that come from these types of pollution and learn activities they might be able to do on their own land that would help prevent this pollution from entering the water. The results of the survey will become part of a Watershed Management Plan to improve and restore the water quality of the York River.

The Wells NERR Research Dept. is involved with the following CICEET Projects-

Project Title: Estuarine Responses to Dredging: Analysis of Sedimentary and Morphological Change in Back Barrier Marsh to Aid Local Management and Develop a Regional Management Tool Principal Investigator (s): Michele Dionne, Wells NERR, ME; Duncan Fitzgerald, Boston University; Joe Kelley, University of Maine; David Burdick and Larry Ward, University of New Hampshire

Management Issue: Coastal management tool for assessing the impacts of dredging in estuaries. Project Summary: An adequate supply of sediment is essential for maintaining salt marshes. Human activities, such as channel dredging and tidal restriction due to road construction, can alter water flows in estuaries and result in dramatic changes in salt marsh sediment supply, affecting the speed of salt marsh erosion. The objective of this project is to determine the impact of dredging and tidal restriction on salt marshes in the Wells NERR. A digital coastal management guide will be created on CD ROM,

providing coastal managers with useful conceptual models for predicting the impacts of dredging and other activities that affect water flow and sediment deposition in salt marshes.

II. Project Title: Microbial Source Tracking in Two Southern Maine Watersheds. A two-year project written by Maine Sea Grant associate Kristen Whiting-Grant, and funded by Cooperative Institute for Coastal and Estuarine Environmental Technology (CICEET), involving Wells NERR, UNH Jackson Estuarine Lab (JEL), USM Muskie School, AmeriCorps and the Maine Conservation Corps. We are pioneering the use in Maine of genetic analysis as a means of determining the source species associated with bacterial contamination in the Webhannet and Little River Estuary. Volunteers collect water samples from streams and the estuaries, staff test for and isolate *E. coli*. At JEL, a genetic technique (ribotyping) creates a genetic fingerprint of the bacteria which is compared to known sources. The project was completed in 2003, although outreach is ongoing by Kristen Whiting-Grant, Maine Sea Grant and Cooperative Extension, located at Wells NERR.

The following information on CICEET taken directly from its website:
(<http://www.ciceet.unh.edu>)

Other Onsite Research:

Michele Dionne, Wells NERR, Nancy McReel, Chuck Lubelczyk.
Project Title: Effect of herbivory by deer on forest regeneration

June Ficker

Project Title: Monitoring avian productivity and survivorship

Outside Researchers:

Theresa Theodose, Ph.D., University of Southern Maine
Project Title: Relationships between soil nutrient availability and species composition of a high salt marsh in southern Maine.

David Burdick, Ph.D. and Roelof Boumans, Ph.D.

University of New Hampshire, University of Maryland

Project Title: Sediment dynamics in salt marshes: functional assessment of accretionary biofilters

Peter Rand, M.D., Chuck Lubelczyk, Robert Smith, M.D.

Maine Medical Center

Project Title: Ecological determinants of the spread of the tick vector of Lyme disease and other pathogens.

8. Distribution

NOAA/ERD retains the right to analyze, synthesize and publish summaries of the NERRS System-wide Monitoring Program data. The PI retains the right to be fully

credited for having collected and processed the data. Following academic courtesy standards, the PI and NERR site where the data were collected will be contacted and fully acknowledged in any subsequent publications in which any part of the data are used. Manuscripts resulting from this NOAA/OCRM supported research that are produced for publication in open literature, including refereed scientific journals, will acknowledge that the research was conducted under an award from the Estuarine Reserves Division, Office of Ocean and Coastal Resource Management, National Ocean Service, National Oceanic and Atmospheric Administration. The data set enclosed within this package/transmission is only as good as the quality assurance and quality control procedures outlined by the enclosed metadata reporting statement. The user bears all responsibility for its subsequent use/misuse in any further analyses or comparisons. The Federal government does not assume liability to the Recipient or third persons, nor will the Federal government reimburse or indemnify the Recipient for its liability due to any losses resulting in any way from the use of this data.

NERR water quality data and metadata can be obtained from the Research Coordinator at the individual NERR site (please see Section 1. Principal investigators and contact persons), from the Data Manager at the Centralized Data Management Office (please see personnel directory under the general information link on the CDMO home page) and online at the CDMO home page <http://cdmo.baruch.sc.edu/>. Data are available in text tab-delimited format, Microsoft Excel spreadsheet format and comma-delimited format.

II. Physical Structure Descriptors

9. Entry verification

Excel data files containing measured values (except for Chl-a which is analyzed at Wells NERR) received from the University of New Hampshire Ocean Process Analysis Lab / Estuarine and Coastal Chemistry Laboratory (OPAL) or from Virginia Institute of Marine Science (VIMS) are used to generate calculated parameter values. Both directly measured and calculated values were entered into this document by Cayce Dalton from files and notes kept by Scott Orringer and Jim Dochtermann, and from files delivered by OPAL and VIMS. The SWMP technicians at Wells NERR were responsible for a visual QA/QC to make sure no entry errors are present. The original Excel files received from UNH and VIMS are archived on the Wells NERR server. Edited files containing additional calculated parameters, are archived on the Wells NERR server and sent to CDMO for additional archiving.

10. Parameter Titles and Variable Names by Data Category

Required NOAA/NERRS System-wide Monitoring Program water quality parameters are denoted by an asterisks “*”. Nutrient parameters currently sampled at the Wells NERR are the Tier I parameters: ammonium (NH₄⁺), nitrate (NO₃⁻), nitrite (NO₂⁻), ortho-phosphate, and Chla; and the Tier II parameter: Silica.

Phosphorus:

Parameter	Variable Name	Units of Measure
*Orthophosphate	PO4F	mg/l as P

Nitrogen:

Parameter	Variable Name	Units of Measure
*Nitrite + Nitrate, Filtered	NO23F	mg/L as N
*Nitrite, Filtered	NO2F	mg/L as N
*Nitrate, Filtered	NO3F	mg/L as N
*Ammonium, Filtered	NH4F	mg/L as N

Other Lab Parameters:

Parameter	Variable Name	Units of Measure
Chlorophyll a	CHLA	µg/l

Notes:

Time is coded based on a 2400 hour clock and is referenced to Eastern Standard Time (EST).

Reserves have the option of measuring either NO23, or NO2 and NO3.

11. Measured and Calculated Laboratory Parameters

Special note on NO23 data:

For all samples processed at OPAL (January-July), NO23 is calculated as the sum of NO2 and NO3, which were processed separately.

For all samples processed at VIMS (August-December), NO23 and NO2 were each measured directly, and NO3 was calculated by subtracting NO2 from NO23.

Variables Measured Directly

Nitrogen species: NO2F, NO23F, NO3F, NH4F

Phosphorus species: PO4F

Other: CHLA

Computed Variables

NO3F: NO23F-NO2F

NO23F: NO2F + NO3F

Note: Data coded "C" in the comments column are calculated.

12. Limits of Detection

Method Detection Limits (MDL), the lowest concentration of a parameter that an analytical procedure can reliably detect, have been established by the University of New Hampshire Estuarine and Coastal Chemistry Laboratory and at the Lachat Instrument

website (<http://www.lachatinstruments.com/applications/AppsSearch.asp>). Table 1 lists the current MDL values, which are reviewed and revised periodically.

Method Detection Limits (MDL) for measured water quality parameters. The following MDL's were provided by the laboratory at the time the data indicated were provided.

	NH4F mg/L	NO2F mg/L	NO3F mg/L	PO4F mg/L	NO23F mg/L
OPAL data: January only	0.0014	0.0007	0.0011	0.0007	n/a
OPAL data: February- July	0.0042	0.0070	0.0070	0.0009	n/a
VIMS data (Aug-Dec)	0.0054	0.0002	n/a	0.0015	0.001

NOTE on Data Reporting & Rounding for OPAL data:

According to Lachat Instruments (1-800-247-7613), the Quick Chem 8000, while running with the 2.0 software, has a precision to 4 decimal places (rounding up from 5).

NOTE regarding Chlorophyll *a* limits of measurement:

Method 445.0 *In Vitro* Determination of Chlorophyll *a* and Pheophytin *a* in Marine and Freshwater Algae by Fluorescence"

Elizabeth J. Arar and Gary B. Collins

Revision 1.2, September 1997

National Exposure Research Laboratory, Office of Research and Development, USEPA, Cincinnati, OH 45268

"Instrument detection limits of 0.05 µg chl *a*/L and 0.06 µg pheo *a*/L in a solution of 90% acetone were determined by this laboratory. Method detection limits (MDL) using mixed assemblages of algae provide little information because the fluorescence of other pigments interferes in the fluorescence of chlorophyll *a* and pheophytin *a*. A single lab estimated detection limit for chlorophyll *a* was determined to be 0.11 µg/L in 10 mL of final extraction solution. The upper limit of the linear dynamic range for the instrumentation used in this method evaluation was 250 µg chl *a*/L."

13. Laboratory Methods

Section 13, Part I: Analyses conducted by Ocean Process Analysis Laboratory at University of New Hampshire (OPAL).

The following information is taken from the website below as directed from Pallavi Mittal (Research Technician) from the UNH Estuarine and Coastal Chemistry Laboratory.

<http://www.lachatinstruments.com/applications/AppsSearch.asp>

NH4 QuickChem Method 31-107-06-1-A 0.07 to 3.57 μM

NO3 and NO2 31-107-04-1-A 0.005 to 5 μM N/L 0.07 to 70 mg N/L

PO4 31-115-01-1-1 1 to 100 μM P/L 0.03 to 3.23 μM P

SiO2 31-114-27-1-B 0.03 to 5 μM SiO2/L 0.5 to 100 μM SiO2/L

Parameter: Orthophosphate, PO4F

Method References:

University of New Hampshire Estuarine and Coastal Chemistry Laboratory

Copyright 2000-2002, Lachat Instruments. All rights reserved. Legal notice

Revision Date: 6/27/2001

PO4 31-115-01-1-1 1 to 100 μM P/L 0.03 to 3.23 μM P

Orthophosphate in Seawaters

Method No: 31-115-01-1-I

Product Line: Flow Injection Analysis

Matrix: Brackish or seawater

Range

Analyte

Range

MDL

Units

Phosphate, ortho

1 to 100

0.25

μM P/L

Principle

Ammonium molybdate and antimony potassium tartrate reacts in an acid medium with phosphate to form an antimony-phospho-molybdate complex. This complex is reduced to an intensely blue-colored complex by ascorbic acid. The color produced is proportional to the phosphate concentration in the sample. Though there is a density difference between seawater and reagent water the bias is less than 2%. Though the method is written for seawater and brackish water it is also applicable to non-saline sample matrixes. The method is calibrated using standards prepared in deionized water. Once calibrated, samples of varying salinities (0 to 35 ppt) may be analyzed. The determination of background absorbance is necessary only for samples, which have color absorbing at 880 nm.

Interferences

Silica forms a pale blue complex, which also absorbs at 880 nm. This interference is generally insignificant as a silicate concentration of approximately 5 mg SiO2/L would be required to produce a 0.14 μg P/L positive error in orthophosphate. See Section 11.2. High iron can cause precipitation of and subsequent loss of phosphate from the dissolved phase.

Using ascorbic acid as the reductant, the color intensity is not influenced by variations in salinity. Stannous chloride reductant does show a significant salt effect.

Turbidity is removed by filtration.

Hydrogen sulfide effects, such as those occurring in samples from deep anoxic basins, can be treated by simple dilution since high sulfide concentrations are most often associated with high phosphate values.

Special Apparatus

Please see Parts and Price list for Ordering Information

Heating Unit

Glass calibration vials must be used for this method (Lachat Part No. 21304)

Preservation Method:

The nutrient processing methodology includes filtering 50 ml of a sample through 25 mm, 0.45 µm HV Millipore Durapore® membrane filters using a Becton, Dickinson and Co. (BD) 60ml polyethylene syringe with Luer-Lok® tip locked to a Millipore Swinnex 25 mm polypropylene filter holder. If a sample is particularly turbid, a 25 mm PALL A/E Glass Fiber Filter is used to filter the sample prior to filtering through the 0.45 µm Millipore filter. The liquid volume of the filtered sample is collected into a Fisherbrand 50 ml polypropylene centrifuge tube (after rinsing collection tube (3x) with sample) and placed in the freezer until brought down to the University of New Hampshire for analysis.

Parameter: Nitrate + Nitrite, NO₂F + NO₃F

Method References:

University of New Hampshire Estuarine and Coastal Chemistry Laboratory

Copyright 2000-2002, Lachat Instruments. All rights reserved. Legal notice

Revision Date: 2/27/2001

NO₃ and NO₂ 31-107-04-1-A 0.005 to 5 µM N/L 0.07 to 70 mg N/L

Nitrate/Nitrite in Brackish Waters or Seawater

Method No: 31-107-04-1-A

Product Line: Flow Injection Analysis

Matrix: Brackish or seawater

Range

Analyte	Range	MDL	Units
Nitrate + Nitrite	1.25 to 5.0	0.03	µM N

Principle

Nitrate is quantitatively reduced to nitrite by passage of the sample through a copperized cadmium column. The nitrite (reduced nitrate plus original nitrite) is then determined by diazotization with sulfanilamide under acidic conditions to form a diazonium ion. The resulting diazonium ion is coupled with N-(1-naphthyl)ethylenediamine dihydrochloride. The resulting pink dye absorbs at 520 nm. Nitrate concentrations are obtained by subtracting nitrite values, which have been previously analyzed, from the nitrite + nitrate values.

Though the method is written for seawater and brackish water, it is also applicable to non-saline sample matrixes.

The method is calibrated using standards prepared in deionized water. Once calibrated, samples of varying salinities (0 to 35 ppt) may be analyzed. The determination of

background absorbance is necessary only for samples which have color absorbing at 540 nm. The salt effect is less than 2%.

Interferences

No Interferences

Special Apparatus

Please see Parts and Price list for Ordering Information

No Special Apparatus

Preservation Method:

The nutrient processing methodology includes filtering 50 ml of a sample through 25 mm, 0.45 μ m HV Millipore Durapore® membrane filters using a Becton, Dickinson and Co. (BD) 60ml polyethylene syringe with Luer-Lok® tip locked to a Millipore Swinnex 25 mm polypropylene filter holder. If a sample is particularly turbid, a 25 mm PALL A/E Glass Fiber Filter is used to filter the sample prior to filtering through the 0.45 μ m Millipore filter. The liquid volume of the filtered sample is collected into a Fisherbrand 50 ml polypropylene centrifuge tube (after rinsing collection tube (3x) with sample) and placed in the freezer until brought down to the University of New Hampshire for analysis.

Parameter: Ammonia, NH₄F

Method References:

University of New Hampshire Estuarine and Coastal Chemistry Laboratory

Copyright 2000-2002, Lachat Instruments. All rights reserved. Legal notice

Revision Date: 6/6/2001

NH₄ QuickChem Method 31-107-06-1-A 0.07 to 3.57 μ M

Ammonia (Phenolate) in Brackish Waters

Method No: 30-107-06-1-A

Product Line: Flow Injection Analysis

Matrix: Brackish waters

EPA Ref No: 350.1

Range

Analyte	Range	MDL	Units
Ammonia	0.1 to 20.0	N/A	mg N/L

Principle

This method is based on the Berthelot reaction. Ammonia reacts with alkaline phenol, then with sodium hypochlorite to form indophenol blue. Sodium nitroprusside (nitroferricyanide) is added to enhance sensitivity. The absorbance of the reaction product is measured at 630 nm, and is directly proportional to the ammonia concentration.

Interferences

EDTA is added to the sample in-line to prevent precipitation of calcium and magnesium as the hydroxides.

Color, and turbidity may interfere. Turbidity is removed by manual filtration. Sample color may be corrected for by running the samples through the manifold without color formation.

Residual chlorine must be removed prior to analysis.

The matrix can vary from fresh to deep-sea water salinity with no effect.

Special Apparatus

Please see Parts and Price list for Ordering Information

Heating Unit (Lachat Part No. A85100)

Preservation Method:

The nutrient processing methodology includes filtering 50 ml of a sample through 25 mm, 0.45 μ m HV Millipore Durapore® membrane filters using a Becton, Dickinson and Co. (BD) 60ml polyethylene syringe with Luer-Lok® tip locked to a Millipore Swinnex 25 mm polypropylene filter holder. If a sample is particularly turbid, a 25 mm PALL A/E Glass Fiber Filter is used to filter the sample prior to filtering through the 0.45 μ m Millipore filter. The liquid volume of the filtered sample is collected into a Fisherbrand 50 ml polypropylene centrifuge tube (after rinsing collection tube (3x) with sample) and placed in the freezer until brought down to the University of New Hampshire for analysis.

Section 13, part II: Analysis conducted at Virginia Institute of Marine Science (VIMS)

Parameter: Orthophosphate, PO₄F

Method References: Virginia Institute of Marine Science Analytical Service Center.

SKALAR Method: O-Phosphate / Total Phosphate Catnr. 503-365.1, issue

042993/MH/93-Demo1. Murphy, J. and J.P. Riley. 1962. A modified single solution

method for the determination of phosphate in natural waters. *Analytica Chim. Acta* 27 :

31-36. EPA 600/R-97/072 Method 365.5 Determination of Orthophosphate in Estuarine and Coastal Waters by Automated Colorimetric Analysis. IN: *Methods for the*

Determination of Chemical Substances in Marine and Estuarine Environmental Matrices - 2nd Edition. National Exposure Research Laboratory, Office of Research and Development . U.S. EPA, Cincinnati, Ohio 45268.

Method Descriptor: Instrumentation: SKALAR San-Plus continuous flow autoanalyzer.

Ammonium molybdate and antimony potassium tartrate react in a sulfuric acid environment to form an antimony-phospho-molybdo complex, which is reduced to a blue colored complex by ascorbic acid. Reaction is heat catalyzed at 40°C and measured colorimetrically at 880nm. The range is 1-50 ppb. Preservation Method: 100 ml of a sample is filtered through 0.45 μ m Millipore filters using a vacuum-pump and a filtering flask apparatus. If samples are extremely dirty a 47mm GF/C filter may be used to filter the sample prior to filtering through the 0.45 μ m Millipore filter. The liquid volume of

the filtered sample is collected into a Nalgene bottle and placed in the freezer until shipment time arrives the following day.

Parameter: Nitrite Method References: Virginia Institute of Marine Science Analytical Service Center. SKALAR Method 467

Method Descriptor: Instrument is SKALAR San-Plus continuous flow autoanalyzer. An adaptation of the diazotization method. Under acidic conditions, nitrite ion reacts with sulfanilimide to yield a diazo compound which couples with N-1-naphthylethylenediamine dihydrochloride to form a soluble dye which is measured colorimetrically at 540nm. The range is 0.001 to 0.050 mg/L.

Preservation Method: 100ml of a sample is filtered through 0.45µm Millipore filters using a vacuum-pump and a filtering flask apparatus. If samples are extremely dirty a 47mm GF/C filter may be used to filter the sample prior to filtering through the 0.45µm Millipore filter. The liquid volume of the filtered sample is collected into a Nalgene bottle and placed in the freezer until shipment time within three days. (Note that all 2003 samples analyzed by VIMS were held much longer due to slow turn around time by first lab.)

Parameter: Nitrate + Nitrite, NO₂F + NO₃F

Method References: Virginia Institute of Marine Science Analytical Service Center. SKALAR Method: Nitrate + Nitrite/ Total Dissolved Nitrogen Catnr. 461-353.2 issue 120293/MH/93128060. U.S. EPA. 1974 Methods for Chemical Analysis of Water and Wastes, pp. 207 -212. Wood, E.D., F.A.G. Armstrong and F.A. Richards. 1967. Determination of nitrate in seawater by cadmium-copper reduction to nitrite. J. Mar. Biol. Assoc. U.K. 47: 23. Grasshoff, K., M. Ehrhardt and K. Kremling. 1983. Methods of Seawater Analysis. Verlag Chemie, Federal Republic of Germany. 419 pp. EPA 600/R-97/072 Method 353.4 Determination of Nitrate and Nitrite in Estuarine and Coastal Waters by Gas Segmented Flow Colorimetric Analysis. IN: Methods for the Determination of Chemical Substances in Marine and Estuarine Environmental Matrices – 2nd Edition. National Exposure Research Laboratory, Office of Research and Development U.S. EPA, Cincinnati, Ohio 45268.

Method Descriptor: Instrumentation: SKALAR San-Plus continuous flow autoanalyzer. Nitrate is reduced to nitrite by a copper/cadmium sulfanil column. The nitrite ion then reacts with sulfanilamide to form a diazo compound. This compound then couples with n-1-naphthylenediamine dihydrochloride to form a reddish/purple azo dye and is read colorimetrically at 540 nm. Nitrate concentration is obtained by subtracting the corresponding nitrite value from the NO₃⁻ + NO₂⁻ concentration. The color development chemistry is the same as that used in Nitrite. Range is 0 -1.2 mg/L.

Preservation Method: 100 ml of a sample is filtered through 0.45 µm Millipore filters using a vacuum-pump and a filtering flask apparatus. If samples are extremely dirty a 47 mm GF/C filter may be used to filter the sample prior to filtering through the 0.45 µm

Millipore filter. The liquid volume of the filtered sample is collected into a Nalgene bottle and placed in the freezer until shipment time arrives the following day.

Parameter: Ammonia, NH₄F

Method References: Virginia Institute of Marine Science Analytical Service Center. U.S. EPA. 1974. Methods for Chemical Analysis of Water and Wastes, pp. 168-174. Standard Methods for the Examination of Water and Wastewater, 14th edition. p 410. Method 418A and 418B (1975). Annual Book of ASTM Standards, Part 31. "Water", Standard 1426-74, Method A, p 237 (1976). EPA 600/R-97/072 Method 349.0. Determination of Ammonia in Estuarine and Coastal Waters by Gas Segmented Continuous Flow Colorimetric Analysis. IN: Methods for the Determination of Chemical Substances in Marine and Estuarine Environmental Matrices - 2nd Edition. National Exposure Research Laboratory, Office of Research and Development U.S. EPA, Cincinnati, Ohio 45268.

Method Descriptor: Instrument is SKALAR San-Plus continuous flow autoanalyzer. Alkaline phenol and hypochlorite react with ammonia to form indophenol blue that is proportional to the ammonia concentration. The blue color formed is intensified with sodium nitroprusside. Reaction is heat catalyzed at 37°C and is measured colorimetrically at 660 nm. The range is 0.01 – 2.0 mg/L.

Preservation Method: 100ml of a sample is filtered through 0.45µm Millipore filters using a vacuum-pump and a filtering flask apparatus. If samples are extremely dirty a 47mm GF/C filter may be used to filter the sample prior to filtering through the 0.45µm Millipore filter. The liquid volume of the filtered sample is collected into a Nalgene bottle and placed in the freezer until shipment time arrives the following day.

Section 13, part III: Analysis conducted at Wells NERR.
Analyses conducted by Wells NERR.

Parameter: Chlorophyll a, CHLA

Method References:

Wells National Estuarine Research Reserve Coastal Ecology Center Laboratory
Strickland, J.D.H., and Parson, T.R. 1972. A Practical Handbook of Seawater Analysis. Fish. Res. Bd. Canada 167:310.
TD-10-AU-005-CE Field Fluorometer Operating Manual. Version 1.4. April 1999. Turner Designs, 845 West Maude Avenue, Sunnyvale, CA 94086.
EPA - Method 445.0. In Vitro Determination of Chlorophyll a and Pheophytin a in Marine and Freshwater Algae by Fluorescence.
Using the Turner Designs Model 10 Analog, The 10AU Digital, Or the TD-700 Fluorometer with EPA Method 445.0. January 19, 1999. Turner Designs, 845 West Maude Avenue, Sunnyvale, CA 94086.
A Procedure For Measuring Extracted Chlorophyll a Free From The Errors Associated With Chlorophyll b and Pheopigments. Turner Designs, 845 West Maude Avenue, Sunnyvale, CA 94086. This method was developed by Dr. Nicholas A. Welschmeyer of

Moss Landing Marine Laboratories, Moss Landing, CA. A paper by Dr. Welschmeyer, Fluorometric Analysis of Chlorophyll a in the presence of Chlorophyll b and Pheopigments, which details his research, appears in Limnology and Oceanography (June 1994).

Method Description:

Instrumentation: Turner Designs 10-AU-005-CE Field fluorometer.

The Chl-a processing methodology here at the Wells NERR Research Laboratory follows the non-acidification method, “A Procedure For Measuring Extracted Chlorophyll a Free From The Errors Associated With Chlorophyll b and Pheopigments”, adapted from the EPA Method 445.0: “In Vitro Determination of Chlorophyll a and Pheophytin a in Marine and Freshwater Algae by Fluorescence.” The method used requires filtering a known quantity of water through a glass fiber filter (47 mm GF/F). The sample is steeped in 90% acetone at least 2 hours and not exceeding 24 hours at 4oC, in the dark. The samples are centrifuged and read on the fluorometer. If the samples cannot be read within that time period, they are stored in the research freezer.

Preservation Method:

This methodology includes filtering 600-1000 ml of a sample through 47 mm Whatman® GF/F filters using a vacuum pump and filter flask apparatus. The Whatman type GF/F filter is either folded immediately after sample filtering, enclosed in a waxine envelope, placed in a petri dish, wrapped with aluminum foil, placed in a sealed freezer bag, and placed in the freezer until it is ready for analysis, or directly placed in 90% acetone for 2-24 hours for immediate analysis. The final concentration of Chl-a = $(F \times v)/V$; where F = the direct fluorescence reading, v = volume of the extract, and V = volume of sample filtered.

14. Reporting of Missing Data and Data with Concentrations Lower than Method Detection Limits (MDL)

Nutrient/Chla comment codes and definitions are provided in the following table. Missing data are denoted by a blank cell “ ” and commented coded with an “M”. Laboratories in the NERRS System submit data that are censored at a lower detection rate limit, called the Method Detection Limit or MDL. MDL’s for specific parameters are listed in the Laboratory Methods and Detection Limits Section (Section II, Part 14) of this document. Measured concentrations that are less than this limit are replaced with the minimum detection limit value and comment coded with a “B” in the variable code comment column. For example, the measured concentration of NO₃F was 0.0005 mg/L as N (MDL=0.0008), the reported value would be 0.0008 with a “B” placed in the NO₃F comment code column. Calculated parameters are comment coded with a “C” and if any of the components used in the calculation are below the MDL, the calculated value is removed and also comment coded with a “B”. If a calculated value is negative, the value is removed and comment coded with an “N”.

Note: The way below MDL values are handled in the NERRS SWMP dataset was changed in November of 2011. Previously, below MDL data from 2002-2006 were also

coded with a B, but replaced with -9999 place holders. Any 2002-2006 nutrient/pigment data downloaded from the CDMO prior to December November of 2011 will contain -9999s representing below MDL concentrations.

Comment Code	Definition
A	Value above upper limit of method detection
B	Value below method detection limit
C	Calculated value
D	Data deleted or calculated value could not be determined due to deleted data, see metadata for details
H	Sample held beyond specified holding time
K	Check metadata for further details
M	Data missing, sample never collected or calculated value could not be determined due to missing data
P	Significant precipitation (≥ 0.25 inches occurred within 24 hours of sampling, ≥ 0.5 inches within 48 hours of sampling, and ≥ 0.75 inches occurred within 72 hours of sampling)
U	Lab analysis from unpreserved sample
S	Data suspect, see metadata for further details

OPAL = University of New Hampshire Ocean Process Analysis Laboratory

VIMS = Virginia Institute of Marine Science

General note on samples processed at VIMS: These samples were transported multiple times. First they were transported to OPAL by Wells NERR staff in multiple trips throughout the year. Then in September 2004, they were retrieved from OPAL and brought back to Wells NERR by Wells NERR staff, and shipped to VIMS a few days later via overnight delivery. The samples remained frozen throughout all trips, except they thawed partially in their final delivery to VIMS, and were analyzed soon afterward.

January 2003 Notes

Ammonia, Nitrate, Nitrite and Orthophosphate conducted at UNH-OPAL lab.

Comment Code K for all January Samples: Times suspect for nutrient sampling on 1/9/2003.

The field record of nutrient sampling in January has been lost or was never made. For the purpose of data submission, time provided is an estimate based on the normal deployment time at 10:30 in the morning.

Missing nutrient data 1/9/2003.

Sites welhnut (Webhannet head of tide) and wellmnut (Little River Mouth) could not be sampled due to ice.

February 2003 Notes

Ammonia, Nitrate and Orthophosphate conducted at UNH-OPAL lab.
Nitrite conducted at VIMS lab.

Missing nutrient data:

welinnut 2/19/2003 22:30 to 2/20/2003 8:30

A problem occurred with the ISCO automatic water sampler program. After collecting 6 samples, intense cold froze the ocean water in the intake tube, blocking further sampling. As a result, only 6 diel samples (instead of the normal 12) were collected and analyzed.

Missing ammonium datum:

welinnut 2/19/2003 20:30

UNH Estuarine and Coastal Chemistry Laboratory indicated “analysis not good, need to rerun” with no follow up at the time of data submittal.

Missing nutrient data 2/20/2003.

Sites welhnut (Webhannet head of tide) and wellmnut (Little River Mouth) could not be sampled due to thick ice.

Holding time for nitrites at all sites, 2/19-20/2003.

Samples were processed at VIMS in February 2005.

March 2003 Notes

Ammonia and Nitrate conducted at UNH-OPAL lab.

Nitrite and Orthophosphate conducted at VIMS lab, except for wellmnut orthophosphate 3/26/2003 14:35 which was processed at UNH-OPAL.

Missing ammonium data:

welinnut 3/26/2003 9:22

UNH Estuarine and Coastal Chemistry Laboratory indicated “analysis not good, need to rerun” with no follow up at the time of writing.

Missing Nitrite data:

wellmnut 3/26/2003 14:35

Sample apparently lost after initial analysis at UNH Estuarine and Coastal Chemistry Laboratory.

Holding time for nitrites and orthophosphate at all sites 3/25-26/2003.

Samples were processed at VIMS in October 2004.

April 2003 Notes

Ammonia, Nitrate and Orthophosphate conducted at UNH-OPAL lab.

Nitrite conducted at VIMS lab.

Holding time for nitrites at all sites 4/21-22/2003.

Samples were processed at VIMS in February 2005.

May 2003 Notes

Ammonia, Nitrate and Orthophosphate conducted at UNH-OPAL lab.
Nitrite conducted at VIMS lab.

Missing phosphate data:

welhtnut 5/20/2003, 10:00 and 10:02.

UNH Estuarine and Coastal Chemistry Laboratory indicated “analysis not good, need to rerun” with no follow up at the time of writing.

Holding time for nitrites at all sites 5/19-20/2003.

Samples were processed at VIMS in February 2005.

June 2003 Notes

Ammonia, Nitrate and Orthophosphate conducted at UNH-OPAL lab.
Nitrite conducted at VIMS lab.

Missing phosphate data:

welinnut 6/18/2003 16:30

welinnut 9/19/2003 10:47

UNH Estuarine and Coastal Chemistry Laboratory indicated “analysis not good, need to rerun” with no follow up at the time of writing.

Missing ammonia data:

welinnut 6/19/2003 4:30

wellmnut 6/19/2003 12:07

UNH Estuarine and Coastal Chemistry Laboratory indicated that this sample demonstrated either atypically high levels or contamination, and was set aside to be re-processed later, with no follow up at the time of data submission.

Missing chlorophyll datum on 6/18/2003, 12:30

This sample lost due to spill during the filtering process.

Holding time for nitrites at all sites 6/18-19/2003.

Samples were processed at VIMS in February 2005.

July 2003 Notes

Ammonia, Nitrate and Orthophosphate conducted at UNH-OPAL lab.
Nitrite conducted at VIMS lab.

Holding time for nitrites at all sites 7/15-16/2003.

Samples were processed at VIMS in February 2005.

August 2003 Notes

Nitrate, Nitrite and Orthophosphate conducted at VIMS lab.

Calculated values for nitrate 8/20-21/2003.

Nitrite was calculated by subtracting nitrite from nitrate+nitrite.

Holding time for samples at all sites 8/20-21/2003.

Nitrites, nitrites, ammonia were processed at VIMS in October 2004.

Orthophosphate was processed at VIMS in March 2005.

September 2003 Notes

Calculated values for nitrate 9/29-30/2003.

Nitrite was calculated by subtracting nitrite from nitrate+nitrite.

Holding time for nitrites, nitrites, ammonia and orthophosphate at all sites 9/29-30/2003.

Samples were processed at VIMS in October 2004, except for

wellmnut 9/30/2003 11:29 orthophosphate and nitrate, which were processed at OPAL.

October 2003 Notes

Calculated values for nitrate 10/22-23/2003.

Nitrite was calculated by subtracting nitrite from nitrate+nitrite.

Holding time for nitrites, nitrites, ammonia and orthophosphate at all sites 10/22-23/2003.

Samples were processed at VIMS in October 2004.

November 2003 Notes

Calculated values for nitrate 11/19-20/2003.

Nitrite was calculated by subtracting nitrite from nitrate+nitrite.

Holding time for nitrites, nitrites, ammonia and orthophosphate at all sites 11/19-20/2003.

Samples were processed at VIMS in October 2004.

December 2003 Notes

Calculated values for nitrate 12/18-19/2003.

Nitrite was calculated by subtracting nitrite from nitrate+nitrite.

Holding time for nitrites, nitrites, ammonia and orthophosphate at all sites 12/18-19/2003.

Samples were processed at VIMS in October 2004.

15) QA/QC Programs

Precision:

Field Variability – True field replicates are taken at each site during grab sampling. Both replicate grabs are taken simultaneously.

Laboratory Variability – none

Inter-organizational splits – same samples were not split or analyzed by two different labs

Accuracy:

Sample Spikes – information unavailable

Standard Reference Material Analysis – see lab protocols

Cross Calibration Exercises – WNERR did not participate in cross calibration exercises.

16) Other Remarks

On 07/22/2025 this dataset was updated to include embedded QAQC flags and codes for anomalous/suspect, rejected, missing, and below detection limit data. System-wide monitoring data beginning in 2007 were processed to allow for QAQC flags and codes to be embedded in the data files rather than using the original single letter codes used for the nutrient and pigment dataset along with the detailed sections in the metadata document for suspect, missing, and rejected data. Please note that prior to 2007, rejected data were deleted from the dataset so they are unavailable to be used at all. Suspect, missing, rejected and below minimum detection flags and appropriate three letter codes were embedded retroactively for dataset consistency. The QAQC flag/codes corresponding to the original letter codes are detailed below.

Flag/code	If also C	Historic Letter Code	Historic Code Definition
<1> [SUL]		A	Value above upper limit of method detection
<4> [SBL]	<4> [SCB]	B	Value below method detection limit
no need to flag/code unless combined		C	Calculated value
<3> [GCD]	<3> [GCR]	D	Data deleted or calculated value could not be determined due to deleted data, see metadata for details
<1> (CHB)		H	Sample held beyond specified holding time
<0> (CSM) unless other flag		K	Check metadata for further details
<2> [GDM]	<2> [GOM]	M	Data missing, sample never collected or calculated value could not be determined due to missing data
<3> [SNV] and <1> [SOC] for components (CRE) or F_Record (CRE)		N	Negative calculated value
<0> (CUS)		P	Significant precipitation (reserve defined, see metadata for further details)
<1> (CSM)		U	Lab analysis from unpreserved sample
		S	Data suspect, see metadata for further details

2003 Rain Events:

January

Date Rain Amount (mm)

6.858

3.302

0.762

1.778

0.254

1.016

0.254

3.556

1.016

0.254

Monthly Total 19.0

February

Date Rain Amount (mm)

3.810

27.432

7.366

3.048

0.508

1.016

1.016
2.032
20.574
14.478
Monthly Total 81.3

March
Date Rain Amount (mm)
26.924
6.096
2.032
2.032
5.334
22.606
3.302
0.508
8.382
18.542
0.254
Monthly Total 96.0

April
Date Rain Amount (mm)
2.540
2.540
3.556
5.588
0.254
12.192
1.016
0.762
10.160
5.080
3.302
32.512
0.254
Monthly Total 79.8

May
Date Rain Amount (mm)
0.254
1.524
2.540
3.302
3.048

9.144
9.144
2.794
1.778
7.112
0.254
6.858
4.064
30.226
0.254
0.254
1.270
2.540
Monthly Total 86.4

June
Date Rain Amount (mm)
16.256
6.350
3.556
1.778
3.048
7.874
4.826
2.286
1.270
6.350
1.524
0.508
Monthly Total 55.6

July
Date Rain Amount (mm)
0.762
0.254
10.160
15.240
0.508
0.762
13.970
2.032
1.270
Monthly Total 45.0

August
Date Rain Amount (mm)

27.940
10.160
2.794
11.938
0.254
4.318
5.842
5.080
0.254
1.524
0.254
31.750
2.032
Monthly Total 104.1

September

Date Rain Amount (mm)

0.254
6.858
0.254
31.496
0.254
33.782
0.254
10.668
26.924
7.874
0.508
2.032
0.508
Monthly Total 121.7

October

Date Rain Amount (mm)

0.762
11.938
0.254
0.254
23.114
41.402
1.524
5.080
22.860
1.524
34.290
Monthly Total 143.0

November

Date	Rain Amount (mm)
------	------------------

1.016	
-------	--

7.112	
-------	--

1.524	
-------	--

2.286	
-------	--

4.572	
-------	--

1.27	
------	--

0.508	
-------	--

1.016	
-------	--

10.668	
--------	--

5.334	
-------	--

Monthly Total	35.3
---------------	------

December

Date	Rain Amount (mm)
------	------------------

0.508	
-------	--

0.508	
-------	--

18.288	
--------	--

0.508	
-------	--

5.334	
-------	--

16.256	
--------	--

3.556	
-------	--

0.254	
-------	--

Monthly Total	45.2
---------------	------